

2890R-39H Information

Heisener.com

Part Number 2890R-39H

Manufacturer API Delevan Inc.

Category Inductors, Coils, Chokes

Fixed Inductors

Description FIXED IND 68UH 325MA 1.85 OHM TH

Package Axial

For the pricing/inventory/lead time, please contact

us

For Reference Only Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









2890R-39H Specifications

Manufacturer API Delevan Inc. Category Inductors, Coils, Chokes Fixed Inductors Package Axial Series 2890R Type Molded Material - Core Iron Inductance 68μH Tolerance ±3% Current Rating 325mA Current - Saturation - Shielding Unshielded DC Resistance (DCR) 1.85 Ohm Max Q @ Freq 75 @ 2.5MHz Frequency - Self Resonant 13MHz	Manufacturer Part Number	2890R-39H
Fixed Inductors	Manufacturer	API Delevan Inc.
Package Axial Series 2890R Type Molded Material - Core Iron Inductance 68μH Tolerance ±3% Current Rating 325mA Current - Saturation - Shielding Unshielded DC Resistance (DCR) 1.85 Ohm Max Q @ Freq 75 @ 2.5MHz	Category	Inductors, Coils, Chokes
Series 2890R Type Molded Material - Core Iron Inductance 68μH Tolerance ±3% Current Rating 325mA Current - Saturation - Shielding Unshielded DC Resistance (DCR) 1.85 Ohm Max Q @ Freq 75 @ 2.5MHz		Fixed Inductors
Type Molded Material - Core Iron Inductance 68μH Tolerance ±3% Current Rating 325mA Current - Saturation - Shielding Unshielded DC Resistance (DCR) 1.85 Ohm Max Q @ Freq 75 @ 2.5MHz	Package	Axial
Material - Core Iron Inductance 68μH Tolerance ±3% Current Rating 325mA Current - Saturation - Shielding Unshielded DC Resistance (DCR) 1.85 Ohm Max Q @ Freq 75 @ 2.5MHz	Series	2890R
Inductance 68μH Tolerance ±3% Current Rating 325mA Current - Saturation - Shielding Unshielded DC Resistance (DCR) 1.85 Ohm Max Q @ Freq 75 @ 2.5MHz	Туре	Molded
Tolerance ±3% Current Rating 325mA Current - Saturation - Shielding Unshielded DC Resistance (DCR) 1.85 Ohm Max Q @ Freq 75 @ 2.5MHz	Material - Core	Iron
Current Rating 325mA Current - Saturation - Shielding Unshielded DC Resistance (DCR) 1.85 Ohm Max Q @ Freq 75 @ 2.5MHz	Inductance	68μΗ
Current - Saturation - Shielding Unshielded DC Resistance (DCR) 1.85 Ohm Max Q @ Freq 75 @ 2.5MHz	Tolerance	±3%
Shielding DC Resistance (DCR) 1.85 Ohm Max Q @ Freq 75 @ 2.5MHz	Current Rating	325mA
DC Resistance (DCR) Q @ Freq 1.85 Ohm Max 75 @ 2.5MHz	Current - Saturation	-
Q @ Freq 75 @ 2.5MHz	Shielding	Unshielded
	DC Resistance (DCR)	1.85 Ohm Max
Frequency - Self Resonant 13MHz	Q @ Freq	75 @ 2.5MHz
A Y	Frequency - Self Resonant	13MHz
Ratings -	Ratings	-
Operating Temperature $-55^{\circ}\text{C} \sim 105^{\circ}\text{C}$	Operating Temperature	-55°C ~ 105°C
Frequency - Test 2.5MHz	Frequency - Test	2.5MHz
Features -	Features	-
Mounting Type Through Hole	Mounting Type	Through Hole
Package / Case Axial	Package / Case	Axial
Supplier Device Package -	Supplier Device Package	-
Size / Dimension 0.280" Dia x 0.900" L (7.11mm x 22.86mm)	Size / Dimension	0.280" Dia x 0.900" L (7.11mm x 22.86mm)

Height - Seated (Max) Report errors?

2890R-39H Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

2890R-39H Payment Methods



















2890R-39H Shipping Methods













If you have any question about 2890R-39H, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com