

## 2902994 Information



For Reference Only

Part Number 2902994

Manufacturer Phoenix Contact

Category Power Supplies - External/Internal (Off-Board)

AC DC Converters

**Description** AC/DC CONVERTER 24V 90W

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# 2902994 Specifications

Manufacturer Part Number         2902994           Manufacturer         Phoenix Contact           Category         Power Supplies - External/Internal (Off-Board)           AC DC Converters           Package         -           Series         UNO           Type         Enclosed           Number of Outputs         1           Voltage - Input         85 ~ 264 VAC           Voltage - Output 1         24V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         3.75A           Power (Watts)         90W           Applications         ITE (Commercial)           Voltage - Isolation         4kV (4000V)
Category         Power Supplies - External/Internal (Off-Board)           AC DC Converters           Package         -           Series         UNO           Type         Enclosed           Number of Outputs         1           Voltage - Input         85 ~ 264 VAC           Voltage - Output 1         24V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         3.75A           Power (Watts)         90W           Applications         ITE (Commercial)
AC DC Converters           Package         -           Series         UNO           Type         Enclosed           Number of Outputs         1           Voltage - Input         85 ~ 264 VAC           Voltage - Output 1         24V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         3.75A           Power (Watts)         90W           Applications         ITE (Commercial)
Package         -           Series         UNO           Type         Enclosed           Number of Outputs         1           Voltage - Input         85 ~ 264 VAC           Voltage - Output 1         24V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         3.75A           Power (Watts)         90W           Applications         ITE (Commercial)
Series         UNO           Type         Enclosed           Number of Outputs         1           Voltage - Input         85 ~ 264 VAC           Voltage - Output 1         24V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         3.75A           Power (Watts)         90W           Applications         ITE (Commercial)
Type Enclosed  Number of Outputs 1  Voltage - Input 85 ~ 264 VAC  Voltage - Output 1 24V  Voltage - Output 2 -  Voltage - Output 3 -  Voltage - Output 4 -  Current - Output (Max) 3.75A  Power (Watts) 90W  Applications ITE (Commercial)
Number of Outputs       1         Voltage - Input       85 ~ 264 VAC         Voltage - Output 1       24V         Voltage - Output 2       -         Voltage - Output 3       -         Voltage - Output 4       -         Current - Output (Max)       3.75A         Power (Watts)       90W         Applications       ITE (Commercial)
Voltage - Input  85 ~ 264 VAC  Voltage - Output 1  24V  Voltage - Output 2  - Voltage - Output 3  - Voltage - Output 4  - Current - Output (Max)  Power (Watts)  Applications  85 ~ 264 VAC  24V  -  Curent - Output 2  -  ITE (Commercial)
Voltage - Output 1  Voltage - Output 2  - Voltage - Output 3  Voltage - Output 4  - Current - Output (Max)  Power (Watts)  Applications  24V  -  Cuthout 2  -  ITE (Commercial)
Voltage - Output 2  Voltage - Output 3  - Voltage - Output 4  - Current - Output (Max)  Power (Watts)  Applications  -  Control - Output (Max)  ITE (Commercial)
Voltage - Output 3  Voltage - Output 4  - Current - Output (Max)  Power (Watts)  Applications  - Voltage - Output 4  - Current - Output (Max)  ITE (Commercial)
Voltage - Output 4 - Current - Output (Max) 3.75A Power (Watts) 90W Applications ITE (Commercial)
Current - Output (Max)  Power (Watts)  Applications  3.75A  90W  ITE (Commercial)
Power (Watts) 90W Applications ITE (Commercial)
Applications ITE (Commercial)
Voltage Igolation AkV (4000V)
Voltage - Isolation 44 V (4000 V)
Efficiency 86%
Operating Temperature $-25^{\circ}\text{C} \sim 70^{\circ}\text{C}$ (With Derating)
Features IP20, Universal Input
Mounting Type DIN Rail
Size / Dimension 3.31" L x 2.17" W x 3.54" H (84.0mm x 55.0mm x 90.0mm)
Report error

#### 2902994 Guarantees



### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## 2902994 Payment Methods





















## 2902994 Shipping Methods













If you have any question about 2902994, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com