

293387-2 Information



For Reference Only

Part Number 293387-2

Manufacturer TE Connectivity AMP Connectors

Category Connectors, Interconnects

Solid State Lighting Connectors

Description CONN SSL OUTLET HSG 2POS 3.6MM

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









293387-2 Specifications

| Manufacturer Part Number 293387-2 Manufacturer TE Connectivity AMP Connectors Category Connectors, Interconnects Package - Series Nector S Style Cable/Wire to Cable/Wire or Board Connector Type Outlet Housing for Pin Contact Number of Positions 2 Mounting Type Free Hanging (In-Line) Termination Crimp Pitch 0.142" (3.60mm) Fastening Type - Features Keying HV-4 Housing Color White Wire Gauge - Contact Material - Contact Finish - Housing Material Polybutylene Terephthalate (PBT), Glass Filled Operating Temperature -40°C ~ 120°C | | |
|--|--------------------------|--|
| Category Connectors, Interconnects Solid State Lighting Connectors Package - Series Nector S Style Cable/Wire to Cable/Wire or Board Connector Type Outlet Housing for Pin Contact Number of Positions 2 Mounting Type Free Hanging (In-Line) Termination Crimp Pitch 0.142" (3.60mm) Fastening Type - Features Keying HV-4 Housing Color White Wire Gauge Contact Material Contact Finish - Housing Material Operating Temperature -40°C ~ 120°C | Manufacturer Part Number | 293387-2 |
| Solid State Lighting Connectors Package Series Nector S Style Cable/Wire to Cable/Wire or Board Connector Type Outlet Housing for Pin Contact Number of Positions 2 Mounting Type Free Hanging (In-Line) Termination Crimp Pitch 0.142" (3.60mm) Fastening Type - Features Keying HV-4 Housing Color White Wire Gauge Contact Material Contact Finish Housing Material Polybutylene Terephthalate (PBT), Glass Filled Operating Temperature | Manufacturer | TE Connectivity AMP Connectors |
| Package - Series Nector S Style Cable/Wire to Cable/Wire or Board Connector Type Outlet Housing for Pin Contact Number of Positions 2 Mounting Type Free Hanging (In-Line) Termination Crimp Pitch 0.142" (3.60mm) Fastening Type - Features Keying HV-4 Housing Color White Wire Gauge - Contact Material - Contact Finish - Housing Material Polybutylene Terephthalate (PBT), Glass Filled Operating Temperature -40°C ~ 120°C | Category | Connectors, Interconnects |
| Series Nector S Style Cable/Wire to Cable/Wire or Board Connector Type Outlet Housing for Pin Contact Number of Positions 2 Mounting Type Free Hanging (In-Line) Termination Crimp Pitch 0.142" (3.60mm) Fastening Type - Features Keying HV-4 Housing Color White Wire Gauge - Contact Material - Contact Finish - Housing Material Polybutylene Terephthalate (PBT), Glass Filled Operating Temperature -40°C ~ 120°C | | Solid State Lighting Connectors |
| Style Cable/Wire to Cable/Wire or Board Connector Type Outlet Housing for Pin Contact Number of Positions 2 Mounting Type Free Hanging (In-Line) Termination Crimp Pitch 0.142" (3.60mm) Fastening Type - Features Keying HV-4 Housing Color White Wire Gauge - Contact Material - Contact Finish - Housing Material Polybutylene Terephthalate (PBT), Glass Filled Operating Temperature -40°C ~ 120°C | Package | - |
| Connector Type Number of Positions 2 Mounting Type Free Hanging (In-Line) Termination Crimp Pitch 0.142" (3.60mm) Fastening Type - Features Keying HV-4 Housing Color White Wire Gauge Contact Material Contact Finish Housing Material Operating Temperature Outlet Housing for Pin Contact Evaluation Crimp 0.142" (3.60mm) - Contact Finish - Housing Material Polybutylene Terephthalate (PBT), Glass Filled -40°C ~ 120°C | Series | Nector S |
| Number of Positions2Mounting TypeFree Hanging (In-Line)TerminationCrimpPitch0.142" (3.60mm)Fastening Type-FeaturesKeying HV-4Housing ColorWhiteWire Gauge-Contact Material-Contact Finish-Housing MaterialPolybutylene Terephthalate (PBT), Glass FilledOperating Temperature-40°C ~ 120°C | Style | Cable/Wire to Cable/Wire or Board |
| Mounting Type Free Hanging (In-Line) Termination Crimp Pitch 0.142" (3.60mm) Fastening Type - Features Keying HV-4 Housing Color White Wire Gauge - Contact Material - Contact Finish - Housing Material Polybutylene Terephthalate (PBT), Glass Filled Operating Temperature -40°C ~ 120°C | Connector Type | Outlet Housing for Pin Contact |
| Termination Crimp Pitch 0.142" (3.60mm) Fastening Type - Features Keying HV-4 Housing Color White Wire Gauge - Contact Material - Contact Finish - Housing Material Polybutylene Terephthalate (PBT), Glass Filled Operating Temperature -40°C ~ 120°C | Number of Positions | 2 |
| Pitch 0.142" (3.60mm) Fastening Type - Features Keying HV-4 Housing Color White Wire Gauge - Contact Material - Contact Finish - Housing Material Polybutylene Terephthalate (PBT), Glass Filled Operating Temperature -40°C ~ 120°C | Mounting Type | Free Hanging (In-Line) |
| Fastening Type - Features Keying HV-4 Housing Color White Wire Gauge - Contact Material - Contact Finish - Housing Material Polybutylene Terephthalate (PBT), Glass Filled Operating Temperature -40°C ~ 120°C | Termination | Crimp |
| Features Keying HV-4 Housing Color White Wire Gauge - Contact Material - Contact Finish - Housing Material Polybutylene Terephthalate (PBT), Glass Filled Operating Temperature -40°C ~ 120°C | Pitch | 0.142" (3.60mm) |
| Housing Color White Wire Gauge Contact Material Contact Finish Housing Material Polybutylene Terephthalate (PBT), Glass Filled Operating Temperature -40°C ~ 120°C | Fastening Type | - |
| Wire Gauge Contact Material Contact Finish Housing Material Operating Temperature Polybutylene Terephthalate (PBT), Glass Filled -40°C ~ 120°C | Features | Keying HV-4 |
| Contact Material - Contact Finish - Housing Material Polybutylene Terephthalate (PBT), Glass Filled Operating Temperature -40°C ~ 120°C | Housing Color | White |
| Contact Finish Housing Material Polybutylene Terephthalate (PBT), Glass Filled Operating Temperature -40°C ~ 120°C | Wire Gauge | - |
| Housing Material Polybutylene Terephthalate (PBT), Glass Filled Operating Temperature $-40^{\circ}\text{C} \sim 120^{\circ}\text{C}$ | Contact Material | - |
| Operating Temperature $-40^{\circ}\text{C} \sim 120^{\circ}\text{C}$ | Contact Finish | - |
| | Housing Material | Polybutylene Terephthalate (PBT), Glass Filled |
| Report errors? | Operating Temperature | -40°C ~ 120°C |
| | | Report errors? |

293387-2 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

293387-2 Payment Methods



















293387-2 Shipping Methods













If you have any question about 293387-2, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com