

### 293387-4 Information

www.heisener.com

**Part Number** 293387-4

Manufacturer TE Connectivity AMP Connectors

Category Connectors, Interconnects

Solid State Lighting Connectors

**Description** CONN SSL OUTLET HSG 2POS 3.6MM

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# 293387-4 Specifications

Manufacturer Part Number       293387-4         Manufacturer       TE Connectivity AMP Connectors         Category       Connectors, Interconnects         Solid State Lighting Connectors         Package       -         Series       Nector S         Style       Cable/Wire to Cable/Wire or Board         Connector Type       Outlet Housing for Pin Contact         Number of Positions       2         Mounting Type       Free Hanging (In-Line)         Termination       Crimp         Pitch       0.142" (3.60mm)         Fastening Type       -         Features       Keying LV-2         Housing Color       White         Wire Gauge       -         Contact Material       -         Contact Finish       -         Housing Material       Polybutylene Terephthalate (PBT), Glass Filled         Operating Temperature       -40°C ~ 120°C	•	
Category Connectors, Interconnects Solid State Lighting Connectors  Package - Series Nector S Style Cable/Wire to Cable/Wire or Board Connector Type Outlet Housing for Pin Contact Number of Positions 2 Mounting Type Free Hanging (In-Line)  Termination Crimp Pitch 0.142" (3.60mm)  Fastening Type - Features Keying LV-2 Housing Color White Wire Gauge Contact Material - Contact Finish - Housing Material Operating Temperature -40°C ~ 120°C	Manufacturer Part Number	293387-4
Solid State Lighting Connectors  Package - Series Nector S  Style Cable/Wire to Cable/Wire or Board  Connector Type Outlet Housing for Pin Contact  Number of Positions 2 Mounting Type Free Hanging (In-Line)  Termination Crimp Pitch 0.142" (3.60mm)  Fastening Type - Features Keying LV-2  Housing Color White  Wire Gauge Contact Material Contact Finish - Housing Material Polybutylene Terephthalate (PBT), Glass Filled Operating Temperature	Manufacturer	TE Connectivity AMP Connectors
Package - Series Nector S  Style Cable/Wire to Cable/Wire or Board Connector Type Outlet Housing for Pin Contact  Number of Positions 2  Mounting Type Free Hanging (In-Line)  Termination Crimp  Pitch 0.142" (3.60mm)  Fastening Type - Features Keying LV-2  Housing Color White  Wire Gauge - Contact Material - Contact Finish - Housing Material Polybutylene Terephthalate (PBT), Glass Filled Operating Temperature -40°C ~ 120°C	Category	Connectors, Interconnects
Series Nector S Style Cable/Wire to Cable/Wire or Board Connector Type Outlet Housing for Pin Contact Number of Positions 2 Mounting Type Free Hanging (In-Line) Termination Crimp Pitch 0.142" (3.60mm) Fastening Type - Features Keying LV-2 Housing Color White Wire Gauge - Contact Material - Contact Finish - Housing Material Polybutylene Terephthalate (PBT), Glass Filled Operating Temperature -40°C ~ 120°C		Solid State Lighting Connectors
Style Cable/Wire to Cable/Wire or Board Connector Type Outlet Housing for Pin Contact  Number of Positions 2  Mounting Type Free Hanging (In-Line)  Termination Crimp  Pitch 0.142" (3.60mm)  Fastening Type -  Features Keying LV-2  Housing Color White  Wire Gauge - Contact Material - Contact Finish - Housing Material Polybutylene Terephthalate (PBT), Glass Filled Operating Temperature -40°C ~ 120°C	Package	-
Connector Type  Number of Positions  2  Mounting Type Free Hanging (In-Line)  Termination Crimp  Pitch 0.142" (3.60mm)  Fastening Type - Features Keying LV-2  Housing Color White  Wire Gauge Contact Material Contact Finish Housing Material Operating Temperature Outlet Housing for Pin Contact  Read Housing (In-Line)  Free Hanging (In-Line)  Crimp  0.142" (3.60mm)  -  -  -  -  -  -  -  -  -  -  -  -  -	Series	Nector S
Number of Positions2Mounting TypeFree Hanging (In-Line)TerminationCrimpPitch0.142" (3.60mm)Fastening Type-FeaturesKeying LV-2Housing ColorWhiteWire Gauge-Contact Material-Contact Finish-Housing MaterialPolybutylene Terephthalate (PBT), Glass FilledOperating Temperature-40°C ~ 120°C	Style	Cable/Wire to Cable/Wire or Board
Mounting Type Free Hanging (In-Line)  Termination Crimp  Pitch 0.142" (3.60mm)  Fastening Type -  Features Keying LV-2  Housing Color White  Wire Gauge -  Contact Material -  Contact Finish -  Housing Material Polybutylene Terephthalate (PBT), Glass Filled  Operating Temperature -40°C ~ 120°C	Connector Type	Outlet Housing for Pin Contact
Termination Crimp  Pitch 0.142" (3.60mm)  Fastening Type -  Features Keying LV-2  Housing Color White  Wire Gauge -  Contact Material -  Contact Finish -  Housing Material Polybutylene Terephthalate (PBT), Glass Filled  Operating Temperature -40°C ~ 120°C	Number of Positions	2
Pitch 0.142" (3.60mm)  Fastening Type - Features Keying LV-2  Housing Color White  Wire Gauge - Contact Material - Contact Finish - Housing Material Polybutylene Terephthalate (PBT), Glass Filled Operating Temperature -40°C ~ 120°C	Mounting Type	Free Hanging (In-Line)
Fastening Type - Features Keying LV-2 Housing Color White Wire Gauge - Contact Material - Contact Finish - Housing Material Polybutylene Terephthalate (PBT), Glass Filled Operating Temperature -40°C ~ 120°C	Termination	Crimp
Features Keying LV-2 Housing Color White Wire Gauge - Contact Material - Contact Finish - Housing Material Polybutylene Terephthalate (PBT), Glass Filled Operating Temperature -40°C ~ 120°C	Pitch	0.142" (3.60mm)
Housing Color  White  Wire Gauge  Contact Material  Contact Finish  Housing Material  Polybutylene Terephthalate (PBT), Glass Filled  Operating Temperature  -40°C ~ 120°C	Fastening Type	-
	Features	Keying LV-2
Contact Material - Contact Finish - Housing Material Polybutylene Terephthalate (PBT), Glass Filled Operating Temperature -40°C ~ 120°C	Housing Color	White
Contact Finish - Housing Material Polybutylene Terephthalate (PBT), Glass Filled Operating Temperature $-40^{\circ}\text{C} \sim 120^{\circ}\text{C}$	Wire Gauge	-
Housing Material Polybutylene Terephthalate (PBT), Glass Filled Operating Temperature $-40^{\circ}\text{C} \sim 120^{\circ}\text{C}$	Contact Material	-
Operating Temperature $-40^{\circ}\text{C} \sim 120^{\circ}\text{C}$	Contact Finish	-
	Housing Material	Polybutylene Terephthalate (PBT), Glass Filled
Report errors?	Operating Temperature	-40°C ~ 120°C
		Report errors?

### 293387-4 Guarantees



### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## 293387-4 Payment Methods

































If you have any question about 293387-4, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com