

293703-2 Information



For Reference Only

Part Number 293703-2

Manufacturer TE Connectivity AMP Connectors

Category Connectors, Interconnects

Solid State Lighting Connectors

Description CONN SSL RCPT HSG 4POS CRIMP

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









293703-2 Specifications

Manufacturer Part Number 293703-2 Manufacturer TE Connectivity AMP Connectors Category Connectors, Interconnects Package - Series Nector S Style Cable/Wire to Cable/Wire or Board Connector Type Receptacle Housing for Pin Contact Number of Positions 4 Mounting Type Free Hanging (In-Line) Termination Crimp Pitch - Fastening Type - Features - Housing Color Black Wire Gauge - Contact Material - Contact Finish - Housing Material Polybutylene Terephthalate (PBT), Glass Filled Operating Temperature -40°C ~ 120°C	•	
Category Connectors, Interconnects Solid State Lighting Connectors Package - Series Nector S Style Cable/Wire to Cable/Wire or Board Connector Type Receptacle Housing for Pin Contact Number of Positions 4 Mounting Type Free Hanging (In-Line) Termination Crimp Pitch - Fastening Type - Features - Housing Color Black Wire Gauge Contact Material Contact Finish - Housing Material Operating Temperature - 40°C ~ 120°C	Manufacturer Part Number	293703-2
Package-SeriesNector SStyleCable/Wire to Cable/Wire or BoardConnector TypeReceptacle Housing for Pin ContactNumber of Positions4Mounting TypeFree Hanging (In-Line)TerminationCrimpPitch-Fastening Type-Features-Housing ColorBlackWire Gauge-Contact Material-Contact Finish-Housing MaterialPolybutylene Terephthalate (PBT), Glass FilledOperating Temperature-40°C ~ 120°C	Manufacturer	TE Connectivity AMP Connectors
Package - Nector S Style Cable/Wire to Cable/Wire or Board Connector Type Receptacle Housing for Pin Contact Number of Positions 4 Mounting Type Free Hanging (In-Line) Termination Crimp Pitch Fastening Type Features Housing Color Black Wire Gauge - Contact Material Contact Material - Contact Material Contact Finish - Polybutylene Terephthalate (PBT), Glass Filled Operating Temperature -40°C ~ 120°C	Category	Connectors, Interconnects
Series Nector S Style Cable/Wire to Cable/Wire or Board Connector Type Receptacle Housing for Pin Contact Number of Positions 4 Mounting Type Free Hanging (In-Line) Termination Crimp Pitch - Fastening Type - Features - Housing Color Black Wire Gauge - Contact Material - Contact Finish - Housing Material Polybutylene Terephthalate (PBT), Glass Filled Operating Temperature - Nector S Receptacle Housing for Pin Contact 4 Cable/Wire or Board 4 Cable/Wire or Board 4 Cable/Wire or Board 4 Coring Free Hanging (In-Line) - Corimp - Corimp - Polybutylene Terephthalate (PBT), Glass Filled		Solid State Lighting Connectors
Style Cable/Wire to Cable/Wire or Board Connector Type Receptacle Housing for Pin Contact Number of Positions 4 Mounting Type Free Hanging (In-Line) Termination Crimp Pitch - Fastening Type - Features - Housing Color Black Wire Gauge - Contact Material - Contact Finish - Housing Material Polybutylene Terephthalate (PBT), Glass Filled Operating Temperature -40°C ~ 120°C	Package	-
Connector TypeReceptacle Housing for Pin ContactNumber of Positions4Mounting TypeFree Hanging (In-Line)TerminationCrimpPitch-Fastening Type-Features-Housing ColorBlackWire Gauge-Contact Material-Contact Finish-Housing MaterialPolybutylene Terephthalate (PBT), Glass FilledOperating Temperature-40°C ~ 120°C	Series	Nector S
Number of Positions4Mounting TypeFree Hanging (In-Line)TerminationCrimpPitch-Fastening Type-Features-Housing ColorBlackWire Gauge-Contact Material-Contact Finish-Housing MaterialPolybutylene Terephthalate (PBT), Glass FilledOperating Temperature-40°C ~ 120°C	Style	Cable/Wire to Cable/Wire or Board
Mounting TypeFree Hanging (In-Line)TerminationCrimpPitch-Fastening Type-Features-Housing ColorBlackWire Gauge-Contact Material-Contact Finish-Housing MaterialPolybutylene Terephthalate (PBT), Glass FilledOperating Temperature-40°C ~ 120°C	Connector Type	Receptacle Housing for Pin Contact
Termination Crimp Pitch - Fastening Type - Features - Housing Color Black Wire Gauge - Contact Material - Contact Finish - Housing Material Polybutylene Terephthalate (PBT), Glass Filled Operating Temperature - Crimp - Crimp - Crimp - Polybutylene Terephthalate (PBT), Glass Filled -40°C ~ 120°C	Number of Positions	4
Pitch - Fastening Type - Features - Housing Color Black Wire Gauge - Contact Material - Contact Finish - Housing Material Polybutylene Terephthalate (PBT), Glass Filled Operating Temperature -40°C ~ 120°C	Mounting Type	Free Hanging (In-Line)
Fastening Type Features Housing Color Black Wire Gauge Contact Material Contact Finish Housing Material Polybutylene Terephthalate (PBT), Glass Filled Operating Temperature	Termination	Crimp
Features - Housing Color Black Wire Gauge - Contact Material - Contact Finish - Housing Material Polybutylene Terephthalate (PBT), Glass Filled Operating Temperature -40°C ~ 120°C	Pitch	-
Housing Color Wire Gauge Contact Material Contact Finish Housing Material Polybutylene Terephthalate (PBT), Glass Filled Operating Temperature Polybutylene Terephthalate (PBT), Glass Filled	Fastening Type	-
Wire Gauge Contact Material Contact Finish Housing Material Operating Temperature Polybutylene Terephthalate (PBT), Glass Filled -40°C ~ 120°C	Features	-
Contact Material - Contact Finish - Housing Material Polybutylene Terephthalate (PBT), Glass Filled Operating Temperature -40°C ~ 120°C	Housing Color	Black
Contact Finish - Housing Material Polybutylene Terephthalate (PBT), Glass Filled Operating Temperature $-40^{\circ}\text{C} \sim 120^{\circ}\text{C}$	Wire Gauge	-
Housing Material Polybutylene Terephthalate (PBT), Glass Filled Operating Temperature $-40^{\circ}\text{C} \sim 120^{\circ}\text{C}$	Contact Material	-
Operating Temperature $-40^{\circ}\text{C} \sim 120^{\circ}\text{C}$	Contact Finish	-
	Housing Material	Polybutylene Terephthalate (PBT), Glass Filled
Report errors?	Operating Temperature	-40°C ~ 120°C
		Report errors?

293703-2 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

293703-2 Payment Methods





















293703-2 Shipping Methods













If you have any question about 293703-2, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com