

2938633 Information



For Reference Only

Part Number 2938633

Manufacturer Phoenix Contact

Category Power Supplies - External/Internal (Off-Board)

AC DC Converters

Description AC/DC CONVERTER 24V 720W

Package

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









2938633 Specifications

Manufacturer Part Number 2938633 Manufacturer Phoenix Contact Category Power Supplies - External/Internal (Off-Board) AC DC Converters Package - Series Quint Type Enclosed Number of Outputs 1 Voltage - Input 400 ~ 480 VAC Voltage - Output 1 24V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 30A Power (Watts) 720W Applications ITE (Commercial) Voltage - Isolation 4kV (4000V) Efficiency 92% Operating Temperature -25°C ~ 70°C (With Derating) Features Adjustable Output, DC Input Capable, IP20, Load Sharing, Universal Input Mounting Type DIN Rail Size / Dimension 5.12" L x 9.45" W x 5.12" H (130.0mm x 240.0mm x 130.0mm)			
Category Power Supplies - External/Internal (Off-Board) AC DC Converters Package - Series Quint Type Enclosed Number of Outputs 1 Voltage - Input 400 ~ 480 VAC Voltage - Output 1 24V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 30A Power (Watts) 720W Applications ITE (Commercial) Voltage - Isolation 4kV (4000V) Efficiency 92% Operating Temperature -25°C ~ 70°C (With Derating) Features Adjustable Output, DC Input Capable, IP20, Load Sharing, Universal Input Mounting Type DIN Rail Size / Dimension 5.12" L x 9.45" W x 5.12" H (130.0mm x 240.0mm x 130.0mm)	Manufacturer Part Number	2938633	
Package - Series Quint Type Enclosed Number of Outputs 1 Voltage - Input 400 ~ 480 VAC Voltage - Output 1 24V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 30A Power (Watts) 720W Applications ITE (Commercial) Voltage - Isolation 4kV (4000V) Efficiency 92% Operating Temperature -25°C ~ 70°C (With Derating) Features Adjustable Output, DC Input Capable, IP20, Load Sharing, Universal Input Mounting Type DIN Rail Size / Dimension 5.12" L x 9.45" W x 5.12" H (130.0mm x 240.0mm x 130.0mm)	Manufacturer	Phoenix Contact	
Package - Series Quint Type Enclosed Number of Outputs 1 Voltage - Input 400 ~ 480 VAC Voltage - Output 1 24V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 30A Power (Watts) 720W Applications ITE (Commercial) Voltage - Isolation 4kV (4000V) Efficiency 92% Operating Temperature -25°C ~ 70°C (With Derating) Features Adjustable Output, DC Input Capable, IP20, Load Sharing, Universal Input Mounting Type DIN Rail Size / Dimension 5.12" L x 9.45" W x 5.12" H (130.0mm x 240.0mm x 130.0mm)	Category	Power Supplies - External/Internal (Off-Board)	
Series Quint Type Enclosed Number of Outputs 1 Voltage - Input 400 ~ 480 VAC Voltage - Output 1 24V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 30A Power (Watts) 720W Applications ITE (Commercial) Voltage - Isolation 4kV (4000V) Efficiency 92% Operating Temperature -25°C ~ 70°C (With Derating) Features Adjustable Output, DC Input Capable, IP20, Load Sharing, Universal Input Mounting Type DIN Rail Size / Dimension 5.12" L x 9.45" W x 5.12" H (130.0mm x 240.0mm x 130.0mm)		AC DC Converters	
TypeEnclosedNumber of Outputs1Voltage - Input400 ~ 480 VACVoltage - Output 124VVoltage - Output 2-Voltage - Output 3-Voltage - Output 4-Current - Output (Max)30APower (Watts)720WApplicationsITE (Commercial)Voltage - Isolation4kV (4000V)Efficiency92%Operating Temperature-25°C ~ 70°C (With Derating)FeaturesAdjustable Output, DC Input Capable, IP20, Load Sharing, Universal InputMounting TypeDIN RailSize / Dimension5.12" L x 9.45" W x 5.12" H (130.0mm x 240.0mm x 130.0mm)	Package	-	
Number of Outputs Voltage - Input 400 ~ 480 VAC Voltage - Output 1 24V Voltage - Output 2 - Voltage - Output 3 Voltage - Output 4 - Current - Output (Max) Applications ITE (Commercial) Voltage - Isolation 4kV (4000V) Efficiency 92% Operating Temperature -25°C ~ 70°C (With Derating) Features Adjustable Output, DC Input Capable, IP20, Load Sharing, Universal Input Mounting Type Size / Dimension 5.12" L x 9.45" W x 5.12" H (130.0mm x 240.0mm x 130.0mm)	Series	Quint	
Voltage - Input400 ~ 480 VACVoltage - Output 124VVoltage - Output 2-Voltage - Output 3-Voltage - Output 4-Current - Output (Max)30APower (Watts)720WApplicationsITE (Commercial)Voltage - Isolation4kV (4000V)Efficiency92%Operating Temperature-25°C ~ 70°C (With Derating)FeaturesAdjustable Output, DC Input Capable, IP20, Load Sharing, Universal InputMounting TypeDIN RailSize / Dimension5.12" L x 9.45" W x 5.12" H (130.0mm x 240.0mm x 130.0mm)	Type	Enclosed	
Voltage - Output 2 Voltage - Output 3 Voltage - Output 4 Current - Output (Max) Applications Voltage - Isolation Voltage - Isolation Efficiency Operating Temperature Features Adjustable Output, DC Input Capable, IP20, Load Sharing, Universal Input Mounting Type DIN Rail Size / Dimension 24V 4V 4V 4V 4C Current - Output (Max) 30A 720W 72	Number of Outputs	1	
Voltage - Output 2 Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) Applications ITE (Commercial) Voltage - Isolation 4kV (4000V) Efficiency Operating Temperature -25°C ~ 70°C (With Derating) Features Adjustable Output, DC Input Capable, IP20, Load Sharing, Universal Input Mounting Type DIN Rail Size / Dimension 5.12" L x 9.45" W x 5.12" H (130.0mm x 240.0mm x 130.0mm)	Voltage - Input	400 ~ 480 VAC	
Voltage - Output 3 Voltage - Output 4 - Current - Output (Max) 30A Power (Watts) 720W Applications ITE (Commercial) Voltage - Isolation 4kV (4000V) Efficiency 92% Operating Temperature -25°C ~ 70°C (With Derating) Features Adjustable Output, DC Input Capable, IP20, Load Sharing, Universal Input Mounting Type DIN Rail Size / Dimension 5.12" L x 9.45" W x 5.12" H (130.0mm x 240.0mm x 130.0mm)	Voltage - Output 1	24V	
Voltage - Output 4 Current - Output (Max) Power (Watts) Applications ITE (Commercial) Voltage - Isolation 4kV (4000V) Efficiency 92% Operating Temperature -25°C ~ 70°C (With Derating) Features Adjustable Output, DC Input Capable, IP20, Load Sharing, Universal Input Mounting Type DIN Rail Size / Dimension 5.12" L x 9.45" W x 5.12" H (130.0mm x 240.0mm x 130.0mm)	Voltage - Output 2	-	
Current - Output (Max) Power (Watts) 720W Applications ITE (Commercial) Voltage - Isolation 4kV (4000V) Efficiency 92% Operating Temperature -25°C ~ 70°C (With Derating) Features Adjustable Output, DC Input Capable, IP20, Load Sharing, Universal Input Mounting Type DIN Rail Size / Dimension 5.12" L x 9.45" W x 5.12" H (130.0mm x 240.0mm x 130.0mm)	Voltage - Output 3	-	
Power (Watts) 720W Applications ITE (Commercial) Voltage - Isolation 4kV (4000V) Efficiency 92% Operating Temperature -25°C ~ 70°C (With Derating) Features Adjustable Output, DC Input Capable, IP20, Load Sharing, Universal Input Mounting Type DIN Rail Size / Dimension 5.12" L x 9.45" W x 5.12" H (130.0mm x 240.0mm x 130.0mm)	Voltage - Output 4	-	
Applications ITE (Commercial) Voltage - Isolation 4kV (4000V) Efficiency 92% Operating Temperature -25°C ~ 70°C (With Derating) Features Adjustable Output, DC Input Capable, IP20, Load Sharing, Universal Input Mounting Type DIN Rail Size / Dimension 5.12" L x 9.45" W x 5.12" H (130.0mm x 240.0mm x 130.0mm)	Current - Output (Max)	30A	
Voltage - Isolation 4kV (4000V) Efficiency 92% Operating Temperature -25°C ~ 70°C (With Derating) Features Adjustable Output, DC Input Capable, IP20, Load Sharing, Universal Input Mounting Type DIN Rail Size / Dimension 5.12" L x 9.45" W x 5.12" H (130.0mm x 240.0mm x 130.0mm)	Power (Watts)	720W	
Efficiency 92% Operating Temperature -25°C ~ 70°C (With Derating) Features Adjustable Output, DC Input Capable, IP20, Load Sharing, Universal Input Mounting Type DIN Rail Size / Dimension 5.12" L x 9.45" W x 5.12" H (130.0mm x 240.0mm x 130.0mm)	Applications	ITE (Commercial)	
Operating Temperature -25°C ~ 70°C (With Derating) Adjustable Output, DC Input Capable, IP20, Load Sharing, Universal Input Mounting Type DIN Rail Size / Dimension 5.12" L x 9.45" W x 5.12" H (130.0mm x 240.0mm x 130.0mm)	Voltage - Isolation	4kV (4000V)	
Features Adjustable Output, DC Input Capable, IP20, Load Sharing, Universal Input Mounting Type DIN Rail Size / Dimension 5.12" L x 9.45" W x 5.12" H (130.0mm x 240.0mm x 130.0mm)	Efficiency	92%	
Mounting Type DIN Rail Size / Dimension 5.12" L x 9.45" W x 5.12" H (130.0mm x 240.0mm x 130.0mm)	Operating Temperature	-25°C ~ 70°C (With Derating)	
Size / Dimension 5.12" L x 9.45" W x 5.12" H (130.0mm x 240.0mm x 130.0mm)	Features	Adjustable Output, DC Input Capable, IP20, Load Sharing, Universal Input	
	Mounting Type	DIN Rail	
Report errors?	Size / Dimension	5.12" L x 9.45" W x 5.12" H (130.0mm x 240.0mm x 130.0mm)	
			Report errors?

2938633 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

2938633 Payment Methods





















2938633 Shipping Methods













If you have any question about 2938633, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com