

### 2940171 Information

Pu.

For Reference Only

Part Number 2940171

Manufacturer Phoenix Contact

**Category** Relays

Power Relays, Over 2 Amps

**Description** RELAY GEN PURPOSE SPST 3A 24V

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# 2940171 Specifications

Manufacturer Part Number  Manufacturer  Phoenix Contact  Relays  Power Relays, Over 2 Amps  Package  Series  Relay Type  General Purpose  Coil Type  Non Latching  Coil Current  6.5mA  Coil Voltage  24VAC/DC  Contact Form  SPST-NO (1 Form A)  Contact Rating (Current)  3A  Switching Voltage  250VAC, 250VDC - Max  Turn On Voltage (Min)  Operate Time  Release Time  15ms  Features  Mounting Type  DIN Rail  Report errors?		
Category         Relays           Power Relays, Over 2 Amps         -           Package         -           Series         -           Relay Type         General Purpose           Coil Type         Non Latching           Coil Current         6.5mA           Coil Voltage         24VAC/DC           Contact Form         SPST-NO (1 Form A)           Contact Rating (Current)         3A           Switching Voltage         250VAC, 250VDC - Max           Turn On Voltage (Max)         -           Turn Off Voltage (Min)         -           Operate Time         5ms           Release Time         15ms           Features         -           Mounting Type         DIN Rail           Termination Style         Screw Terminal	Manufacturer Part Number	2940171
Power Relays, Over 2 Amps Package - Series - Relay Type General Purpose Coil Type Non Latching Coil Current 6.5mA Coil Voltage 24V AC/DC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 3A Switching Voltage 250VAC, 250VDC - Max Turn On Voltage (Max) - Turn Off Voltage (Min) Operate Time Spss - Sms Release Time 15ms Features - Mounting Type DIN Rail Termination Style Screw Terminal	Manufacturer	Phoenix Contact
Package - Series - Relay Type General Purpose General Purpose Non Latching Coil Type Non Latching 6.5mA Coil Voltage 24VAC/DC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 3A Switching Voltage 250VAC, 250VDC - Max Turn On Voltage (Max) - Turn Off Voltage (Min) - Operate Time 5ms Release Time 15ms Features - Mounting Type DIN Rail Termination Style Screw Terminal	Category	Relays
Series - General Purpose Coil Type Non Latching Coil Current 6.5mA Coil Voltage 24VAC/DC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 3A Switching Voltage 250VAC, 250VDC - Max Turn On Voltage (Max) - Turn Off Voltage (Min) Operate Time 5ms Release Time 15ms Features - Mounting Type DIN Rail Termination Style Screw Terminal		Power Relays, Over 2 Amps
Relay Type Coil Type Non Latching Coil Current 6.5mA Coil Voltage 24VAC/DC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 3A Switching Voltage 250VAC, 250VDC - Max Turn On Voltage (Max) - Turn Off Voltage (Min) Operate Time Sms Release Time 15ms Features Mounting Type DIN Rail Termination Style Screw Terminal	Package	-
Coil Type	Series	-
Coil Current Coil Voltage 24VAC/DC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 3A Switching Voltage 250VAC, 250VDC - Max Turn On Voltage (Max) Turn Off Voltage (Min) Operate Time 5ms Release Time 15ms Features - Mounting Type DIN Rail Termination Style Screw Terminal	Relay Type	General Purpose
Coil Voltage 24VAC/DC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 3A Switching Voltage 250VAC, 250VDC - Max Turn On Voltage (Max) - Turn Off Voltage (Min) - Operate Time 5ms Release Time 15ms Features - Mounting Type DIN Rail Termination Style Screw Terminal	Coil Type	Non Latching
Contact Form SPST-NO (1 Form A)  Contact Rating (Current) 3A  Switching Voltage 250VAC, 250VDC - Max  Turn On Voltage (Max) -  Turn Off Voltage (Min) -  Operate Time 5ms  Release Time 15ms  Features -  Mounting Type DIN Rail  Termination Style Screw Terminal	Coil Current	6.5mA
Contact Rating (Current)  Switching Voltage  250VAC, 250VDC - Max  Turn On Voltage (Max)  Turn Off Voltage (Min)  Operate Time  5ms  Release Time  15ms  Features  - Mounting Type  DIN Rail  Termination Style	Coil Voltage	24VAC/DC
Switching Voltage 250VAC, 250VDC - Max  Turn On Voltage (Max) -  Turn Off Voltage (Min) -  Operate Time 5ms  Release Time 15ms  Features -  Mounting Type DIN Rail  Termination Style Screw Terminal	Contact Form	SPST-NO (1 Form A)
Turn On Voltage (Max)  Turn Off Voltage (Min)  Operate Time  Sms  Release Time  15ms  Features  - Mounting Type  DIN Rail  Termination Style  Screw Terminal	Contact Rating (Current)	3A
Turn Off Voltage (Min)  Operate Time  Sms  Release Time  15ms  Features  Mounting Type  DIN Rail  Termination Style  Screw Terminal	Switching Voltage	250VAC, 250VDC - Max
Operate Time 5ms Release Time 15ms Features - Mounting Type DIN Rail Termination Style Screw Terminal	Turn On Voltage (Max)	-
Release Time 15ms  Features - Mounting Type DIN Rail Termination Style Screw Terminal	Turn Off Voltage (Min)	-
Features - Mounting Type DIN Rail Termination Style Screw Terminal	Operate Time	5ms
Mounting Type DIN Rail Termination Style Screw Terminal	Release Time	15ms
Termination Style Screw Terminal	Features	-
·	Mounting Type	DIN Rail
Report errors?	Termination Style	Screw Terminal
		Report errors?

#### 2940171 Guarantees



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## 2940171 Payment Methods





















### 2940171 Shipping Methods













If you have any question about 2940171, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com