

2963763 Information



For Reference Only

Part Number 2963763

Manufacturer Phoenix Contact

Category Relays

Power Relays, Over 2 Amps

Description RELAY SAFETY DPST 6A 24V

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









2963763 Specifications

Manufacturer Part Number 2963763 Manufacturer Phoenix Contact Category Relays Power Relays, Over 2 Amps Package - Series - Relay Type Safety Coil Type - Coil Current 140mA Coil Voltage 24VAC/DC Contact Form DPST (2 Form A) Contact Rating (Current) 6A Switching Voltage 250VAC, 250VDC - Max Turn On Voltage (Max) - Turn Off Voltage (Min) - Operate Time 100ms Release Time 45ms Features - Mounting Type DIN Rail Termination Style Screw Terminal		
Category Relays Power Relays, Over 2 Amps Package - Series - Relay Type Safety Coil Type - Coil Current 140mA Coil Voltage 24VAC/DC Contact Form DPST (2 Form A) Contact Rating (Current) 6A Switching Voltage 250VAC, 250VDC - Max Turn On Voltage (Max) - Turn Off Voltage (Min) - Operate Time 100ms Release Time 45ms Features - Mounting Type DIN Rail Termination Style Screw Terminal	Manufacturer Part Number	2963763
Package Series Relay Type Safety Coil Type Coil Current 140mA Coil Voltage 24VAC/DC Contact Form DPST (2 Form A) Contact Rating (Current) 6A Switching Voltage 250VAC, 250VDC - Max Turn On Voltage (Max) Turn Off Voltage (Min) Operate Time 100ms Release Time 45ms Features Mounting Type DIN Rail Termination Style Safety Safety Core Relays, Over 2 Amps In Core Relays Ove	Manufacturer	Phoenix Contact
Package - Series - Relay Type Safety Safety Coil Type - Coil Current 140mA Coil Voltage 24V AC/DC Contact Form DPST (2 Form A) Contact Rating (Current) 6A Switching Voltage 250V AC, 250V DC - Max Turn On Voltage (Max) - Turn Off Voltage (Min) - Operate Time 100ms Release Time 45ms Features - Mounting Type DIN Rail Termination Style Safety Safe	Category	Relays
Series-Relay TypeSafetyCoil Type-Coil Current140mACoil Voltage24VAC/DCContact FormDPST (2 Form A)Contact Rating (Current)6ASwitching Voltage250VAC, 250VDC - MaxTurn On Voltage (Max)-Turn Off Voltage (Min)-Operate Time100msRelease Time45msFeatures-Mounting TypeDIN RailTermination StyleScrew Terminal		Power Relays, Over 2 Amps
Relay Type Coil Type - Coil Current 140mA Coil Voltage 24VAC/DC Contact Form DPST (2 Form A) Contact Rating (Current) 6A Switching Voltage 250VAC, 250VDC - Max Turn On Voltage (Max) - Turn Off Voltage (Min) Operate Time 100ms Release Time 45ms Features Mounting Type DIN Rail Termination Style Safety Safety Safety Safety Safety 140mA 24VAC/DC A A DPST (2 Form A) 6A Suitching Voltage 250VAC, 250VDC - Max - DIN Rail Safety DIN Rail Screw Terminal	Package	-
Coil Type - Coil Current 140mA Coil Voltage 24VAC/DC Contact Form DPST (2 Form A) Contact Rating (Current) 6A Switching Voltage 250VAC, 250VDC - Max Turn On Voltage (Max) - Turn Off Voltage (Min) - Operate Time 100ms Release Time 45ms Features - Mounting Type DIN Rail Termination Style Screw Terminal	Series	-
Coil Current 140mA Coil Voltage 24VAC/DC Contact Form DPST (2 Form A) Contact Rating (Current) 6A Switching Voltage 250VAC, 250VDC - Max Turn On Voltage (Max) - Turn Off Voltage (Min) - Operate Time 100ms Release Time 45ms Features Mounting Type DIN Rail Termination Style Screw Terminal	Relay Type	Safety
Coil Voltage 24VAC/DC Contact Form DPST (2 Form A) Contact Rating (Current) 6A Switching Voltage 250VAC, 250VDC - Max Turn On Voltage (Max) - Turn Off Voltage (Min) - Operate Time 100ms Release Time 45ms Features - Mounting Type DIN Rail Termination Style Screw Terminal	Coil Type	-
Contact Form DPST (2 Form A) Contact Rating (Current) 6A Switching Voltage 250VAC, 250VDC - Max Turn On Voltage (Max) - Turn Off Voltage (Min) - Operate Time 100ms Release Time 45ms Features - Mounting Type DIN Rail Termination Style Screw Terminal	Coil Current	140mA
Contact Rating (Current) Switching Voltage 250VAC, 250VDC - Max Turn On Voltage (Max) - Turn Off Voltage (Min) Operate Time 100ms Release Time 45ms Features - Mounting Type DIN Rail Termination Style	Coil Voltage	24VAC/DC
Switching Voltage 250VAC, 250VDC - Max Turn On Voltage (Max) - Turn Off Voltage (Min) - Operate Time 100ms Release Time 45ms Features - Mounting Type DIN Rail Termination Style Screw Terminal	Contact Form	DPST (2 Form A)
Turn On Voltage (Max) Turn Off Voltage (Min) Operate Time 100ms Release Time 45ms Features - Mounting Type DIN Rail Termination Style	Contact Rating (Current)	6A
Turn Off Voltage (Min) Operate Time 100ms Release Time 45ms Features - Mounting Type DIN Rail Termination Style Screw Terminal	Switching Voltage	250VAC, 250VDC - Max
Operate Time 100ms Release Time 45ms Features - Mounting Type DIN Rail Termination Style Screw Terminal	Turn On Voltage (Max)	-
Release Time 45ms Features - Mounting Type DIN Rail Termination Style Screw Terminal	Turn Off Voltage (Min)	-
Features - DIN Rail Termination Style Screw Terminal	Operate Time	100ms
Mounting Type DIN Rail Termination Style Screw Terminal	Release Time	45ms
Termination Style Screw Terminal	Features	-
·	Mounting Type	DIN Rail
Report errors?	Termination Style	Screw Terminal
		Report errors?

2963763 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

2963763 Payment Methods





















2963763 Shipping Methods













If you have any question about 2963763, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com