

### 299-43-636-10-002000

#### 299-43-636-10-002000 Information

everw.heisener.com	 299-43-636-10-002000 Mill-Max Manufacturing Corp. Connectors, Interconnects Sockets for ICs, Transistors CONN IC DIP SOCKET 36POS GOLD - For the pricing/inventory/lead time, please contact us	
For Reference Only	Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

#### **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



#### 299-43-636-10-002000 Specifications

Manufacturer Part Number299-43-636-10-002000ManufacturerMill-Max Manufacturing Corp.CategoryConnectors, InterconnectsPackage-Package-Series299TypeDIP, 0.6" (15.24mm) Row SpacingNumber of Positions or Pins (Grid)36 (2 x 18)Pitch - MatingOl00" (2.54mm)Contact Finish - MatingGoldContact Finish Thickness - MatingBeryllium CopperMounting TypeThrough Hole, Right Angle, HorizontalFeaturesClosed FrameFeaturesSolderPitch - Post0.100" (2.54mm)Fireh - PostSolder
CategoryConnectors, InterconnectsCategorySockets for ICs, TransistorsPackage-Series299TypeDIP, 0.6" (15.24mm) Row SpacingNumber of Positions or Pins (Grid)36 (2 x 18)Pitch - Mating0.100" (2.54mm)Contact Finish - MatingGoldContact Finish Thickness - MatingBeryllium CopperMounting TypeThrough Hole, Right Angle, HorizontalFeaturesClosed FrameTerminationSolderPitch - Post0.100" (2.54mm)
NormalSockets for ICs, TransistorsPackage-Series299TypeDIP, 0.6" (15.24mm) Row SpacingNumber of Positions or Pins (Grid)36 (2 x 18)Pitch - Mating0.100" (2.54mm)Contact Finish - MatingGoldContact Finish Thickness - MatingBeryllium CopperMounting TypeThrough Hole, Right Angle, HorizontalFeaturesClosed FramePitch - Post0.100" (2.54mm)
Package-Series299TypeDIP, 0.6" (15.24mm) Row SpacingNumber of Positions or Pins (Grid)36 (2 x 18)Pitch - Mating0.100" (2.54mm)Contact Finish - MatingGoldContact Finish Thickness - Mating30µin (0.76µm)Contact Material - MatingBeryllium CopperMounting TypeThrough Hole, Right Angle, HorizontalFeaturesClosed FramePitch - Post0.100" (2.54mm)
Series299TypeDIP, 0.6" (15.24mm) Row SpacingNumber of Positions or Pins (Grid)36 (2 x 18)Pitch - Mating0.100" (2.54mm)Contact Finish - MatingGoldContact Finish - Mating30µin (0.76µm)Contact Finish Thickness - MatingBeryllium CopperMounting TypeThrough Hole, Right Angle, HorizontalFeaturesClosed FrameTerminationSolderPitch - Post0.100" (2.54mm)
TypeDIP, 0.6" (15.24mm) Row SpacingNumber of Positions or Pins (Grid)36 (2 x 18)Pitch - Mating0.100" (2.54mm)Contact Finish - MatingGoldContact Finish Thickness - Mating30µin (0.76µm)Contact Material - MatingBeryllium CopperMounting TypeThrough Hole, Right Angle, HorizontalFeaturesClosed FrameTerminationSolderPitch - Post0.100" (2.54mm)
Number of Positions or Pins (Grid)36 (2 x 18)Pitch - Mating0.100" (2.54mm)Contact Finish - MatingGoldContact Finish Thickness - Mating30µin (0.76µm)Contact Material - MatingBeryllium CopperMounting TypeThrough Hole, Right Angle, HorizontalFeaturesClosed FrameTerminationSolderPitch - Post0.100" (2.54mm)
Pitch - Mating0.100" (2.54mm)Contact Finish - MatingGoldContact Finish Thickness - Mating30µin (0.76µm)Contact Material - MatingBeryllium CopperMounting TypeThrough Hole, Right Angle, HorizontalFeaturesClosed FrameTerminationSolderPitch - Post0.100" (2.54mm)
Contact Finish - MatingGoldContact Finish Thickness - Mating30µin (0.76µm)Contact Material - MatingBeryllium CopperMounting TypeThrough Hole, Right Angle, HorizontalFeaturesClosed FrameTerminationSolderPitch - Post0.100" (2.54mm)
Contact Finish Thickness - Mating30µin (0.76µm)Contact Material - MatingBeryllium CopperMounting TypeThrough Hole, Right Angle, HorizontalFeaturesClosed FrameTerminationSolderPitch - Post0.100" (2.54mm)
Contact Material - MatingBeryllium CopperMounting TypeThrough Hole, Right Angle, HorizontalFeaturesClosed FrameTerminationSolderPitch - Post0.100" (2.54mm)
Mounting TypeThrough Hole, Right Angle, HorizontalFeaturesClosed FrameTerminationSolderPitch - Post0.100" (2.54mm)
FeaturesClosed FrameTerminationSolderPitch - Post0.100" (2.54mm)
Termination Solder   Pitch - Post 0.100" (2.54mm)
Pitch - Post     0.100" (2.54mm)
Contact Finish - Post Tin
Contact Finish Thickness - Post 200µin (5.08µm)
Contact Material - Post Brass Alloy
Housing Material Polycyclohexylenedimethylene Terephthalate (PCT), Polyester
Operating Temperature $-55^{\circ}C \sim 125^{\circ}C$
Report error

#### 299-43-636-10-002000 Guarantees



**Quality Guarantees** 

We provide 90 days warranty. \* If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

# SERVICE EUARANTEE

#### **Service Guarantees**

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

## 299-43-636-10-002000 Payment Methods



If you have any question about 299-43-636-10-002000, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com