

299-93-628-10-002000

299-93-628-10-002000 Information





Request a Quote

For Reference Only

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



299-93-628-10-002000 Specifications

Manufacturer Mill-Max Manufacturing Corp. Connectors, Interconnects Sockets for ICs, Transistors Package - Series 299 Type DIP, 0.6" (15.24mm) Row Spacing Number of Positions or Pins (Grid) 28 (2 x 14) Pitch - Mating 0.100" (2.54mm) Contact Finish - Mating Gold Contact Finish Thickness - Mating 30µin (0.76µm) Contact Finish Thickness - Mating Beryllium Copper Mounting Type Through Hole, Right Angle, Horizontal Pertures Closed Frame Contact Finish - Post 0.100" (2.54mm) Contact Finish Thickness - Post Solder Contact Finish - Post 0.100" (2.54mm) Contact Finish Thickness - Post 0.100" (2.54mm) Contact Finish Thickness - Pos			
CategoryConnectors, Interconnects Sockets for ICs, TransistorsPackage-Series299TypeDIP, 0.6" (15.24mm) Row SpacingNumber of Positions or Pins (Grid)28 (2 x 14)Ohtor" (2.54mm)0.100" (2.54mm)Contact Finish - MatingGoldContact Finish Thickness - Mating30µin (0.76µm)Contact Finish Thickness - MatingBeryllium CopperMounting TypeThrough Hole, Right Angle, HorizontalFeaturesClosed FramePriminationSolderPitch - Post0.100" (2.54mm)Contact Finish Thickness - Post200µin (5.08µm)Contact Finish Thickness - Post200µin (5.08µm)Contact Material - PostBrass AlloyPhousing MaterialPolycyclohexylenedimethylene Terephthalate (PCT), PolyesterOperating Temperature-55°C ~ 125°C	Manufacturer Part Number	299-93-628-10-002000	
Sockets for ICs, TransistorsPackage-Series299TypeDIP, 0.6" (15.24mm) Row SpacingNumber of Positions or Pins (Grid)28 (2 x 14)Pitch - Mating0.100" (2.54mm)Contact Finish - MatingGoldContact Finish Thickness - Mating30µin (0.76µm)Contact Finish Thickness - MatingBeryllium CopperMounting TypeThrough Hole, Right Angle, HorizontalFeaturesClosed FrameTerminationSolderPitch - Post0.100" (2.54mm)Contact Finish Thickness - Post200µin (5.08µm)Contact Finish Thickness - Post200µin (5.08µm)Contact Finish Thickness - PostPolycyclohexylenedimethylene Terephthalate (PCT), PolyesterOperating Temperature-55°C ~ 125°C	Manufacturer	Mill-Max Manufacturing Corp.	
Package-Series299TypeDIP, 0.6" (15.24mm) Row SpacingNumber of Positions or Pins (Grid)28 (2 x 14)Pitch - Mating0.100" (2.54mm)Contact Finish - MatingGoldContact Finish Thickness - Mating30µin (0.76µm)Contact Material - MatingBeryllium CopperMounting TypeThrough Hole, Right Angle, HorizontalFeaturesClosed FrameTerminationSolderPitch - Post0.100" (2.54mm)Contact Finish Thickness - Post200µin (5.08µm)Contact Finish Thickness - Post200µin (5.08µm)Contact Finish Thickness - PostBrass AlloyContact Material - PostPolycyclohexylenedimethylene Terephthalate (PCT), PolyesterOperating Temperature-55°C ~ 125°C	Category	Connectors, Interconnects	
Series299TypeDIP, 0.6" (15.24mm) Row SpacingNumber of Positions or Pins (Grid)28 (2 x 14)Pitch - Mating0.100" (2.54mm)Contact Finish - MatingGoldContact Finish - Mating30µin (0.76µm)Contact Material - MatingBeryllium CopperMounting TypeThrough Hole, Right Angle, HorizontalFeaturesClosed FrameTerminationSolderPitch - Post0.100" (2.54mm)Contact Finish Thickness - Post0.100" (2.54mm)Contact Finish Thickness - Post200µin (5.08µm)Contact Finish Thickness - Post200µin (5.08µm)Contact Material - PostBrass AlloyHousing MaterialPolycyclohexylenedimethylene Terephthalate (PCT), PolyesterOperating Temperature-55°C ~ 125°C		Sockets for ICs, Transistors	
TypeDIP, 0.6" (15.24mm) Row SpacingNumber of Positions or Pins (Grid)28 (2 x 14)Pitch - Mating0.100" (2.54mm)Contact Finish - MatingGoldContact Finish Thickness - Mating30µin (0.76µm)Contact Material - MatingBeryllium CopperMounting TypeThrough Hole, Right Angle, HorizontalFeaturesClosed FrameTerminationSolderPitch - Post0.100" (2.54mm)Contact Finish Thickness - Post0.100" (2.54mm)Contact Finish Thickness - Post200µin (5.08µm)Contact Material - Post200µin (5.08µm)Contact Material - PostBrass AlloyHousing MaterialPolycyclohexylenedimethylene Terephthalate (PCT), PolyesterOperating Temperature-55°C ~ 125°C	Package	-	
Number of Positions or Pins (Grid)28 (2 x 14)Pitch - Mating0.100" (2.54mm)Contact Finish - MatingGoldContact Finish Thickness - Mating30µin (0.76µm)Contact Material - MatingBeryllium CopperMounting TypeThrough Hole, Right Angle, HorizontalFeaturesClosed FrameTerminationSolderPitch - Post0.100" (2.54mm)Contact Finish Thickness - Nost200µin (5.08µm)Contact Finish Thickness - Post200µin (5.08µm)Contact Material - PostDinu (5.08µm)Contact Material - PostBrass AlloyPolycyclohexylenedimethylene Terephthalate (PCT), PolyesterOperating Temperature-55°C ~ 125°C	Series	299	
Pitch - Mating0.100" (2.54mm)Contact Finish - MatingGoldContact Finish Thickness - Mating30µin (0.76µm)Contact Material - MatingBeryllium CopperMounting TypeThrough Hole, Right Angle, HorizontalFeaturesClosed FrameTerminationSolderPitch - Post0.100" (2.54mm)Contact Finish - PostDino" (2.54mm)Contact Finish - Post200µin (5.08µm)Contact Material - PostBrass AlloyHousing MaterialPolycyclohexylenedimethylene Terephthalate (PCT), PolyesterOperating Temperature-55°C ~ 125°C	Туре	DIP, 0.6" (15.24mm) Row Spacing	
Contact Finish - MatingGoldContact Finish Thickness - Mating30µin (0.76µm)Contact Material - MatingBeryllium CopperMounting TypeThrough Hole, Right Angle, HorizontalFeaturesClosed FrameTerminationSolderPitch - Post0.100" (2.54mm)Contact Finish - Post200µin (5.08µm)Contact Finish Thickness - PostBrass AlloyHousing Material - PostPolycyclohexylenedimethylene Terephthalate (PCT), PolyesterGoperating Temperature-55°C ~ 125°C	Number of Positions or Pins (Grid)	28 (2 x 14)	
Contact Finish Thickness - Mating30µin (0.76µm)Contact Material - MatingBeryllium CopperMounting TypeThrough Hole, Right Angle, HorizontalFeaturesClosed FrameTerminationSolderPitch - Post0.100" (2.54mm)Contact Finish - PostTin-LeadContact Finish Thickness - Post200µin (5.08µm)Contact Material - PostBrass AlloyHousing MaterialPolycyclohexylenedimethylene Terephthalate (PCT), PolyesterOperating Temperature-55°C ~ 125°C	Pitch - Mating	0.100" (2.54mm)	
Contact Material - MatingBeryllium CopperMounting TypeThrough Hole, Right Angle, HorizontalMounting TypeClosed FrameFeaturesClosed FrameTerminationSolderPitch - Post0.100" (2.54mm)Contact Finish - PostTin-LeadContact Finish Thickness - Post200µin (5.08µm)Contact Material - PostBrass AlloyHousing MaterialPolycyclohexylenedimethylene Terephthalate (PCT), PolyesterOperating Temperature-55°C ~ 125°C	Contact Finish - Mating	Gold	
Mounting TypeThrough Hole, Right Angle, HorizontalFeaturesClosed FrameTerminationSolderPitch - Post0.100" (2.54mm)Contact Finish - PostTin-LeadContact Finish Thickness - Post200µin (5.08µm)Contact Material - PostBrass AlloyHousing MaterialPolycyclohexylenedimethylene Terephthalate (PCT), PolyesterOperating Temperature-55°C ~ 125°C	Contact Finish Thickness - Mating	30µin (0.76µm)	
FeaturesClosed FrameTerminationSolderPitch - Post0.100" (2.54mm)Contact Finish - PostTin-LeadContact Finish Thickness - Post200µin (5.08µm)Contact Material - PostBrass AlloyHousing MaterialPolycyclohexylenedimethylene Terephthalate (PCT), PolyesterOperating Temperature-55°C ~ 125°C	Contact Material - Mating	Beryllium Copper	
TerminationSolderPitch - Post0.100" (2.54mm)Contact Finish - PostTin-LeadContact Finish Thickness - Post200µin (5.08µm)Contact Material - PostBrass AlloyHousing MaterialPolycyclohexylenedimethylene Terephthalate (PCT), PolyesterOperating Temperature-55°C ~ 125°C	Mounting Type	Through Hole, Right Angle, Horizontal	
Pitch - Post0.100" (2.54mm)Contact Finish - PostTin-LeadContact Finish Thickness - Post200µin (5.08µm)Contact Material - PostBrass AlloyHousing MaterialPolycyclohexylenedimethylene Terephthalate (PCT), PolyesterOperating Temperature-55°C ~ 125°C	Features	Closed Frame	
Contact Finish - PostTin-LeadContact Finish Thickness - Post200µin (5.08µm)Contact Material - PostBrass AlloyHousing MaterialPolycyclohexylenedimethylene Terephthalate (PCT), PolyesterOperating Temperature-55°C ~ 125°C	Termination	Solder	
Contact Finish Thickness - Post200µin (5.08µm)Contact Material - PostBrass AlloyHousing MaterialPolycyclohexylenedimethylene Terephthalate (PCT), PolyesterOperating Temperature-55°C ~ 125°C	Pitch - Post	0.100" (2.54mm)	
Contact Material - PostBrass AlloyHousing MaterialPolycyclohexylenedimethylene Terephthalate (PCT), PolyesterOperating Temperature-55°C ~ 125°C	Contact Finish - Post	Tin-Lead	
Housing MaterialPolycyclohexylenedimethylene Terephthalate (PCT), PolyesterOperating Temperature-55°C ~ 125°C	Contact Finish Thickness - Post	200µin (5.08µm)	
Operating Temperature $-55^{\circ}C \sim 125^{\circ}C$	Contact Material - Post	Brass Alloy	
	Housing Material	Polycyclohexylenedimethylene Terephthalate (PCT), Polyester	
Report errors?	Operating Temperature	-55°C ~ 125°C	
			Report errors?

E-mail: salesdept@heisener.com

299-93-628-10-002000 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE BUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

299-93-628-10-002000 Payment Methods



If you have any question about 299-93-628-10-002000, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com