

2P1515 Information



For Reference Only

Part Number 2P1515

Manufacturer Switchcraft Inc.

Category Connectors, Interconnects Barrel - Power Connectors

Description CONN PWR PLUG 2.5X5.5MM SOLDER

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









2P1515 Specifications

Manufacturer Part Number 2P1515 Manufacturer Switchcraft Inc. Category Connectors, Interconnects Barrel - Power Connectors Package - Series - Connector Type Plug Gender Female Industry Recognized Mating Diameter 2.50mm ID (0.098"), 5.50mm OD (0.217") Actual Diameter 0.098" (2.50mm ID), 0.217" (5.50mm OD) Number of Positions/Contacts 2 Conductors, 2 Contacts Internal Switch(s) Does Not Contain Switch Mounting Type Free Hanging (In-Line) Mounting Feature - Termination Solder Eyelet(s) Shielding Unshielded Features - Insulation Color Black Voltage - Rated - Current Rating - Report errors?		
Category Connectors, Interconnects Barrel - Power Connectors Package - Series - Connector Type Plug Gender Female Industry Recognized Mating Diameter 2.50mm ID (0.098"), 5.50mm OD (0.217") Actual Diameter 0.098" (2.50mm ID), 0.217" (5.50mm OD) Number of Positions/Contacts 1nternal Switch(s) Does Not Contain Switch Mounting Type Free Hanging (In-Line) Mounting Feature - Termination Solder Eyelet(s) Shielding Unshielded Features Insulation Color Black Voltage - Rated Current Rating - Connectors, Interconnects Busch Louis - Power Connectors Barrel - Power Connectors Barrel - Power Connectors Barrel - Power Connectors Barrel - Power Connectors - Connectors Louis - Power Connectors - Barrel - Power Connectors Barrel - Power Connectors - Current Rating - Connectors Louis - Power Connectors - Current Rating - Connectors - Current Rating	Manufacturer Part Number	2P1515
Barrel - Power Connectors Package - Series - Connector Type Plug Gender Female Industry Recognized Mating Diameter 2.50mm ID (0.098"), 5.50mm OD (0.217") Actual Diameter 0.098" (2.50mm ID), 0.217" (5.50mm OD) Number of Positions/Contacts 1nternal Switch(s) Does Not Contain Switch Mounting Type Free Hanging (In-Line) Mounting Feature - Termination Solder Eyelet(s) Shielding Unshielded Features Insulation Color Black Voltage - Rated Current Rating -	Manufacturer	Switchcraft Inc.
Package - Series - Connector Type Plug Gender Female Industry Recognized Mating Diameter 2.50mm ID (0.098"), 5.50mm OD (0.217") Actual Diameter 0.098" (2.50mm ID), 0.217" (5.50mm OD) Number of Positions/Contacts 2 Conductors, 2 Contacts Internal Switch(s) Does Not Contain Switch Mounting Type Free Hanging (In-Line) Mounting Feature - Termination Solder Eyelet(s) Shielding Unshielded Features - Insulation Color Black Voltage - Rated - Current Rating	Category	Connectors, Interconnects
Series - Connector Type Plug Gender Female Industry Recognized Mating Diameter 2.50mm ID (0.098"), 5.50mm OD (0.217") Actual Diameter 0.098" (2.50mm ID), 0.217" (5.50mm OD) Number of Positions/Contacts 2 Conductors, 2 Contacts Internal Switch(s) Does Not Contain Switch Mounting Type Free Hanging (In-Line) Mounting Feature - Termination Solder Eyelet(s) Shielding Unshielded Features - Insulation Color Black Voltage - Rated - Current Rating - Contain Switch - Current Rating - Contain Switch - Current Rating - Current Rating - Contain Switch - Contain Switch - Current Rating - Contain Switch - Contain Switch - Current Rating - Contain Switch - Con		Barrel - Power Connectors
Connector Type Gender Female Industry Recognized Mating Diameter 2.50mm ID (0.098"), 5.50mm OD (0.217") Actual Diameter 0.098" (2.50mm ID), 0.217" (5.50mm OD) Number of Positions/Contacts 2 Conductors, 2 Contacts Internal Switch(s) Does Not Contain Switch Mounting Type Free Hanging (In-Line) Mounting Feature - Termination Solder Eyelet(s) Shielding Unshielded Features - Insulation Color Black Voltage - Rated - Current Rating	Package	-
Gender Female Industry Recognized Mating Diameter 2.50mm ID (0.098"), 5.50mm OD (0.217") Actual Diameter 0.098" (2.50mm ID), 0.217" (5.50mm OD) Number of Positions/Contacts 2 Conductors, 2 Contacts Internal Switch(s) Does Not Contain Switch Mounting Type Free Hanging (In-Line) Mounting Feature - Termination Solder Eyelet(s) Shielding Unshielded Features - Insulation Color Black Voltage - Rated - Current Rating -	Series	-
Industry Recognized Mating Diameter Actual Diameter 0.098" (2.50mm ID) (0.217" (5.50mm OD) Number of Positions/Contacts 2 Conductors, 2 Contacts Internal Switch(s) Does Not Contain Switch Mounting Type Free Hanging (In-Line) Mounting Feature - Termination Solder Eyelet(s) Shielding Unshielded Features Insulation Color Black Voltage - Rated Current Rating - 2.50mm ID (0.098"), 5.50mm OD (0.217") 0.098" (2.50mm ID), 0.217" (5.50mm OD) 1.50mm ID (0.098"), 5.50mm OD (0.217") 1.50mm ID (0.098"), 5.50mm	Connector Type	Plug
Actual Diameter 0.098" (2.50mm ID), 0.217" (5.50mm OD) Number of Positions/Contacts 2 Conductors, 2 Contacts Internal Switch(s) Does Not Contain Switch Mounting Type Free Hanging (In-Line) Mounting Feature - Termination Solder Eyelet(s) Shielding Unshielded Features - Insulation Color Black Voltage - Rated - Current Rating -	Gender	Female
Number of Positions/Contacts2 Conductors, 2 ContactsInternal Switch(s)Does Not Contain SwitchMounting TypeFree Hanging (In-Line)Mounting Feature-TerminationSolder Eyelet(s)ShieldingUnshieldedFeatures-Insulation ColorBlackVoltage - Rated-Current Rating-	Industry Recognized Mating Diameter	2.50mm ID (0.098"), 5.50mm OD (0.217")
Internal Switch(s) Mounting Type Free Hanging (In-Line) Mounting Feature - Termination Solder Eyelet(s) Shielding Unshielded Features - Insulation Color Black Voltage - Rated Current Rating - Current Rating - Does Not Contain Switch Free Hanging (In-Line) - Unshielded - Current Rating - Contain Switch Free Hanging (In-Line) - Black - Current Rating	Actual Diameter	0.098" (2.50mm ID), 0.217" (5.50mm OD)
Mounting TypeFree Hanging (In-Line)Mounting Feature-TerminationSolder Eyelet(s)ShieldingUnshieldedFeatures-Insulation ColorBlackVoltage - Rated-Current Rating-	Number of Positions/Contacts	2 Conductors, 2 Contacts
Mounting Feature-TerminationSolder Eyelet(s)ShieldingUnshieldedFeatures-Insulation ColorBlackVoltage - Rated-Current Rating-	Internal Switch(s)	Does Not Contain Switch
Termination Solder Eyelet(s) Shielding Unshielded Features - Insulation Color Black Voltage - Rated - Current Rating -	Mounting Type	Free Hanging (In-Line)
Shielding Unshielded Features - Insulation Color Black Voltage - Rated - Current Rating -	Mounting Feature	-
Features - Insulation Color Black Voltage - Rated - Current Rating -	Termination	Solder Eyelet(s)
Insulation Color Black Voltage - Rated - Current Rating -	Shielding	Unshielded
Voltage - Rated - Current Rating -	Features	-
Current Rating -	Insulation Color	Black
-	Voltage - Rated	-
Report errors?	Current Rating	-
		Report errors?

2P1515 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

2P1515 Payment Methods



















2P1515 Shipping Methods













If you have any question about 2P1515, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com