



2R5SVPC680M Information



For Reference Only

Part Number 2R5SVPC680M

Manufacturer Panasonic Electronic Components

Category Capacitors

Aluminum - Polymer Capacitors

Description CAP ALUM POLY 68UF 20% 2.5V SMD

Package Radial, Can - SMD

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









2R5SVPC680M Specifications

| Manufacturer Part Number 2R5SVPC680M Manufacturer Panasonic Electronic Components Category Capacitors Package Radial, Can - SMD Series OS-CON?, SVPC Type Polymer Capacitance 68µF Tolerance ±20% Voltage - Rated 2.5V ESR (Equivalent Series Resistance) 20 mOhm Lifetime @ Temp. 2000 Hrs @ 105°C Operating Temperature -55°C ~ 105°C Applications - Ripple Current - Low Frequency 168.5mA @ 120Hz Ripple Current - High Frequency 3.37A @ 100kHz Impedance - Lead Spacing - Size / Dimension 0.315" Dia (8.00mm) Height - Seated (Max) 0.276" (7.00mm) Surface Mount Land Size 0.327" L x 0.327" W (8.30mm x 8.30mm) Mounting Type Surface Mount Package / Case Radial, Can - SMD | | |
|--|------------------------------------|---------------------------------------|
| Category Capacitors Package Radial, Can - SMD Series OS-CON?, SVPC Type Polymer Capacitance 68μF Tolerance ±20% Voltage - Rated 2.5V ESR (Equivalent Series Resistance) 20 mOhm Lifetime @ Temp. 2000 Hrs @ 105°C Operating Temperature -55°C ~ 105°C Applications - Ripple Current - Low Frequency 168.5mA @ 120Hz Ripple Current - High Frequency 3.37A @ 100kHz Impedance - Lead Spacing - Size / Dimension 0.315" Dia (8.00mm) Height - Seated (Max) 0.276" (7.00mm) Surface Mount Land Size 0.327" L x 0.327" W (8.30mm x 8.30mm) Mounting Type Surface Mount Package / Case Radial, Can - SMD | Manufacturer Part Number | 2R5SVPC680M |
| Aluminum - Polymer Capacitors Package Radial, Can - SMD Series OS-CON?, SVPC Type Polymer Capacitance 68µF Tolerance ±20% Voltage - Rated 2.5V ESR (Equivalent Series Resistance) 20 mOhm Lifetime @ Temp. 2000 Hrs @ 105°C Operating Temperature -55°C ~ 105°C Applications - Ripple Current - Low Frequency 168.5mA @ 120Hz Ripple Current - High Frequency 3.37A @ 100kHz Impedance - Lead Spacing - Size / Dimension 0.315" Dia (8.00mm) Height - Seated (Max) 0.276" (7.00mm) Surface Mount Land Size 0.327" L x 0.327" W (8.30mm x 8.30mm) Mounting Type Surface Mount Package / Case | Manufacturer | Panasonic Electronic Components |
| Package Radial, Can - SMD Series OS-CON?, SVPC Type Polymer Capacitance 68µF Tolerance ±20% Voltage - Rated 2.5V ESR (Equivalent Series Resistance) 20 mOhm Lifetime @ Temp. 2000 Hrs @ 105°C Operating Temperature -55°C ~ 105°C Applications - Ripple Current - Low Frequency 168.5mA @ 120Hz Ripple Current - High Frequency 3.37A @ 100kHz Impedance - Lead Spacing - Size / Dimension 0.315" Dia (8.00mm) Height - Seated (Max) 0.276" (7.00mm) Surface Mount Land Size 0.327" L x 0.327" W (8.30mm x 8.30mm) Mounting Type Surface Mount Package / Case Radial, Can - SMD | Category | Capacitors |
| Series OS-CON?, SVPC Type Polymer Capacitance 68µF Tolerance ±20% Voltage - Rated 2.5V ESR (Equivalent Series Resistance) 20 mOhm Lifetime @ Temp. 2000 Hrs @ 105°C Operating Temperature -55°C ~ 105°C Applications - Ripple Current - Low Frequency 168.5mA @ 120Hz Ripple Current - High Frequency 3.37A @ 100kHz Impedance - Lead Spacing - Size / Dimension 0.315" Dia (8.00mm) Height - Seated (Max) 0.276" (7.00mm) Surface Mount Land Size 0.327" L x 0.327" W (8.30mm x 8.30mm) Mounting Type Surface Mount Package / Case Radial, Can - SMD | | Aluminum - Polymer Capacitors |
| Type Polymer Capacitance 68µF Tolerance ±20% Voltage - Rated 2.5V ESR (Equivalent Series Resistance) 20 mOhm Lifetime @ Temp. 2000 Hrs @ 105°C Operating Temperature -55°C ~ 105°C Applications - Ripple Current - Low Frequency 168.5mA @ 120Hz Ripple Current - High Frequency 3.37A @ 100kHz Impedance - Lead Spacing - Size / Dimension 0.315" Dia (8.00mm) Height - Seated (Max) 0.276" (7.00mm) Surface Mount Land Size 0.327" L x 0.327" W (8.30mm x 8.30mm) Mounting Type Surface Mount Package / Case Radial, Can - SMD | Package | Radial, Can - SMD |
| Capacitance 68μF Tolerance ±20% Voltage - Rated 2.5V ESR (Equivalent Series Resistance) 20 mOhm Lifetime @ Temp. 2000 Hrs @ 105°C Operating Temperature -55°C ~ 105°C Applications - Ripple Current - Low Frequency 168.5mA @ 120Hz Ripple Current - High Frequency 3.37A @ 100kHz Impedance - Lead Spacing - Size / Dimension 0.315" Dia (8.00mm) Height - Seated (Max) 0.276" (7.00mm) Surface Mount Land Size 0.327" L x 0.327" W (8.30mm x 8.30mm) Mounting Type Surface Mount Package / Case Radial, Can - SMD | Series | OS-CON?, SVPC |
| Tolerance±20%Voltage - Rated2.5VESR (Equivalent Series Resistance)20 mOhmLifetime @ Temp.2000 Hrs @ 105°COperating Temperature-55°C ~ 105°CApplications-Ripple Current - Low Frequency168.5mA @ 120HzRipple Current - High Frequency3.37A @ 100kHzImpedance-Lead Spacing-Size / Dimension0.315" Dia (8.00mm)Height - Seated (Max)0.276" (7.00mm)Surface Mount Land Size0.327" L x 0.327" W (8.30mm x 8.30mm)Mounting TypeSurface MountPackage / CaseRadial, Can - SMD | Туре | Polymer |
| Voltage - Rated2.5VESR (Equivalent Series Resistance)20 mOhmLifetime @ Temp.2000 Hrs @ 105°COperating Temperature-55°C ~ 105°CApplications-Ripple Current - Low Frequency168.5mA @ 120HzRipple Current - High Frequency3.37A @ 100kHzImpedance-Lead Spacing-Size / Dimension0.315" Dia (8.00mm)Height - Seated (Max)0.276" (7.00mm)Surface Mount Land Size0.327" L x 0.327" W (8.30mm x 8.30mm)Mounting TypeSurface MountPackage / CaseRadial, Can - SMD | Capacitance | 68μF |
| ESR (Equivalent Series Resistance) Lifetime @ Temp. 2000 Hrs @ 105°C Operating Temperature -55°C ~ 105°C Applications Ripple Current - Low Frequency 168.5mA @ 120Hz Ripple Current - High Frequency 3.37A @ 100kHz Impedance - Lead Spacing Size / Dimension Height - Seated (Max) Surface Mount Land Size 0.327" L x 0.327" W (8.30mm x 8.30mm) Mounting Type Surface Mount Package / Case Radial, Can - SMD | Tolerance | ±20% |
| Lifetime @ Temp. Operating Temperature -55°C ~ 105°C Applications - Ripple Current - Low Frequency Ripple Current - High Frequency 3.37A @ 100kHz Impedance Lead Spacing - Size / Dimension Height - Seated (Max) Surface Mount Land Size Agoling Temperature -2000 Hrs @ 105°C -55°C ~ 105°C - 168.5mA @ 120Hz 3.37A @ 100kHz | Voltage - Rated | 2.5V |
| Operating Temperature Applications - Ripple Current - Low Frequency Ripple Current - High Frequency 168.5mA @ 120Hz 3.37A @ 100kHz Impedance - Lead Spacing - Size / Dimension Height - Seated (Max) Surface Mount Land Size Package / Case - Sive - Sive - Case - Sive - | ESR (Equivalent Series Resistance) | 20 mOhm |
| Applications Ripple Current - Low Frequency 168.5mA @ 120Hz 3.37A @ 100kHz Impedance Lead Spacing Size / Dimension Height - Seated (Max) Surface Mount Land Size O.327" L x 0.327" W (8.30mm x 8.30mm) Mounting Type Surface Mount Package / Case Radial, Can - SMD | Lifetime @ Temp. | 2000 Hrs @ 105°C |
| Ripple Current - Low Frequency Ripple Current - High Frequency 3.37A @ 100kHz Impedance - Lead Spacing - Size / Dimension 0.315" Dia (8.00mm) Height - Seated (Max) 0.276" (7.00mm) Surface Mount Land Size 0.327" L x 0.327" W (8.30mm x 8.30mm) Mounting Type Surface Mount Package / Case Radial, Can - SMD | Operating Temperature | -55°C ~ 105°C |
| Ripple Current - High Frequency Impedance - Lead Spacing - Size / Dimension Height - Seated (Max) Surface Mount Land Size Mounting Type Surface Mount Package / Case 3.37A @ 100kHz - 4.00mm 0.315" Dia (8.00mm) 0.276" (7.00mm) 8.30mm x 8.30mm) 8.30mm x 8.30mm) | Applications | - |
| Impedance - Lead Spacing - Size / Dimension 0.315" Dia (8.00mm) Height - Seated (Max) 0.276" (7.00mm) Surface Mount Land Size 0.327" L x 0.327" W (8.30mm x 8.30mm) Mounting Type Surface Mount Package / Case Radial, Can - SMD | Ripple Current - Low Frequency | 168.5mA @ 120Hz |
| Lead Spacing Size / Dimension 0.315" Dia (8.00mm) Height - Seated (Max) 0.276" (7.00mm) Surface Mount Land Size 0.327" L x 0.327" W (8.30mm x 8.30mm) Mounting Type Surface Mount Package / Case Radial, Can - SMD | Ripple Current - High Frequency | 3.37A @ 100kHz |
| Size / Dimension0.315" Dia (8.00mm)Height - Seated (Max)0.276" (7.00mm)Surface Mount Land Size0.327" L x 0.327" W (8.30mm x 8.30mm)Mounting TypeSurface MountPackage / CaseRadial, Can - SMD | Impedance | - |
| Height - Seated (Max) Surface Mount Land Size 0.276" (7.00mm) 0.327" L x 0.327" W (8.30mm x 8.30mm) Mounting Type Surface Mount Package / Case Radial, Can - SMD | Lead Spacing | - |
| Surface Mount Land Size 0.327" L x 0.327" W (8.30mm x 8.30mm) Mounting Type Surface Mount Package / Case Radial, Can - SMD | Size / Dimension | 0.315" Dia (8.00mm) |
| Mounting Type Surface Mount Package / Case Radial, Can - SMD | Height - Seated (Max) | 0.276" (7.00mm) |
| Package / Case Radial, Can - SMD | Surface Mount Land Size | 0.327" L x 0.327" W (8.30mm x 8.30mm) |
| | Mounting Type | Surface Mount |
| Report errors? | Package / Case | Radial, Can - SMD |
| | | Report errors? |

2R5SVPC680M Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

2R5SVPC680M Payment Methods



















2R5SVPC680M Shipping Methods













If you have any question about 2R5SVPC680M, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com