

2R5TAE680ML

Quote

2R5TAE680ML Information

Heisener.com	 2R5TAE680ML Panasonic Electronic Components Capacitors Tantalum - Polymer Capacitors CAP TANT POLY 680UF 2.5V 2917 2917 (7343 Metric) For the pricing/inventory/lead time, please contact	
For Reference Only	us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



2R5TAE680ML Specifications

Manufacturer Panasonic Electronic Components Category Capacitors Tantalum - Polymer Capacitors Tantalum - Polymer Capacitors Package 2917 (7343 Metric) Series POSCAP? TA Capacitance 680µF Tolerance ±20% Voltage - Rated 2,5V Type Molded ESR (Equivalent Series Resistance) 25 mOhm Operating Temperature -55°C ~ 105°C Lifetime @ Temp. 2000 Hrs @ 105°C Mounting Type Surface Mount, MLCC Package / Case 2917 (7343 Metric) Size / Dimension 0.287" L x 0.169" W (7.30mm x 4.30mm) Height - Seated (Max) 0.118" (3.00mm) Lead Spacing - Manufacturer Size Code D3L		
Category Capacitors Tantalum - Polymer Capacitors Package 2917 (7343 Metric) Series POSCAP? TA Capacitance 680µF Tolerance ±20% Voltage - Rated 2.5V Type Molded ESR (Equivalent Series Resistance) 25 mOhm Operating Temperature -55°C ~ 105°C Lifetime @ Temp. 2000 Hrs @ 105°C Mounting Type Surface Mount, MLCC Package / Case 2917 (7343 Metric) Size / Dimension 0.287" L x 0.169" W (7.30mm x 4.30mm) Height - Seated (Max) 0.118" (3.00mm) Lead Spacing - Features General Purpose	Manufacturer Part Number	2R5TAE680ML
Tantalum - Polymer CapacitorsPackage2917 (7343 Metric)SeriesPOSCAP? TACapacitance680µFTolerance±20%Voltage - Rated2.5VTypeMoldedESR (Equivalent Series Resistance)25 mOhmOperating Temperature-55°C ~ 105°CLifetime @ Temp.2000 Hrs @ 105°CMounting TypeSurface Mount, MLCCPackage / Case2917 (7343 Metric)Size / Dimension0.287" L x 0.169" W (7.30mm x 4.30mm)Height - Seated (Max)0.118" (3.00mm)Lead Spacing-FeaturesGeneral Purpose	Manufacturer	Panasonic Electronic Components
Package2917 (7343 Metric)SeriesPOSCAP? TACapacitance680µFTolerance±20%Voltage - Rated2.5VTypeMoldedESR (Equivalent Series Resistance)25 mOhmOperating Temperature-55°C ~ 105°CLifetime @ Temp.2000 Hrs @ 105°CMounting TypeSurface Mount, MLCCPackage / Case2917 (7343 Metric)Size / Dimension0.287" L x 0.169" W (7.30mm x 4.30mm)Height - Seated (Max)0.118" (3.00mm)Lead Spacing-FaturesGeneral Purpose	Category	Capacitors
Series POSCAP? TA Capacitance 680μF Capacitance ±20% Tolerance ±20% Voltage - Rated 2.5V Type Molded ESR (Equivalent Series Resistance) 25 mOhm Operating Temperature -55°C ~ 105°C Lifetime @ Temp. 2000 Hrs @ 105°C Mounting Type Surface Mount, MLCC Package / Case 2917 (7343 Metric) Size / Dimension 0.18" (3.00mm) Height - Seated (Max) 0.118" (3.00mm) Lead Spacing - Features General Purpose		Tantalum - Polymer Capacitors
Capacitance 680μF Capacitance ±20% Tolerance ±20% Voltage - Rated 2.5V Type Molded ESR (Equivalent Series Resistance) 25 mOhm Operating Temperature -55°C ~ 105°C Lifetime @ Temp. 2000 Hrs @ 105°C Mounting Type Surface Mount, MLCC Package / Case 2917 (7343 Metric) Size / Dimension 0.287" L x 0.169" W (7.30mm x 4.30mm) Height - Seated (Max) 0.118" (3.00mm) Lead Spacing - Features General Purpose	Package	2917 (7343 Metric)
Tolerance±20%Yoltage - Rated2.5VTypeMoldedESR (Equivalent Series Resistance)25 mOhmOperating Temperature-55°C ~ 105°CLifetime @ Temp.2000 Hrs @ 105°CMounting TypeSurface Mount, MLCCPackage / Case2917 (7343 Metric)Size / Dimension0.287" L x 0.169" W (7.30mm x 4.30mm)Height - Seated (Max)0.118" (3.00mm)Lead Spacing-FeaturesGeneral Purpose	Series	POSCAP? TA
Voltage - Rated2.5VTypeMoldedESR (Equivalent Series Resistance)25 mOhmOperating Temperature-55°C ~ 105°CLifetime @ Temp.2000 Hrs @ 105°CMounting TypeSurface Mount, MLCCPackage / Case2917 (7343 Metric)Size / Dimension0.287" L x 0.169" W (7.30mm x 4.30mm)Height - Seated (Max)0.118" (3.00mm)Lead Spacing-FeaturesGeneral Purpose	Capacitance	680µF
TypeMoldedESR (Equivalent Series Resistance)25 mOhmOperating Temperature-55°C ~ 105°CLifetime @ Temp.2000 Hrs @ 105°CMounting TypeSurface Mount, MLCCPackage / Case2917 (7343 Metric)Size / Dimension0.287" L x 0.169" W (7.30mm x 4.30mm)Height - Seated (Max)0.118" (3.00mm)Lead Spacing-Manufacturer Size CodeD3LFeaturesGeneral Purpose	Tolerance	$\pm 20\%$
A25 mOhmESR (Equivalent Series Resistance)25 mOhmOperating Temperature-55°C ~ 105°CLifetime @ Temp.2000 Hrs @ 105°CMounting TypeSurface Mount, MLCCPackage / Case2917 (7343 Metric)Size / Dimension0.287" L x 0.169" W (7.30mm x 4.30mm)Height - Seated (Max)0.118" (3.00mm)Lead Spacing-Manufacturer Size CodeD3LFeaturesGeneral Purpose	Voltage - Rated	2.5V
Operating Temperature-55°C ~ 105°CLifetime @ Temp.2000 Hrs @ 105°CMounting TypeSurface Mount, MLCCPackage / Case2917 (7343 Metric)Size / Dimension0.287" L x 0.169" W (7.30mm x 4.30mm)Height - Seated (Max)0.118" (3.00mm)Lead Spacing-Manufacturer Size CodeD3LFeaturesGeneral Purpose	Туре	Molded
Lifetime @ Temp.2000 Hrs @ 105°CMounting TypeSurface Mount, MLCCPackage / Case2917 (7343 Metric)Size / Dimension0.287" L x 0.169" W (7.30mm x 4.30mm)Height - Seated (Max)0.118" (3.00mm)Lead Spacing-Manufacturer Size CodeD3LFeaturesGeneral Purpose	ESR (Equivalent Series Resistance)	25 mOhm
Mounting TypeSurface Mount, MLCCPackage / Case2917 (7343 Metric)Size / Dimension0.287" L x 0.169" W (7.30mm x 4.30mm)Height - Seated (Max)0.118" (3.00mm)Lead Spacing-Manufacturer Size CodeD3LFeaturesGeneral Purpose	Operating Temperature	-55°C ~ 105°C
Package / Case2917 (7343 Metric)Size / Dimension0.287" L x 0.169" W (7.30mm x 4.30mm)Height - Seated (Max)0.118" (3.00mm)Lead Spacing-Manufacturer Size CodeD3LFeaturesGeneral Purpose	Lifetime @ Temp.	2000 Hrs @ 105°C
Size / Dimension0.287" L x 0.169" W (7.30mm x 4.30mm)Height - Seated (Max)0.118" (3.00mm)Lead Spacing-Manufacturer Size CodeD3LFeaturesGeneral Purpose	Mounting Type	Surface Mount, MLCC
Height - Seated (Max)0.118" (3.00mm)Lead Spacing-Manufacturer Size CodeD3LFeaturesGeneral Purpose	Package / Case	2917 (7343 Metric)
Lead Spacing-Manufacturer Size CodeD3LFeaturesGeneral Purpose	Size / Dimension	0.287" L x 0.169" W (7.30mm x 4.30mm)
Manufacturer Size CodeD3LFeaturesGeneral Purpose	Height - Seated (Max)	0.118" (3.00mm)
Features General Purpose	Lead Spacing	-
	Manufacturer Size Code	D3L
Report errors?	Features	General Purpose
		Report errors?

2R5TAE680ML Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

2R5TAE680ML Payment Methods



2R5TAE680ML Shipping Methods



If you have any question about 2R5TAE680ML, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com