



2R5THE330MI Information

2R5THE330MI Part Number

Manufacturer Panasonic Electronic Components

Category Capacitors

Tantalum - Polymer Capacitors

Description CAP TANT POLY 330UF 2.5V 2917

Package 2917 (7343 Metric)

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









2R5THE330MI Specifications

Manufacturer Part Number Manufacturer Panasonic Electronic Components Category Capacitors Tantalum - Polymer Capacitors Package 2917 (7343 Metric) Series POSCAP? TH Capacitance 330µF Tolerance ±20% Voltage - Rated 2.5V Type Molded ESR (Equivalent Series Resistance) 18 mOhm @ 100kHz Operating Temperature Lifetime @ Temp. Mounting Type Surface Mount Package / Case 2917 (7343 Metric) Surface Mount Package / Case 2917 (7343 Metric) Surface Mount Package / Case 2917 (7343 Metric) Size / Dimension 0.287" L x 0.169" W (7.30mm x 4.30mm) Height - Seated (Max) Lead Spacing Manufacturer Size Code Features General Purpose		
Category Capacitors Package 2917 (7343 Metric) Series POSCAP? TH Capacitance 330μF Tolerance ±20% Voltage - Rated 2.5 V Type Molded ESR (Equivalent Series Resistance) 18 mOhm @ 100kHz Operating Temperature -55°C ~ 125°C Lifetime @ Temp. 1000 Hrs @ 125°C Mounting Type Surface Mount Package / Case 2917 (7343 Metric) Size / Dimension 0.287" L x 0.169" W (7.30mm x 4.30mm) Height - Seated (Max) 0.075" (1.90mm) Lead Spacing - Manufacturer Size Code D2E Features General Purpose	Manufacturer Part Number	2R5THE330MI
Package 2917 (7343 Metric) Series POSCAP? TH Capacitance 330μF Tolerance ±20% Voltage - Rated 2.5V Type Molded ESR (Equivalent Series Resistance) 18 mOhm @ 100kHz Operating Temperature -55°C ~ 125°C Lifetime @ Temp. 1000 Hrs @ 125°C Mounting Type Surface Mount Package / Case 2917 (7343 Metric) Size / Dimension 0.287" L x 0.169" W (7.30mm x 4.30mm) Height - Seated (Max) 0.075" (1.90mm) Lead Spacing - Manufacturer Size Code D2E Features General Purpose	Manufacturer	Panasonic Electronic Components
Package 2917 (7343 Metric) Series POSCAP? TH Capacitance 330μF Tolerance ±20% Voltage - Rated 2.5V Type Molded ESR (Equivalent Series Resistance) 18 mOhm @ 100kHz Operating Temperature -55°C ~ 125°C Lifetime @ Temp. 1000 Hrs @ 125°C Mounting Type Surface Mount Package / Case 2917 (7343 Metric) Size / Dimension 0.287" L x 0.169" W (7.30mm x 4.30mm) Height - Seated (Max) 0.075" (1.90mm) Lead Spacing - Manufacturer Size Code D2E Features General Purpose	Category	Capacitors
Series POSCAP? TH Capacitance 330µF Tolerance ±20% Voltage - Rated 2.5V Type Molded ESR (Equivalent Series Resistance) 18 mOhm @ 100kHz Operating Temperature -55°C ~ 125°C Lifetime @ Temp. 1000 Hrs @ 125°C Mounting Type Surface Mount Package / Case 2917 (7343 Metric) Size / Dimension 0.287" L x 0.169" W (7.30mm x 4.30mm) Height - Seated (Max) 0.075" (1.90mm) Lead Spacing - Manufacturer Size Code D2E Features General Purpose		Tantalum - Polymer Capacitors
Capacitance 330μF Tolerance ±20% Voltage - Rated 2.5V Type Molded ESR (Equivalent Series Resistance) 18 mOhm @ 100kHz Operating Temperature -55°C ~ 125°C Lifetime @ Temp. 1000 Hrs @ 125°C Mounting Type Surface Mount Package / Case 2917 (7343 Metric) Size / Dimension 0.287" L x 0.169" W (7.30mm x 4.30mm) Height - Seated (Max) 0.075" (1.90mm) Lead Spacing - Manufacturer Size Code D2E Features General Purpose	Package	2917 (7343 Metric)
Tolerance ±20% Voltage - Rated 2.5V Type Molded ESR (Equivalent Series Resistance) 18 mOhm @ 100kHz Operating Temperature -55°C ~ 125°C Lifetime @ Temp. 1000 Hrs @ 125°C Mounting Type Surface Mount Package / Case 2917 (7343 Metric) Size / Dimension 0.287" L x 0.169" W (7.30mm x 4.30mm) Height - Seated (Max) 0.075" (1.90mm) Lead Spacing - Manufacturer Size Code D2E Features General Purpose	Series	POSCAP? TH
Voltage - Rated Type Molded ESR (Equivalent Series Resistance) 18 mOhm @ 100kHz Operating Temperature -55°C ~ 125°C Lifetime @ Temp. 1000 Hrs @ 125°C Mounting Type Surface Mount Package / Case 2917 (7343 Metric) Size / Dimension 0.287" L x 0.169" W (7.30mm x 4.30mm) Height - Seated (Max) Lead Spacing Manufacturer Size Code Features General Purpose	Capacitance	330μF
Type Molded ESR (Equivalent Series Resistance) 18 mOhm @ 100kHz Operating Temperature -55°C ~ 125°C Lifetime @ Temp. 1000 Hrs @ 125°C Mounting Type Surface Mount Package / Case 2917 (7343 Metric) Size / Dimension 0.287" L x 0.169" W (7.30mm x 4.30mm) Height - Seated (Max) 0.075" (1.90mm) Lead Spacing - Manufacturer Size Code D2E Features General Purpose	Tolerance	±20%
ESR (Equivalent Series Resistance) 18 mOhm @ 100kHz Operating Temperature -55°C ~ 125°C Lifetime @ Temp. 1000 Hrs @ 125°C Mounting Type Surface Mount Package / Case 2917 (7343 Metric) Size / Dimension 0.287" L x 0.169" W (7.30mm x 4.30mm) Height - Seated (Max) Lead Spacing Manufacturer Size Code Features General Purpose	Voltage - Rated	2.5V
Operating Temperature Lifetime @ Temp. 1000 Hrs @ 125°C Mounting Type Surface Mount Package / Case 2917 (7343 Metric) Size / Dimension 0.287" L x 0.169" W (7.30mm x 4.30mm) Height - Seated (Max) 0.075" (1.90mm) Lead Spacing Manufacturer Size Code Features General Purpose	Туре	Molded
Lifetime @ Temp. 1000 Hrs @ 125°C Mounting Type Surface Mount Package / Case 2917 (7343 Metric) Size / Dimension 0.287" L x 0.169" W (7.30mm x 4.30mm) Height - Seated (Max) 0.075" (1.90mm) Lead Spacing Manufacturer Size Code Features General Purpose	ESR (Equivalent Series Resistance)	18 mOhm @ 100kHz
Mounting Type Surface Mount Package / Case 2917 (7343 Metric) Size / Dimension 0.287" L x 0.169" W (7.30mm x 4.30mm) Height - Seated (Max) 0.075" (1.90mm) Lead Spacing - Manufacturer Size Code D2E Features General Purpose	Operating Temperature	-55°C ~ 125°C
Package / Case 2917 (7343 Metric) Size / Dimension 0.287" L x 0.169" W (7.30mm x 4.30mm) Height - Seated (Max) 0.075" (1.90mm) Lead Spacing - Manufacturer Size Code D2E Features General Purpose	Lifetime @ Temp.	1000 Hrs @ 125°C
Size / Dimension 0.287" L x 0.169" W (7.30mm x 4.30mm) Height - Seated (Max) 0.075" (1.90mm) Lead Spacing - Manufacturer Size Code D2E Features General Purpose	Mounting Type	Surface Mount
Height - Seated (Max) Lead Spacing Manufacturer Size Code Features O.075" (1.90mm) - D2E General Purpose	Package / Case	2917 (7343 Metric)
Lead Spacing-Manufacturer Size CodeD2EFeaturesGeneral Purpose	Size / Dimension	0.287" L x 0.169" W (7.30mm x 4.30mm)
Manufacturer Size Code D2E Features General Purpose	Height - Seated (Max)	0.075" (1.90mm)
Features General Purpose	Lead Spacing	-
	Manufacturer Size Code	D2E
Report errors?	Features	General Purpose
		Report errors?

2R5THE330MI Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

2R5THE330MI Payment Methods



















2R5THE330MI Shipping Methods













If you have any question about 2R5THE330MI, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com