



2R5TPU68MSK Information

vww.heisener.com

For Reference Only

Part Number 2R5TPU68MSK

Manufacturer Panasonic Electronic Components

Category Capacitors

Tantalum - Polymer Capacitors

Description CAP TANT POLY 68UF 2.5V 0805

Package 0805 (2012 Metric)

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









2R5TPU68MSK Specifications

Manufacturer 2R5TPU68MSK Manufacturer Panasonic Electronic Components Category Capacitors Tantalum - Polymer Capacitors Package 0805 (2012 Metric) Series POSCAP? TPU Capacitance 68µF Tolerance ±20% Voltage - Rated 2.5V Type Molded ESR (Equivalent Series Resistance) 150 mOhm Operating Temperature -55°C ~ 85°C Lifetime @ Temp. 1000 Hrs @ 85°C Mounting Type Surface Mount Package / Case 0805 (2012 Metric) Size / Dimension 0.079" L x 0.049" W (2.00mm x 1.25mm) Height - Seated (Max) 0.039" (1.00mm) Lead Spacing - Manufacturer Size Code 509		
Category Capacitors Package 0805 (2012 Metric) Series POSCAP? TPU Capacitance 68µF Tolerance ±20% Voltage - Rated 2.5V Type Molded ESR (Equivalent Series Resistance) 150 mOhm Operating Temperature -55°C ~ 85°C Lifetime @ Temp. 1000 Hrs @ 85°C Mounting Type Surface Mount Package / Case 0805 (2012 Metric) Size / Dimension 0.079" L x 0.049" W (2.00mm x 1.25mm) Height - Seated (Max) 0.039" (1.00mm) Lead Spacing -	Manufacturer Part Number	2R5TPU68MSK
PackageTantalum - Polymer CapacitorsPackage0805 (2012 Metric)SeriesPOSCAP? TPUCapacitance68μFTolerance±20%Voltage - Rated2.5 VTypeMoldedESR (Equivalent Series Resistance)150 mOhmOperating Temperature-55°C ~ 85°CLifetime @ Temp.1000 Hrs @ 85°CMounting TypeSurface MountPackage / Case0805 (2012 Metric)Size / Dimension0.079" L x 0.049" W (2.00mm x 1.25mm)Height - Seated (Max)0.039" (1.00mm)Lead Spacing-	Manufacturer	Panasonic Electronic Components
Package 0805 (2012 Metric) Series POSCAP? TPU Capacitance 68μF Tolerance ±20% Voltage - Rated 2.5 V Type Molded ESR (Equivalent Series Resistance) 150 mOhm Operating Temperature -55°C ~ 85°C Lifetime @ Temp. 1000 Hrs @ 85°C Mounting Type Surface Mount Package / Case 0805 (2012 Metric) Size / Dimension 0.079" L x 0.049" W (2.00mm x 1.25mm) Height - Seated (Max) 0.039" (1.00mm) Lead Spacing -	Category	Capacitors
SeriesPOSCAP? TPUCapacitance $68\mu F$ Tolerance $\pm 20\%$ Voltage - Rated $2.5V$ TypeMoldedESR (Equivalent Series Resistance) 150 mOhm Operating Temperature $-55^{\circ}\text{C} \sim 85^{\circ}\text{C}$ Lifetime @ Temp. $1000 \text{ Hrs @ }85^{\circ}\text{C}$ Mounting TypeSurface MountPackage / Case $0805 (2012 \text{ Metric})$ Size / Dimension $0.079^{\circ}\text{L x } 0.049^{\circ}\text{W } (2.00 \text{mm x } 1.25 \text{mm})$ Height - Seated (Max) 0.039° (1.00mm)Lead Spacing-		Tantalum - Polymer Capacitors
Capacitance 68μF Tolerance ±20% Voltage - Rated 2.5V Type Molded ESR (Equivalent Series Resistance) 150 mOhm Operating Temperature -55°C ~ 85°C Lifetime @ Temp. 1000 Hrs @ 85°C Mounting Type Surface Mount Package / Case 0805 (2012 Metric) Size / Dimension 0.079" L x 0.049" W (2.00mm x 1.25mm) Height - Seated (Max) 0.039" (1.00mm) Lead Spacing -	Package	0805 (2012 Metric)
Tolerance ±20% Voltage - Rated 2.5V Type Molded ESR (Equivalent Series Resistance) 150 mOhm Operating Temperature -55°C ~ 85°C Lifetime @ Temp. 1000 Hrs @ 85°C Mounting Type Surface Mount Package / Case 0805 (2012 Metric) Size / Dimension 0.079" L x 0.049" W (2.00mm x 1.25mm) Height - Seated (Max) 0.039" (1.00mm) Lead Spacing -	Series	POSCAP? TPU
Voltage - Rated Type Molded ESR (Equivalent Series Resistance) Operating Temperature -55°C ~ 85°C Lifetime @ Temp. 1000 Hrs @ 85°C Mounting Type Surface Mount Package / Case 0805 (2012 Metric) Size / Dimension Height - Seated (Max) Lead Spacing - Molded 2.5V Molded 150 mOhm -55°C ~ 85°C 1000 Hrs @ 85°C 0000 Hrs @ 85°C	Capacitance	68μF
Type Molded ESR (Equivalent Series Resistance) 150 mOhm Operating Temperature -55°C ~ 85°C Lifetime @ Temp. 1000 Hrs @ 85°C Mounting Type Surface Mount Package / Case 0805 (2012 Metric) Size / Dimension 0.079" L x 0.049" W (2.00mm x 1.25mm) Height - Seated (Max) 0.039" (1.00mm) Lead Spacing -	Tolerance	±20%
ESR (Equivalent Series Resistance) Operating Temperature -55°C ~ 85°C Lifetime @ Temp. 1000 Hrs @ 85°C Mounting Type Surface Mount Package / Case 0805 (2012 Metric) Size / Dimension 0.079" L x 0.049" W (2.00mm x 1.25mm) Height - Seated (Max) 0.039" (1.00mm) Lead Spacing -	Voltage - Rated	2.5V
Operating Temperature -55°C ~ 85°C Lifetime @ Temp. 1000 Hrs @ 85°C Mounting Type Surface Mount Package / Case 0805 (2012 Metric) Size / Dimension 0.079" L x 0.049" W (2.00mm x 1.25mm) Height - Seated (Max) 0.039" (1.00mm) Lead Spacing -	Туре	Molded
Lifetime @ Temp. 1000 Hrs @ 85°C Mounting Type Surface Mount Package / Case 0805 (2012 Metric) Size / Dimension 0.079" L x 0.049" W (2.00mm x 1.25mm) Height - Seated (Max) 0.039" (1.00mm) Lead Spacing -	ESR (Equivalent Series Resistance)	150 mOhm
Mounting Type Surface Mount Package / Case 0805 (2012 Metric) Size / Dimension 0.079" L x 0.049" W (2.00mm x 1.25mm) Height - Seated (Max) 0.039" (1.00mm) Lead Spacing -	Operating Temperature	-55°C ~ 85°C
Package / Case 0805 (2012 Metric) Size / Dimension 0.079" L x 0.049" W (2.00mm x 1.25mm) Height - Seated (Max) 0.039" (1.00mm) Lead Spacing -	Lifetime @ Temp.	1000 Hrs @ 85°C
Size / Dimension 0.079" L x 0.049" W (2.00mm x 1.25mm) Height - Seated (Max) 0.039" (1.00mm) Lead Spacing -	Mounting Type	Surface Mount
Height - Seated (Max) Lead Spacing 0.039" (1.00mm) -	Package / Case	0805 (2012 Metric)
Lead Spacing -	Size / Dimension	0.079" L x 0.049" W (2.00mm x 1.25mm)
	Height - Seated (Max)	0.039" (1.00mm)
Manufacturer Size Code S09	Lead Spacing	-
manatactary bize code	Manufacturer Size Code	S09
Features General Purpose	Features	General Purpose
Report errors?		Report errors?

2R5TPU68MSK Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

2R5TPU68MSK Payment Methods



















2R5TPU68MSK Shipping Methods













If you have any question about 2R5TPU68MSK, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com