

2TPF330M6

2TPF330M6 Information

www.heisener.com	Part Number Manufacturer Category Description Package	2TPF330M6 Panasonic Electronic Components Capacitors Tantalum - Polymer Capacitors CAP TANT POLY 330UF 2V 2917 2917 (7343 Metric) For the pricing/inventory/lead time, please contact us	
For Reference Only		Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



2TPF330M6 Specifications

Manufacturer Panasonic Electronic Components Category Capacitors Tantalum - Polymer Capacitors Tantalum - Polymer Capacitors Package 2917 (7343 Metric) Package 2917 (7343 Metric) Series POSCAP? TPF Capacitance 330µF Tolerance ±20% Voltage - Rated 2V Type Molded ESR (Equivalent Series Resistance) 6 mOhm Operating Temperature -55°C ~ 105°C Lifetime @ Temp. 2000 Hrs @ 105°C Mounting Type Surface Mount Package / Case 2917 (7343 Metric) Size / Dimension 0.287" L x 0.169" W (7.30mm x 4.30mm) Height - Seated (Max) 0.079" (2.00mm) Lead Spacing - Manufacturer Size Code DEE		
CategoryCapacitorsTantalum - Polymer CapacitorsPackage2917 (7343 Metric)SeriesPOSCAP? TPFCapacitance330µFCapacitance±20%Voltage - Rated2VYopeMoldedESR (Equivalent Series Resistance)6 mOhmOperating Temperature-55°C ~ 105°CLifetime @ Temp.2000 Hrs @ 105°CMounting TypeSurface MountPackage / Case2917 (7343 Metric)Size / Dimension0.287" L x 0.169" W (7.30mm x 4.30mm)Height - Seated (Max)-Manufacturer Size CodeDZEFeaturesGeneral Purpose	Manufacturer Part Number	2TPF330M6
Tantalum - Polymer CapacitorsPackage2917 (7343 Metric)SeriesPOSCAP? TPFCapacitance330µFTolerance±20%Voltage - Rated2VTypeMoldedESR (Equivalent Series Resistance)6 mOhmOperating Temperature-55°C ~ 105°CLifetime @ Temp.2000 Hrs @ 105°CMounting TypeSurface MountPackage / Case2917 (7343 Metric)Size / Dimension0.287" L x 0.169" W (7.30mm x 4.30mm)Height - Seated (Max)0.079" (2.00mm)Lead Spacing-FeaturesGeneral Purpose	Manufacturer	Panasonic Electronic Components
Package2917 (7343 Metric)SeriesPOSCAP? TPFCapacitance330µFTolerance±20%Voltage - Rated2VTypeMoldedESR (Equivalent Series Resistance)6 mOhmOperating Temperature55°C ~ 105°CLifetime @ Temp.2000 Hrs @ 105°CMounting TypeSurface MountPackage / Case2917 (7343 Metric)Size / Dimension0.287" L x 0.169" W (7.30mm x 4.30mm)Height - Seated (Max)0.079" (2.00mm)Lead Spacing-FeaturesGeneral Purpose	Category	Capacitors
SeriesPOSCAP? TPFCapacitance330µFTolerance±20%Voltage - Rated2VTypeMoldedESR (Equivalent Series Resistance)6 mOhmOperating Temperature-55°C ~ 105°CLifetime @ Temp.2000 Hrs @ 105°CMounting TypeSurface MountPackage / Case2917 (7343 Metric)Size / Dimension0.287" L x 0.169" W (7.30mm x 4.30mm)Height - Seated (Max)0.079" (2.00mm)Lead Spacing-FaturesGeneral Purpose		Tantalum - Polymer Capacitors
Capacitance330μFCapacitance330μFTolerance±20%Voltage - Rated2VTypeMoldedESR (Equivalent Series Resistance)6 mOhmOperating Temperature-55°C ~ 105°CLifetime @ Temp.2000 Hrs @ 105°CMounting TypeSurface MountPackage / Case2917 (7343 Metric)Size / Dimension0.287" L x 0.169" W (7.30mm x 4.30mm)Height - Seated (Max)0.079" (2.00mm)Lead Spacing-FeaturesGeneral Purpose	Package	2917 (7343 Metric)
Tolerance±20%Tolerance±20%Voltage - Rated2VTypeMoldedESR (Equivalent Series Resistance)6 mOhmOperating Temperature-55°C ~ 105°CLifetime @ Temp.2000 Hrs @ 105°CMounting TypeSurface MountPackage / Case2917 (7343 Metric)Size / Dimension0.287" L x 0.169" W (7.30mm x 4.30mm)Height - Seated (Max)0.079" (2.00mm)Lead Spacing-FeaturesGeneral Purpose	Series	POSCAP? TPF
Voltage - Rated2VTypeMoldedESR (Equivalent Series Resistance)6 mOhmOperating Temperature-55°C ~ 105°CLifetime @ Temp.2000 Hrs @ 105°CMounting TypeSurface MountPackage / Case2917 (7343 Metric)Size / Dimension0.287" L x 0.169" W (7.30mm x 4.30mm)Height - Seated (Max)0.079" (2.00mm)Lead Spacing-Manufacturer Size CodeD2EFeaturesGeneral Purpose	Capacitance	330µF
TypeMoldedESR (Equivalent Series Resistance)6 mOhmOperating Temperature-55°C ~ 105°CLifetime @ Temp.2000 Hrs @ 105°CMounting TypeSurface MountPackage / Case2917 (7343 Metric)Size / Dimension0.287" L x 0.169" W (7.30mm x 4.30mm)Height - Seated (Max)0.079" (2.00mm)Lead Spacing-Manufacturer Size CodeD2EFeaturesGeneral Purpose	Tolerance	$\pm 20\%$
Ar6 mOhmESR (Equivalent Series Resistance)6 mOhmOperating Temperature-55°C ~ 105°CLifetime @ Temp.2000 Hrs @ 105°CMounting TypeSurface MountPackage / Case2917 (7343 Metric)Size / Dimension0.287" L x 0.169" W (7.30mm x 4.30mm)Height - Seated (Max)0.079" (2.00mm)Lead Spacing-Manufacturer Size CodeD2EFeaturesGeneral Purpose	Voltage - Rated	2V
Operating Temperature-55°C ~ 105°CLifetime @ Temp.2000 Hrs @ 105°CMounting TypeSurface MountPackage / Case2917 (7343 Metric)Size / Dimension0.287" L x 0.169" W (7.30mm x 4.30mm)Height - Seated (Max)0.079" (2.00mm)Lead Spacing-Manufacturer Size CodeD2EFeaturesGeneral Purpose	Туре	Molded
Lifetime @ Temp.2000 Hrs @ 105°CMounting TypeSurface MountPackage / Case2917 (7343 Metric)Size / Dimension0.287" L x 0.169" W (7.30mm x 4.30mm)Height - Seated (Max)0.079" (2.00mm)Lead Spacing-Manufacturer Size CodeD2EFeaturesGeneral Purpose	ESR (Equivalent Series Resistance)	6 mOhm
Nounting TypeSurface MountPackage / Case2917 (7343 Metric)Package / Case0.287" L x 0.169" W (7.30mm x 4.30mm)Size / Dimension0.079" (2.00mm)Height - Seated (Max)0.079" (2.00mm)Lead Spacing-Manufacturer Size CodeD2EFeaturesGeneral Purpose	Operating Temperature	-55°C ~ 105°C
Package / Case2917 (7343 Metric)Size / Dimension0.287" L x 0.169" W (7.30mm x 4.30mm)Height - Seated (Max)0.079" (2.00mm)Lead Spacing-Manufacturer Size CodeD2EFeaturesGeneral Purpose	Lifetime @ Temp.	2000 Hrs @ 105°C
Size / Dimension0.287" L x 0.169" W (7.30mm x 4.30mm)Height - Seated (Max)0.079" (2.00mm)Lead Spacing-Manufacturer Size CodeD2EFeaturesGeneral Purpose	Mounting Type	Surface Mount
Height - Seated (Max)0.079" (2.00mm)Lead Spacing-Manufacturer Size CodeD2EFeaturesGeneral Purpose	Package / Case	2917 (7343 Metric)
Lead Spacing-Manufacturer Size CodeD2EFeaturesGeneral Purpose	Size / Dimension	0.287" L x 0.169" W (7.30mm x 4.30mm)
Manufacturer Size CodeD2EFeaturesGeneral Purpose	Height - Seated (Max)	0.079" (2.00mm)
Features General Purpose	Lead Spacing	-
	Manufacturer Size Code	D2E
Report errors?	Features	General Purpose
		Report errors?

2TPF330M6 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE BUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

DISCOVER

2TPF330M6 Payment Methods WIRE transfer PayPal Wisher Or MoneyGram Alipay: VISA 2 2TPF330M6 Shipping Methods



If you have any question about 2TPF330M6, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com