

3-1393818-2 Information

Heisener.com

Part Number 3-1393818-2

Manufacturer TE Connectivity Potter & Brumfield Relays

Category Relays

Signal Relays, Up to 2 Amps

Description RELAY GEN PURPOSE DPDT 2A 15V

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









3-1393818-2 Specifications

Manufacturer Part Number 3-1393818-2 Manufacturer TE Connectivity Potter & Brumfield Relays Category Relays Package - Series V23162, AXICOM Relay Type General Purpose Coil Type Non Latching Coil Current 46.1mA Coil Voltage 15VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 2A Switching Voltage 125VAC, 150VDC - Max Turn On Voltage (Max) 6.8 VDC Turn Off Voltage (Min) - Operate Time 7.5ms Release Time 3ms Features Sealed - Hermetically Mounting Type Socketable Termination Style Plug In		
CategoryRelaysPackage-SeriesV23162, AXICOMRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current46.1mACoil Voltage15VDCContact FormDPDT (2 Form C)Contact Rating (Current)2ASwitching Voltage125VAC, 150VDC - MaxTurn On Voltage (Max)6.8 VDCTurn Off Voltage (Min)-Operate Time7.5msRelease Time3msFeaturesSealed - HermeticallyMounting TypeSocketableTermination StylePlug In	Manufacturer Part Number	3-1393818-2
Package-SeriesV23162, AXICOMRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current46.1mACoil Voltage15VDCContact FormDPDT (2 Form C)Contact Rating (Current)2ASwitching Voltage125VAC, 150VDC - MaxTurn On Voltage (Max)6.8 VDCTurn Off Voltage (Min)-Operate Time7.5msRelease Time3msFeaturesSealed - HermeticallyMounting TypeSocketableTermination StylePlug In	Manufacturer	TE Connectivity Potter & Brumfield Relays
Package - Series V23162, AXICOM Relay Type General Purpose Coil Type Non Latching Coil Current 46.1mA Coil Voltage 15VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 2A Switching Voltage 125VAC, 150VDC - Max Turn On Voltage (Max) 6.8 VDC Turn Off Voltage (Min) - Operate Time 7.5ms Release Time 3ms Features Sealed - Hermetically Mounting Type Socketable Termination Style Plug In	Category	Relays
SeriesV23162, AXICOMRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current46.1mACoil Voltage15VDCContact FormDPDT (2 Form C)Contact Rating (Current)2ASwitching Voltage125VAC, 150VDC - MaxTurn On Voltage (Max)6.8 VDCTurn Off Voltage (Min)-Operate Time7.5msRelease Time3msFeaturesSealed - HermeticallyMounting TypeSocketableTermination StylePlug In		Signal Relays, Up to 2 Amps
Relay TypeGeneral PurposeCoil TypeNon LatchingCoil Current46.1mACoil Voltage15VDCContact FormDPDT (2 Form C)Contact Rating (Current)2ASwitching Voltage125VAC, 150VDC - MaxTurn On Voltage (Max)6.8 VDCTurn Off Voltage (Min)-Operate Time7.5msRelease Time3msFeaturesSealed - HermeticallyMounting TypeSocketableTermination StylePlug In	Package	-
Coil Type Non Latching Coil Current 46.1mA Coil Voltage 15VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 2A Switching Voltage 125VAC, 150VDC - Max Turn On Voltage (Max) 6.8 VDC Turn Off Voltage (Min) - Operate Time 7.5ms Release Time 3ms Features Sealed - Hermetically Mounting Type Socketable Termination Style Plug In	Series	V23162, AXICOM
Coil Current46.1mACoil Voltage15VDCContact FormDPDT (2 Form C)Contact Rating (Current)2ASwitching Voltage125VAC, 150VDC - MaxTurn On Voltage (Max)6.8 VDCTurn Off Voltage (Min)-Operate Time7.5msRelease Time3msFeaturesSealed - HermeticallyMounting TypeSocketableTermination StylePlug In	Relay Type	General Purpose
Coil Voltage 15VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 2A Switching Voltage 125VAC, 150VDC - Max Turn On Voltage (Max) 6.8 VDC Turn Off Voltage (Min) - Operate Time 7.5ms Release Time 3ms Features Sealed - Hermetically Mounting Type Socketable Termination Style Plug In	Coil Type	Non Latching
Contact Form DPDT (2 Form C) Contact Rating (Current) Switching Voltage 125VAC, 150VDC - Max Turn On Voltage (Max) 6.8 VDC Turn Off Voltage (Min) Operate Time 7.5ms Release Time 3ms Features Sealed - Hermetically Mounting Type Socketable Termination Style	Coil Current	46.1mA
Contact Rating (Current) Switching Voltage 125VAC, 150VDC - Max Turn On Voltage (Max) 6.8 VDC Turn Off Voltage (Min) Operate Time 7.5ms Release Time 3ms Features Sealed - Hermetically Mounting Type Socketable Termination Style Plug In	Coil Voltage	15VDC
Switching Voltage 125VAC, 150VDC - Max Turn On Voltage (Max) 6.8 VDC Turn Off Voltage (Min) - Operate Time 7.5ms Release Time 3ms Features Sealed - Hermetically Mounting Type Socketable Termination Style Plug In	Contact Form	DPDT (2 Form C)
Turn On Voltage (Max) Turn Off Voltage (Min) Operate Time 7.5ms Release Time 3ms Features Sealed - Hermetically Mounting Type Socketable Termination Style Plug In	Contact Rating (Current)	2A
Turn Off Voltage (Min) Operate Time 7.5ms Release Time 3ms Features Sealed - Hermetically Mounting Type Socketable Termination Style Plug In	Switching Voltage	125VAC, 150VDC - Max
Operate Time 7.5ms Release Time 3ms Features Sealed - Hermetically Mounting Type Socketable Termination Style Plug In	Turn On Voltage (Max)	6.8 VDC
Release Time 3ms Features Sealed - Hermetically Mounting Type Socketable Termination Style Plug In	Turn Off Voltage (Min)	-
Features Sealed - Hermetically Mounting Type Socketable Termination Style Plug In	Operate Time	7.5ms
Mounting Type Socketable Termination Style Plug In	Release Time	3ms
Termination Style Plug In	Features	Sealed - Hermetically
	Mounting Type	Socketable
Report errors?	Termination Style	Plug In
T		Report errors?

3-1393818-2 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

3-1393818-2 Payment Methods





















3-1393818-2 Shipping Methods













If you have any question about 3-1393818-2, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com