

3-1470209-2

3-1470209-2 Information

Heisener.com	Part Number	3-1470209-2	
	Manufacturer	TE Connectivity AMP Connectors	ा अन्ध्र जा
	Category	Connectors, Interconnects	
		Rectangular Connectors - Headers, Receptacles, Female Sockets	
	Description	CONN RCPT 18POS DL 2MM 8GOLD T/H	- F-6-67.25
	Package	-	E 10 20 4
For Reference Only		For the pricing/inventory/lead time, please contact	TELEVISIE''''
		us	
		Website: https://www.heisener.com	Request a Quote
		E-mail: salesdept@heisener.com	

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



3-1470209-2 Specifications

Manufacturer Part Number3-1470209-2Manufacturer ATE Connectory AMP ConnectorsCategoryConnectors, InterconnectsRectangular Connectors - Headers, Receptacles, Female SocketsPackage-SeriesAMPMODUConnector TypeReceptacleContact TypeReceptacleSortact TypeBoardNumber of Positions LoadedAINumber of Positions LoadedAINumber of Rows2Row Spacing - MatingOto/P'' (2.00mm)Mounting TypeThrough HoleTerminationSolderFastening TypeQualContact Finish - MatingGoldContact Finish - MatingMin (0.20µm)Insulation ColorBlackInsulation Finish Thickness - MatingMin (0.20µm)Contact Finish Thickness - MatingMin (0.20µm)Contact Length - Post0.102" (2.60mm)Contact Length - Post.102" (2.60mm)Contact Finish F				
CategoryConnectors, InterconnectsRectangular Connectors - Headers, Receptacles, Female SocketsPackage-SeriesAMPMODUConnector TypeReceptacleContact TypeFemale SocketStyleBoard to BoardNumber of Positions18Number of Positions LoadedAllNumber of Rows2Row Spacing - Mating0.079" (2.00mm)Number of Rows2Row Spacing - MatingSolderMounting TypeThrough HoleFreminationSolderContact Finish - MatingGoldContact Finish Thickness - MatingSolderInsulation ColorBlackInsulation Height0.177" (4.50mm)Contact Length - Post0.102" (2.00mm)Staten TypeSolderStaten TypeSolderContact Finish Thickness - MatingSolderStaten TypeSolderStaten TypeSolder<	Manufacturer Part Number	3-1470209-2		
Rectangular Connectors - Headers, Receptacles, Female SocketsPackage-SeriesAMPMODUConnector TypeReceptacleContact TypeFemale SocketStyleBoard to BoardNumber of Positions18Number of Positions LoadedAllPitch - Mating0.079" (2.00mm)Number of Rows2Row Spacing - Mating0.079" (2.00mm)Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - MatingBiackInsulation ColorBlackInsulation Height0.177" (4.50mm)Contact Length - Post0.102" (2.60mm)Contact Length - Post-40°C ~ 105°C	Manufacturer	TE Connectivity AMP Connectors		
Package-SeriesAMPMODUConnector TypeReceptacleContact TypeFemale SocketStyleBoard to BoardNumber of Positions18Number of Positions LoadedAllPitch - Mating0.079" (2.00mm)Number of Rows2Row Spacing - Mating0.079" (2.00mm)Mounting Type0.079" (2.00mm)Youring TypeSolderFarening TypeSolderFortart Finish - MatingGoldContact Finish - MatingGoldSolderSundoncolorInsulation ColorBackInsulation Finish - Mating0.177" (4.50mm)Contact Finish Thickness - Mating0.102" (2.60mm)Solder Finish Thickness - Mating0.102" (2.60mm)Contact Finish Type0.102" (2.60mm)Contact Finish Type0.102" (2.60mm)Solder Finish Type	Category	Connectors, Interconnects		
SeriesAMPMODUConnector TypeReceptacleContact TypeFemale SocketStyleBoard to BoardNumber of PositionsI8Number of Positions LoadedAllPitch - Mating0.079" (2.00mm)Number of Rows2Row Spacing - Mating0.079" (2.00mm)Mounting TypeOndy" (2.00mm)FreminationSolderFastening TypeSolderContact Finish - MatingGoldContact Finish - MatingBin (0.20µm)Insulation ColorBackInsulation Height0.177" (4.50µm)Contact Length - Post0.102" (2.00µm)Contact Finish Thotkness - Mating0.102" (2.00µm)Contact Length - Post0.102" (2.00µm)Contact Finish Thotkness - Mating0.102" (2.00µm)Contact Length - Post0.102" (2.00µm) </td <td></td> <td colspan="2">Rectangular Connectors - Headers, Receptacles, Female Sockets</td>		Rectangular Connectors - Headers, Receptacles, Female Sockets		
Connector TypeReceptacleContact TypeFemale SocketStyleBoard to BoardNumber of Positions18Number of Positions LoadedAllPitch - Mating0.079" (.200mm)Number of Rows2Row Spacing - Mating0.079" (.200mm)Mounting TypeThrough HoleTerminationSolderContact Finish - MatingGoldContact Finish - MatingGoldInsulation ColorBlackInsulation Height0.17" (4.50mm)Contact Length - Post0.102" (2.60mm)Contact Finish - Mating0.102" (2.60mm)Contact Finish - Post0.102" (2.60mm)Contact Finish - Mating0.102" (2.60mm)Contact Length - Post0.102" (2.60mm)Contact Finish - Post0.102" (2.60m	Package	-		
Contact TypeFemale SocketStyleBoard to BoardNumber of Positions18Number of Positions LoadedAllPitch - Mating0.079" (2.00mm)Number of Rows2Row Spacing - Mating0.079" (2.00mm)Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldInsulation ColorBlackInsulation Height0.17" (4.50mm)Contact Length - Post0.102" (2.60mm)Operating Temperature40°C ~ 105°C	Series	AMPMODU		
StyleBoard to BoardNumber of Positions18Number of Positions LoadedAllPitch - Mating0.079" (2.00mm)Number of Rows2Row Spacing - Mating0.079" (2.00mm)Mounting Type0.079" (2.00mm)TerminationSolderFastening TypePush-PullContact Finish - MatingGoldInsulation ColorBlackInsulation Height0.177" (4.50mm)Contact Length - Post0.102" (2.60mm)Operating Temperature-40°C ~ 105°C	Connector Type	Receptacle		
Number of Positions 18 Number of Positions Loaded All Pitch - Mating 0.079" (2.00mm) Number of Rows 2 Row Spacing - Mating 0.079" (2.00mm) Mounting Type 0.079" (2.00mm) Termination 0.079" (2.00mm) Termination Solder Fastening Type Push-Pull Contact Finish - Mating Gold Contact Finish Thickness - Mating Black Insulation Color Black Insulation Height 0.177" (4.50mm) Operating Temperature -40°C ~ 105°C	Contact Type	Female Socket		
Number of Positions LoadedAllPitch - Mating0.079" (2.00mm)Number of Rows2Row Spacing - Mating0.079" (2.00mm)Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - MatingBlackInsulation Color0.177" (4.50mm)Contact Length - Post0.102" (2.60mm)Operating Temperature40°C ~ 105°C	Style	Board to Board		
Pitch - Mating0.079" (2.00mm)Number of Rows2Row Spacing - Mating0.079" (2.00mm)Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - MatingBiackInsulation ColorJ.177" (4.50mm)Contact Length - Post0.102" (2.60mm)Operating Temperature-40°C ~ 105°C	Number of Positions	18		
Number of Rows2Row Spacing - Mating0.079" (2.00mm)Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - MatingBlackInsulation ColorBlackInsulation Height0.177" (4.50mm)Contact Length - Post0.102" (2.60mm)Operating Temperature-40°C ~ 105°C	Number of Positions Loaded	All		
Row Spacing - Mating0.079" (2.00mm)Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - MatingBiackInsulation Color0.177" (4.50mm)Contact Length - Post0.102" (2.60mm)Operating Temperature-40°C ~ 105°C	Pitch - Mating	0.079" (2.00mm)		
Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - MatingBµin (0.20µm)Insulation ColorBlackInsulation Height0.177" (4.50mm)Contact Length - Post0.102" (2.60mm)Operating Temperature-40°C ~ 105°C	Number of Rows	2		
TerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating&µin (0.20µm)Insulation ColorBlackInsulation Height0.177" (4.50mm)Contact Length - Post0.102" (2.60mm)Operating Temperature-40°C ~ 105°C	Row Spacing - Mating	0.079" (2.00mm)		
Fastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating8µin (0.20µm)Insulation ColorBlackInsulation Height0.177" (4.50mm)Contact Length - Post0.102" (2.60mm)Operating Temperature40°C ~ 105°C	Mounting Type	Through Hole		
Contact Finish - MatingGoldContact Finish Thickness - Mating8µin (0.20µm)Insulation ColorBlackInsulation Height0.177" (4.50mm)Contact Length - Post0.102" (2.60mm)Operating Temperature-40°C ~ 105°C	Termination	Solder		
Contact Finish Thickness - Mating8µin (0.20µm)Insulation ColorBlackInsulation Height0.177" (4.50mm)Contact Length - Post0.102" (2.60mm)Operating Temperature-40°C ~ 105°C	Fastening Type	Push-Pull		
Insulation ColorBlackInsulation Height0.177" (4.50mm)Contact Length - Post0.102" (2.60mm)Operating Temperature-40°C ~ 105°C	Contact Finish - Mating	Gold		
Insulation Height 0.177" (4.50mm) Contact Length - Post 0.102" (2.60mm) Operating Temperature -40°C ~ 105°C	Contact Finish Thickness - Mating	8µin (0.20µm)		
Contact Length - Post0.102" (2.60mm)Operating Temperature-40°C ~ 105°C	Insulation Color	Black		
Operating Temperature $-40^{\circ}\text{C} \sim 105^{\circ}\text{C}$	Insulation Height	0.177" (4.50mm)		
	Contact Length - Post	0.102" (2.60mm)		
	Operating Temperature	-40°C ~ 105°C		
Material Flammability Rating UL94 V-0	Material Flammability Rating	UL94 V-0		

Contact Finish - Post	Tin		
Mated Stacking Heights	-		
Ingress Protection	-		
Features	-		
		Report errors	?

3-1470209-2 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.



If you have any question about 3-1470209-2, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com