

3-1617076-7 Information

Heisener.com

Part Number 3-1617076-7

Manufacturer TE Connectivity Aerospace, Defense and Marine

Category Relays

Signal Relays, Up to 2 Amps

Description RELAY GENERAL PURPOSE 4PDT 2A

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









3-1617076-7 Specifications

Manufacturer Part Number 3-1617076-7 Manufacturer TE Connectivity Aerospace, Defense and Marine Category Relays Signal Relays, Up to 2 Amps Package - Series 3SBH, CII Relay Type General Purpose Coil Type Non Latching Coil Current - Coil Voltage - Contact Form 4PDT (4 Form C) Contact Rating (Current) 2A Switching Voltage 115VAC, 28VDC - Max Turn On Voltage (Max) - Turn Off Voltage (Min) - Operate Time - Release Time - Features Sealed - Hermetically Mounting Type - Termination Style -		
CategoryRelaysPackage-Series3SBH, CIIRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current-Coil Voltage-Contact Form4PDT (4 Form C)Contact Rating (Current)2ASwitching Voltage115VAC, 28VDC - MaxTurn On Voltage (Max)-Turn Off Voltage (Min)-Operate Time-Release Time-FeaturesSealed - HermeticallyMounting Type-Termination Style-	Manufacturer Part Number	3-1617076-7
Package-Series3SBH, CIIRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current-Coil Voltage-Contact Form4PDT (4 Form C)Contact Rating (Current)2ASwitching Voltage115VAC, 28VDC - MaxTurn On Voltage (Max)-Turn Off Voltage (Min)-Operate Time-Release Time-FeaturesSealed - HermeticallyMounting Type-Termination Style-	Manufacturer	TE Connectivity Aerospace, Defense and Marine
Package - Series 3SBH, CII Relay Type General Purpose Coil Type Non Latching Coil Current - Coil Voltage - Contact Form 4PDT (4 Form C) Contact Rating (Current) 2A Switching Voltage 115VAC, 28VDC - Max Turn On Voltage (Max) - Turn Off Voltage (Min) - Operate Time - Relase Time - Features Sealed - Hermetically Mounting Type - Termination Style -	Category	Relays
Series 3SBH, CII Relay Type General Purpose Coil Type Non Latching Coil Current - Coil Voltage - Contact Form 4PDT (4 Form C) Contact Rating (Current) 2A Switching Voltage 115VAC, 28VDC - Max Turn On Voltage (Max) - Turn Off Voltage (Min) - Operate Time - Release Time - Features Sealed - Hermetically Mounting Type - Termination Style -		Signal Relays, Up to 2 Amps
Relay TypeGeneral PurposeCoil TypeNon LatchingCoil Current-Coil Voltage-Contact Form4PDT (4 Form C)Contact Rating (Current)2ASwitching Voltage115VAC, 28VDC - MaxTurn On Voltage (Max)-Turn Off Voltage (Min)-Operate Time-Release Time-FeaturesSealed - HermeticallyMounting Type-Termination Style-	Package	-
Coil TypeNon LatchingCoil Current-Coil Voltage-Contact Form4PDT (4 Form C)Contact Rating (Current)2ASwitching Voltage115VAC, 28VDC - MaxTurn On Voltage (Max)-Turn Off Voltage (Min)-Operate Time-Release Time-FeaturesSealed - HermeticallyMounting Type-Termination Style-	Series	3SBH, CII
Coil Current Coil Voltage - Contact Form 4PDT (4 Form C) Contact Rating (Current) 2A Switching Voltage 115VAC, 28VDC - Max Turn On Voltage (Max) - Turn Off Voltage (Min) Operate Time Release Time - Features Sealed - Hermetically Mounting Type - Termination Style -	Relay Type	General Purpose
Coil Voltage - 4PDT (4 Form C) Contact Form 2A Contact Rating (Current) 2A Switching Voltage 115VAC, 28VDC - Max Turn On Voltage (Max) - Turn Off Voltage (Min) - Operate Time - Release Time - Features Sealed - Hermetically Mounting Type - Termination Style -	Coil Type	Non Latching
Contact Form 4PDT (4 Form C) Contact Rating (Current) 2A Switching Voltage 115VAC, 28VDC - Max Turn On Voltage (Max) - Turn Off Voltage (Min) - Operate Time - Release Time - Features Sealed - Hermetically Mounting Type - Termination Style -	Coil Current	-
Contact Rating (Current) Switching Voltage 115VAC, 28VDC - Max Turn On Voltage (Max) - Turn Off Voltage (Min) Operate Time Release Time Features Sealed - Hermetically Mounting Type - Termination Style 2A Switching (Current) - Saled - Max - Substitute (Min) - Substitute (Coil Voltage	-
Switching Voltage 115VAC, 28VDC - Max Turn On Voltage (Max) - Turn Off Voltage (Min) - Operate Time - Release Time - Features Sealed - Hermetically Mounting Type - Termination Style -	Contact Form	4PDT (4 Form C)
Turn On Voltage (Max) Turn Off Voltage (Min) Operate Time Release Time - Features Sealed - Hermetically Mounting Type - Termination Style -	Contact Rating (Current)	2A
Turn Off Voltage (Min) Operate Time Release Time Features Sealed - Hermetically Mounting Type - Termination Style -	Switching Voltage	115VAC, 28VDC - Max
Operate Time - Release Time - Sealed - Hermetically Mounting Type - Termination Style - Sealed - Hermetically - Hermetically - Sealed - Hermetically - Hermetically - Sealed - Hermetically - Hermetic	Turn On Voltage (Max)	-
Release Time - Features Sealed - Hermetically Mounting Type - Termination Style -	Turn Off Voltage (Min)	-
Features Sealed - Hermetically Mounting Type - Termination Style -	Operate Time	-
Mounting Type - Termination Style -	Release Time	-
Termination Style -	Features	Sealed - Hermetically
·	Mounting Type	-
Report errors?	Termination Style	-
		Report errors?

3-1617076-7 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

3-1617076-7 Payment Methods



















3-1617076-7 Shipping Methods













If you have any question about 3-1617076-7, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com