

3-2172089-2 Information



For Reference Only

Part Number 3-2172089-2

Manufacturer TE Connectivity AMP Connectors

Category Connectors, Interconnects
Circular Connectors

Description CONN RCPT 4POS PNL MT SKT PCB M8

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









3-2172089-2 Specifications

Manufacturer Part Number Manufacturer TE Connectivity AMP Connectors Category Connectors, Interconnects Circular Connectors Package - Series M8 Connector Type Receptacle, Female Sockets Number of Positions 4 Shell Size - Insert M8-4 Shell Size, MIL - Mounting Type Panel Mount, Bulkhead - Front Side Nut; Through Hole Termination Solder Fastening Type Push-Pull Orientation - Ingress Protection Shell Material, Finish Contact Finish Gold Features Voltage - Rated Voltage - Rated Current Rating 4A		
CategoryConnectors, InterconnectsPackage-SeriesM8Connector TypeReceptacle, Female SocketsNumber of Positions4Shell Size - InsertM8-4Shell Size, MIL-Mounting TypePanel Mount, Bulkhead - Front Side Nut; Through HoleTerminationSolderFastening TypePush-PullOrientation-Ingress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishZinc Die Cast, Nickel PlatedContact FinishGoldFeaturesBoard Lock, ShieldedVoltage - Rated30VAC/DCCurrent Rating4A	Manufacturer Part Number	3-2172089-2
Package-SeriesM8Connector TypeReceptacle, Female SocketsNumber of Positions4Shell Size - InsertM8-4Shell Size, MIL-Mounting TypePanel Mount, Bulkhead - Front Side Nut; Through HoleTerminationSolderFastening TypePush-PullOrientation-Ingress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishZinc Die Cast, Nickel PlatedContact FinishGoldFeaturesBoard Lock, ShieldedVoltage - Rated30VAC/DCCurrent Rating4A	Manufacturer	TE Connectivity AMP Connectors
Package-SeriesM8Connector TypeReceptacle, Female SocketsNumber of Positions4Shell Size - InsertM8-4Shell Size, MIL-Mounting TypePanel Mount, Bulkhead - Front Side Nut; Through HoleTerminationSolderFastening TypePush-PullOrientation-Ingress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishZinc Die Cast, Nickel PlatedContact FinishGoldFeaturesBoard Lock, ShieldedVoltage - Rated30VAC/DCCurrent Rating4A	Category	Connectors, Interconnects
SeriesM8Connector TypeReceptacle, Female SocketsNumber of Positions4Shell Size - InsertM8-4Shell Size, MIL-Mounting TypePanel Mount, Bulkhead - Front Side Nut; Through HoleTerminationSolderFastening TypePush-PullOrientation-Ingress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishZinc Die Cast, Nickel PlatedContact FinishGoldFeaturesBoard Lock, ShieldedVoltage - Rated30VAC/DCCurrent Rating4A		Circular Connectors
Connector Type Receptacle, Female Sockets Number of Positions 4 Shell Size - Insert M8-4 Shell Size, MIL - Mounting Type Panel Mount, Bulkhead - Front Side Nut; Through Hole Termination Solder Fastening Type Push-Pull Orientation - Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Zinc Die Cast, Nickel Plated Contact Finish Gold Features Board Lock, Shielded Voltage - Rated 30VAC/DC Current Rating 4A	Package	-
Number of Positions Shell Size - Insert M8-4 Shell Size, MIL Mounting Type Panel Mount, Bulkhead - Front Side Nut; Through Hole Termination Solder Fastening Type Push-Pull Orientation - Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Zinc Die Cast, Nickel Plated Contact Finish Gold Features Board Lock, Shielded Voltage - Rated 30VAC/DC Current Rating 4A	Series	M8
Shell Size - Insert Shell Size, MIL - Mounting Type Panel Mount, Bulkhead - Front Side Nut; Through Hole Termination Solder Fastening Type Push-Pull Orientation - Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Zinc Die Cast, Nickel Plated Contact Finish Gold Features Board Lock, Shielded Voltage - Rated 30VAC/DC Current Rating 4A	Connector Type	Receptacle, Female Sockets
Shell Size, MIL Mounting Type Panel Mount, Bulkhead - Front Side Nut; Through Hole Termination Solder Fastening Type Push-Pull Orientation - Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Zinc Die Cast, Nickel Plated Contact Finish Gold Features Board Lock, Shielded Voltage - Rated 30VAC/DC Current Rating 4A	Number of Positions	4
Mounting Type Panel Mount, Bulkhead - Front Side Nut; Through Hole Termination Solder Fastening Type Push-Pull Orientation - Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Zinc Die Cast, Nickel Plated Contact Finish Gold Features Board Lock, Shielded Voltage - Rated 30VAC/DC Current Rating 4A	Shell Size - Insert	M8-4
Termination Solder Fastening Type Push-Pull Orientation - Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Zinc Die Cast, Nickel Plated Contact Finish Gold Features Board Lock, Shielded Voltage - Rated 30VAC/DC Current Rating 4A	Shell Size, MIL	-
Fastening Type Push-Pull Orientation - Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Zinc Die Cast, Nickel Plated Contact Finish Gold Features Board Lock, Shielded Voltage - Rated 30VAC/DC Current Rating 4A	Mounting Type	Panel Mount, Bulkhead - Front Side Nut; Through Hole
Orientation - Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Zinc Die Cast, Nickel Plated Contact Finish Gold Features Board Lock, Shielded Voltage - Rated 30VAC/DC Current Rating 4A	Termination	Solder
Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Zinc Die Cast, Nickel Plated Contact Finish Gold Features Board Lock, Shielded Voltage - Rated 30VAC/DC Current Rating 4A	Fastening Type	Push-Pull
Shell Material, Finish Contact Finish Gold Features Board Lock, Shielded Voltage - Rated Current Rating 4A	Orientation	-
Contact Finish Gold Features Board Lock, Shielded Voltage - Rated 30VAC/DC Current Rating 4A	Ingress Protection	IP67 - Dust Tight, Waterproof
Features Board Lock, Shielded Voltage - Rated 30VAC/DC Current Rating 4A	Shell Material, Finish	Zinc Die Cast, Nickel Plated
Voltage - Rated 30VAC/DC Current Rating 4A	Contact Finish	Gold
Current Rating 4A	Features	Board Lock, Shielded
	Voltage - Rated	30VAC/DC
Report errors?	Current Rating	4A
Report circles.		Report errors?

3-2172089-2 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

3-2172089-2 Payment Methods



















3-2172089-2 Shipping Methods













If you have any question about 3-2172089-2, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com