

3-2834074-2 Information



For Reference Only

Part Number 3-2834074-2

Manufacturer TE Connectivity AMP Connectors

Category Connectors, Interconnects Solid State Lighting Connectors

Description 2P PLUG, MINIATURE WATERPROOF CO

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









3-2834074-2 Specifications

Manufacturer Part Number 3-2834074-2 Manufacturer TE Connectivity AMP Connectors Category Connectors, Interconnects Package - Series SlimSeal Style Cable/Wire to Cable/Wire Connector Type Plug Housing for Socket Contact Number of Positions 2 Mounting Type Free Hanging (In-Line) Termination Crimp Pitch 0.098" (2.50mm) Fastening Type Latch Lock Features - Housing Color Red Wire Gauge - Contact Material - Contact Finish - Housing Material Thermoplastic Operating Temperature -40°C ~ 105°C Report errors?		
CategoryConnectors, InterconnectsPackage-SeriesSlimSealStyleCable/Wire to Cable/WireConnector TypePlug Housing for Socket ContactNumber of Positions2Mounting TypeFree Hanging (In-Line)TerminationCrimpePitch0.098" (2.50mm)Fastening TypeLatch LockFeatures-Housing ColorRedWire Gauge-Contact Material-Contact Finish-Housing MaterialThermoplasticOperating Temperature-40°C ~ 105°C	Manufacturer Part Number	3-2834074-2
Package - Series SlimSeal Style Cable/Wire to Cable/Wire Connector Type Plug Housing for Socket Contact Number of Positions 2 Mounting Type Free Hanging (In-Line) Termination Crimp Pitch 0.098" (2.50mm) Fastening Type Latch Lock Features - Housing Color Red Wire Gauge - Contact Material - Contact Finish - Housing Material Thermoplastic Operating Temperature -40°C ~ 105°C	Manufacturer	TE Connectivity AMP Connectors
Package-SeriesSlimSealStyleCable/Wire to Cable/WireConnector TypePlug Housing for Socket ContactNumber of Positions2Mounting TypeFree Hanging (In-Line)TerminationCrimpPitch0.098" (2.50mm)Fastening TypeLatch LockFeatures-Housing ColorRedWire Gauge-Contact Material-Contact Finish-Housing MaterialThermoplasticOperating Temperature-40°C ~ 105°C	Category	Connectors, Interconnects
Series SlimSeal Style Cable/Wire to Cable/Wire Connector Type Plug Housing for Socket Contact Number of Positions 2 Mounting Type Free Hanging (In-Line) Termination Crimp Pitch 0.098" (2.50mm) Fastening Type Latch Lock Features - Housing Color Red Wire Gauge - Contact Material - Contact Finish - Housing Material Thermoplastic Operating Temperature -40°C ~ 105°C		Solid State Lighting Connectors
StyleCable/Wire to Cable/WireConnector TypePlug Housing for Socket ContactNumber of Positions2Mounting TypeFree Hanging (In-Line)TerminationCrimpPitch0.098" (2.50mm)Fastening TypeLatch LockFeatures-Housing ColorRedWire Gauge-Contact Material-Contact Finish-Housing MaterialThermoplasticOperating Temperature-40°C ~ 105°C	Package	-
Connector Type Plug Housing for Socket Contact Number of Positions 2 Mounting Type Free Hanging (In-Line) Termination Crimp Pitch 0.098" (2.50mm) Fastening Type Latch Lock Features - Housing Color Red Wire Gauge - Contact Material - Contact Finish - Housing Material Thermoplastic Operating Temperature - Plug Housing for Socket Contact Red Ausing Clar Free Hanging (In-Line) Free Hanging (In-Line) Free Hanging (In-Line) Red	Series	SlimSeal
Number of Positions2Mounting TypeFree Hanging (In-Line)TerminationCrimpPitch0.098" (2.50mm)Fastening TypeLatch LockFeatures-Housing ColorRedWire Gauge-Contact Material-Contact Finish-Housing MaterialThermoplasticOperating Temperature-40°C ~ 105°C	Style	Cable/Wire to Cable/Wire
Mounting TypeFree Hanging (In-Line)TerminationCrimpPitch0.098" (2.50mm)Fastening TypeLatch LockFeatures-Housing ColorRedWire Gauge-Contact Material-Contact Finish-Housing MaterialThermoplasticOperating Temperature-40°C ~ 105°C	Connector Type	Plug Housing for Socket Contact
Termination Crimp Pitch 0.098" (2.50mm) Fastening Type Latch Lock Features - Housing Color Red Wire Gauge - Contact Material - Contact Finish - Housing Material Thermoplastic Operating Temperature -40°C ~ 105°C	Number of Positions	2
Pitch 0.098" (2.50mm) Fastening Type Latch Lock Features - Housing Color Red Wire Gauge - Contact Material - Contact Finish - Housing Material Thermoplastic Operating Temperature -40°C ~ 105°C	Mounting Type	Free Hanging (In-Line)
Fastening Type Latch Lock Features - Housing Color Red Wire Gauge - Contact Material - Contact Finish - Housing Material Thermoplastic Operating Temperature Latch Lock - Thermoplastic40°C ~ 105°C	Termination	Crimp
Features - Housing Color Red Wire Gauge - Contact Material - Contact Finish - Housing Material Thermoplastic Operating Temperature -40°C ~ 105°C	Pitch	0.098" (2.50mm)
Housing Color Wire Gauge Contact Material Contact Finish Housing Material Thermoplastic Operating Temperature Red	Fastening Type	Latch Lock
Wire Gauge - Contact Material - Contact Finish - Housing Material Thermoplastic Operating Temperature -40°C ~ 105°C	Features	-
Contact Material - Contact Finish - Housing Material Thermoplastic Operating Temperature -40°C ~ 105°C	Housing Color	Red
Contact Finish - Housing Material Thermoplastic Operating Temperature -40°C ~ 105°C	Wire Gauge	-
Housing Material Thermoplastic Operating Temperature $-40^{\circ}\text{C} \sim 105^{\circ}\text{C}$	Contact Material	-
Operating Temperature $-40^{\circ}\text{C} \sim 105^{\circ}\text{C}$	Contact Finish	-
	Housing Material	Thermoplastic
Report errors?	Operating Temperature	-40°C ~ 105°C
		Report errors?

3-2834074-2 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

3-2834074-2 Payment Methods





















3-2834074-2 Shipping Methods













If you have any question about 3-2834074-2, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com