

30 PSI-D-4V Information

Heisener.com

Part Number 30 PSI-D-4V

ManufacturerAll Sensors CorporationCategorySensors, Transducers

Pressure Sensors, Transducers

Description SENSOR 30PSID 4V DUAL

Package 4-SIP Module

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









30 PSI-D-4V Specifications

Manufacturer Part Number 30 PSI-D-4V Manufacturer All Sensors Corporation Category Sensors, Transducers Package 4-SIP Module Series AXCA Pressure Type Differential Operating Pressure ±30 PSI (±206.84 kPa) Output Type Analog Voltage Output 0.25 V ~ 4.25 V Accuracy ±0.5% Voltage - Supply 4.5 V ~ 5.5 V Port Size Male - 0.19" (4.8mm) Tube, Dual Port Style Barbless Features Amplified Output, Temperature Compensated Termination Style PCB Maximum Pressure ±60 PSI (±413.69 kPa) Operating Temperature -25°C ~ 85°C Package / Case 4-SIP Module Supplier Device Package - In Processory Report errors?		
CategorySensors, TransducersPackage4-SIP ModuleSeriesAXCAPressure TypeDifferentialOperating Pressure±30 PSI (±206.84 kPa)Output TypeAnalog VoltageOutput0.25 V ~ 4.25 VAccuracy±0.5%Voltage - Supply4.5 V ~ 5.5 VPort SizeMale - 0.19" (4.8mm) Tube, DualPort StyleBarblessFeaturesAmplified Output, Temperature CompensatedTermination StylePCBMaximum Pressure±60 PSI (±413.69 kPa)Operating Temperature-25°C ~ 85°CPackage / Case4-SIP ModuleSupplier Device Package-	Manufacturer Part Number	30 PSI-D-4V
Package 4-SIP Module Series AXCA Pressure Type Differential Operating Pressure	Manufacturer	All Sensors Corporation
Package4-SIP ModuleSeriesAXCAPressure TypeDifferentialOperating Pressure±30 PSI (±206.84 kPa)Output TypeAnalog VoltageOutput0.25 V ~ 4.25 VAccuracy±0.5%Voltage - Supply4.5 V ~ 5.5 VPort SizeMale - 0.19" (4.8mm) Tube, DualPort StyleBarblessFeaturesAmplified Output, Temperature CompensatedTermination StylePCBMaximum Pressure±60 PSI (±413.69 kPa)Operating Temperature-25°C ~ 85°CPackage / Case4-SIP ModuleSupplier Device Package-	Category	Sensors, Transducers
SeriesAXCAPressure TypeDifferentialOperating Pressure±30 PSI (±206.84 kPa)Output TypeAnalog VoltageOutput0.25 V ~ 4.25 VAccuracy±0.5%Voltage - Supply4.5 V ~ 5.5 VPort SizeMale - 0.19" (4.8mm) Tube, DualPort StyleBarblessFeaturesAmplified Output, Temperature CompensatedTermination StylePCBMaximum Pressure±60 PSI (±413.69 kPa)Operating Temperature-25°C ~ 85°CPackage / Case4-SIP ModuleSupplier Device Package-		Pressure Sensors, Transducers
Pressure Type Operating Pressure ±30 PSI (±206.84 kPa) Output Type Analog Voltage Output 0.25 V ~ 4.25 V Accuracy ±0.5% Voltage - Supply 4.5 V ~ 5.5 V Port Size Male - 0.19" (4.8mm) Tube, Dual Port Style Barbless Features Amplified Output, Temperature Compensated Termination Style Maximum Pressure ±60 PSI (±413.69 kPa) Operating Temperature -25°C ~ 85°C Package / Case 4-SIP Module Supplier Device Package	Package	4-SIP Module
Operating Pressure $\pm 30 \text{ PSI } (\pm 206.84 \text{ kPa})$ Output Type Analog Voltage Output $0.25 \text{ V} \sim 4.25 \text{ V}$ Accuracy $\pm 0.5\%$ Voltage - Supply $4.5 \text{ V} \sim 5.5 \text{ V}$ Port Size Male - 0.19 " (4.8mm) Tube, Dual Port Style Barbless Features Amplified Output, Temperature Compensated Termination Style PCB Maximum Pressure $\pm 60 \text{ PSI } (\pm 413.69 \text{ kPa})$ Operating Temperature $-25^{\circ}\text{C} \sim 85^{\circ}\text{C}$ Package / Case $4-\text{SIP Module}$ Supplier Device Package	Series	AXCA
Output Type Output Outp	Pressure Type	Differential
Output $0.25 \text{ V} \sim 4.25 \text{ V}$ Accuracy $\pm 0.5\%$ Voltage - Supply $4.5 \text{ V} \sim 5.5 \text{ V}$ Port SizeMale - 0.19 " (4.8mm) Tube, DualPort StyleBarblessFeaturesAmplified Output, Temperature CompensatedTermination StylePCBMaximum Pressure $\pm 60 \text{ PSI } (\pm 413.69 \text{ kPa})$ Operating Temperature $-25^{\circ}\text{C} \sim 85^{\circ}\text{C}$ Package / Case $4-\text{SIP Module}$ Supplier Device Package-	Operating Pressure	±30 PSI (±206.84 kPa)
Accuracy ±0.5% Voltage - Supply 4.5 V ~ 5.5 V Port Size Male - 0.19" (4.8mm) Tube, Dual Port Style Barbless Features Amplified Output, Temperature Compensated Termination Style PCB Maximum Pressure ±60 PSI (±413.69 kPa) Operating Temperature -25°C ~ 85°C Package / Case 4-SIP Module Supplier Device Package	Output Type	Analog Voltage
Voltage - Supply 4.5 V ~ 5.5 V Port Size Male - 0.19" (4.8mm) Tube, Dual Port Style Barbless Features Amplified Output, Temperature Compensated Termination Style PCB Maximum Pressure ±60 PSI (±413.69 kPa) Operating Temperature -25°C ~ 85°C Package / Case 4-SIP Module Supplier Device Package -	Output	0.25 V ~ 4.25 V
Port Size Male - 0.19" (4.8mm) Tube, Dual Port Style Barbless Features Amplified Output, Temperature Compensated Termination Style PCB Maximum Pressure ±60 PSI (±413.69 kPa) Operating Temperature -25°C ~ 85°C Package / Case 4-SIP Module Supplier Device Package -	Accuracy	±0.5%
Port Style Barbless Features Amplified Output, Temperature Compensated Termination Style PCB Maximum Pressure ±60 PSI (±413.69 kPa) Operating Temperature -25°C ~ 85°C Package / Case 4-SIP Module Supplier Device Package	Voltage - Supply	4.5 V ~ 5.5 V
Features Amplified Output, Temperature Compensated Termination Style PCB Maximum Pressure $\pm 60 \text{ PSI } (\pm 413.69 \text{ kPa})$ Operating Temperature $-25^{\circ}\text{C} \sim 85^{\circ}\text{C}$ Package / Case $\pm 4-\text{SIP Module}$ Supplier Device Package $\pm 60 \text{ PSI } (\pm 413.69 \text{ kPa})$	Port Size	Male - 0.19" (4.8mm) Tube, Dual
Termination Style PCB Maximum Pressure $\pm 60 \text{ PSI } (\pm 413.69 \text{ kPa})$ Operating Temperature $-25^{\circ}\text{C} \sim 85^{\circ}\text{C}$ Package / Case 4-SIP Module Supplier Device Package $-$	Port Style	Barbless
Maximum Pressure ± 60 PSI (± 413.69 kPa)Operating Temperature -25° C $\sim 85^{\circ}$ CPackage / Case 4 -SIP ModuleSupplier Device Package-	Features	Amplified Output, Temperature Compensated
Operating Temperature -25°C ~ 85°C Package / Case 4-SIP Module Supplier Device Package -	Termination Style	PCB
Package / Case 4-SIP Module Supplier Device Package -	Maximum Pressure	±60 PSI (±413.69 kPa)
Supplier Device Package -	Operating Temperature	-25°C ~ 85°C
	Package / Case	4-SIP Module
Report errors?	Supplier Device Package	-
		Report errors?

30 PSI-D-4V Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

30 PSI-D-4V Payment Methods



















30 PSI-D-4V Shipping Methods













If you have any question about 30 PSI-D-4V, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com