

3006506 Information



For Reference Only

Part Number 3006506

Manufacturer Phoenix Contact

Category Connectors, Interconnects

Terminal Blocks - Din Rail, Channel

Description CONN TERM BLK FEED THRU 14-26AWG

Package

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









3006506	Specifications
2000200	Specifications

Manufacturer Part Number 3006506 Manufacturer Phoenix Contact Category Connectors, Interconnects Terminal Blocks - Din Rail, Channel Package - Series CLIPLINE ZVIOK Type Feed Through, Isolated Disconnect Type - Number of Positions 5 Number of Levels 2 Terminal - Width 5.2mm Termination Style Push In, Spring Current - IEC 17.5A Voltage - IEC 250V Current - UL 15A Voltage - UL 300V Wire Gauge or Range - AWG 14-26 AWG Wire Gauge or Range - mm² 0.14-2.5mm² Features - Color Gray		
Category Connectors, Interconnects Terminal Blocks - Din Rail, Channel Package - Series CLIPLINE ZVIOK Type Feed Through, Isolated Disconnect Type - Number of Positions 5 Number of Levels 2 Terminal - Width 5.2mm Termination Style Push In, Spring Current - IEC 17.5A Voltage - IEC 250V Current - UL 15A Voltage - UL 300V Wire Gauge or Range - AWG Wire Gauge or Range - amp² 0.14-2.5mm² Features - Color Gray	Manufacturer Part Number	3006506
Package - CLIPLINE ZVIOK Type Feed Through, Isolated Disconnect Type - Number of Positions 5 Number of Levels 2 Terminal - Width 5.2mm Termination Style Push In, Spring Current - IEC 17.5A Voltage - IEC 250V Current - UL 15A Voltage - UL 300V Wire Gauge or Range - AWG Wire Gauge or Range - mm² 0.14-2.5mm² Features - Color Gray	Manufacturer	Phoenix Contact
Package-SeriesCLIPLINE ZVIOKTypeFeed Through, IsolatedDisconnect Type-Number of Positions5Number of Levels2Terminal - Width5.2mmTermination StylePush In, SpringCurrent - IEC17.5AVoltage - IEC250VCurrent - UL15AVoltage - UL300VWire Gauge or Range - AWG14-26 AWGWire Gauge or Range - mm²0.14-2.5mm²Features-ColorGray	Category	Connectors, Interconnects
Series CLIPLINE ZVIOK Type Feed Through, Isolated Disconnect Type - Number of Positions 5 Number of Levels 2 Terminal - Width 5.2mm Termination Style Push In, Spring Current - IEC 17.5A Voltage - IEC 250V Current - UL 15A Voltage - UL 300V Wire Gauge or Range - AWG 14-26 AWG Wire Gauge or Range - mm² 0.14-2.5mm² Features - Color Gray		Terminal Blocks - Din Rail, Channel
Type Feed Through, Isolated Disconnect Type - Number of Positions 5 Number of Levels 2 Terminal - Width 5.2mm Termination Style Push In, Spring Current - IEC 17.5A Voltage - IEC 250V Current - UL 15A Voltage - UL 300V Wire Gauge or Range - AWG 14-26 AWG Wire Gauge or Range - mm² 0.14-2.5mm² Features - Color Gray	Package	-
Disconnect Type Number of Positions 5 Number of Levels 2 Terminal - Width 5.2mm Termination Style Push In, Spring Current - IEC 17.5A Voltage - IEC 250V Current - UL 15A Voltage - UL 300V Wire Gauge or Range - AWG Wire Gauge or Range - mm² O.14-2.5mm² Features Color Gray	Series	CLIPLINE ZVIOK
Number of Positions5Number of Levels2Terminal - Width5.2mmTermination StylePush In, SpringCurrent - IEC17.5AVoltage - IEC250VCurrent - UL15AVoltage - UL300VWire Gauge or Range - AWG14-26 AWGWire Gauge or Range - mm²0.14-2.5mm²Features-ColorGray	Туре	Feed Through, Isolated
Number of Levels 2 Terminal - Width 5.2mm Termination Style Push In, Spring Current - IEC 17.5A Voltage - IEC 250V Current - UL 15A Voltage - UL 300V Wire Gauge or Range - AWG 14-26 AWG Wire Gauge or Range - mm² 0.14-2.5mm² Features - Color Gray	Disconnect Type	-
Terminal - Width Termination Style Push In, Spring Current - IEC 17.5A Voltage - IEC 250V Current - UL 15A Voltage - UL 300V Wire Gauge or Range - AWG Wire Gauge or Range - mm² Features - Color Gray	Number of Positions	5
Termination Style Current - IEC 17.5A Voltage - IEC 250V Current - UL 15A Voltage - UL 300V Wire Gauge or Range - AWG Wire Gauge or Range - mm² Features - Color Gray	Number of Levels	2
Current - IEC 17.5A Voltage - IEC 250V Current - UL 15A Voltage - UL 300V Wire Gauge or Range - AWG 14-26 AWG Wire Gauge or Range - mm² 0.14-2.5mm² Features - Color Gray	Terminal - Width	5.2mm
Voltage - IEC Current - UL 15A Voltage - UL 300V Wire Gauge or Range - AWG Wire Gauge or Range - mm² Features - Color Gray	Termination Style	Push In, Spring
Current - UL 15A Voltage - UL 300V Wire Gauge or Range - AWG 14-26 AWG Wire Gauge or Range - mm² 0.14-2.5mm² Features - Gray	Current - IEC	17.5A
Voltage - UL300VWire Gauge or Range - AWG14-26 AWGWire Gauge or Range - mm²0.14-2.5mm²Features-ColorGray	Voltage - IEC	250V
Wire Gauge or Range - AWG Wire Gauge or Range - mm² O.14-2.5mm² Features Color Gray	Current - UL	15A
Wire Gauge or Range - mm ² Features Color Gray	Voltage - UL	300V
Features - Color Gray	Wire Gauge or Range - AWG	14-26 AWG
Color Gray	Wire Gauge or Range - mm ²	0.14-2.5mm ²
	Features	-
Report errors?	Color	Gray
		Report errors?

3006506 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

3006506 Payment Methods





















3006506 Shipping Methods













If you have any question about 3006506, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com