



301A10089X-1S Information

Heisener.com

301A10089X-1S Part Number

Manufacturer Conec

Category Connectors, Interconnects

D-Sub Connectors

Description CONN D-SUB PLUG 9POS PNL MNT IDC

Package

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









301A10089X-1S Specifications

Manufacturer Part Number 301A10089X-1S Manufacturer Conee Category Connectors, Interconnects D-Sub Connectors Package - Series - Connector Style D-Sub Connector Type Plug, Male Pins Number of Positions 9 Number of Rows 2 Shell Size, Connector Layout 1 (DE, E) Contact Type Signal Mounting Type Panel Mount Flange Feature Housing/Shell (Unthreaded) Termination IDC, Ribbon Cable Features Grounding Indents, Strain Relief Shell Material, Finish Steel, Tin Plated Contact Finish Thickness 8µin (0.20µm) Ingress Protection - Material Flammability Rating UL94 V-0	•	
CategoryConnectors, InterconnectsPackage-Series-Connector StyleD-SubConnector TypePlug, Male PinsNumber of Positions9Number of Rows2Shell Size, Connector Layout1 (DE, E)Contact TypeSignalMounting TypePanel MountFlange FeatureHousing/Shell (Unthreaded)TerminationIDC, Ribbon CableFeaturesGrounding Indents, Strain ReliefShell Material, FinishSteel, Tin PlatedContact FinishGoldContact Finish Thickness8µin (0.20µm)Ingress Protection-Material Flammability RatingUL94 V-0	Manufacturer Part Number	301A10089X-1S
Package-Series-Connector StyleD-SubConnector TypePlug, Male PinsNumber of Positions9Number of Rows2Shell Size, Connector Layout1 (DE, E)Contact TypeSignalMounting TypePanel MountFlange FeatureHousing/Shell (Unthreaded)TerminationIDC, Ribbon CableFeaturesGrounding Indents, Strain ReliefShell Material, FinishSteel, Tin PlatedContact Finish ThicknessSµin (0.20μm)Ingress Protection-Material Flammability RatingUL94 V-0	Manufacturer	Conec
Package-Series-Connector StyleD-SubConnector TypePlug, Male PinsNumber of Positions9Number of Rows2Shell Size, Connector Layout1 (DE, E)Contact TypeSignalMounting TypePanel MountFlange FeatureHousing/Shell (Unthreaded)TerminationIDC, Ribbon CableFeaturesGrounding Indents, Strain ReliefShell Material, FinishSteel, Tin PlatedContact Finish Thickness8μin (0.20μm)Ingress Protection-Material Flammability RatingUL94 V-0	Category	Connectors, Interconnects
Series-Connector StyleD-SubConnector TypePlug, Male PinsNumber of Positions9Number of Rows2Shell Size, Connector Layout1 (DE, E)Contact TypeSignalMounting TypePanel MountFlange FeatureHousing/Shell (Unthreaded)TerminationIDC, Ribbon CableFeaturesGrounding Indents, Strain ReliefShell Material, FinishSteel, Tin PlatedContact Finish ThicknessSµin (0.20μm)Ingress Protection-Material Flammability RatingUL94 V-0		D-Sub Connectors
Connector StyleD-SubConnector TypePlug, Male PinsNumber of Positions9Number of Rows2Shell Size, Connector Layout1 (DE, E)Contact TypeSignalMounting TypePanel MountFlange FeatureHousing/Shell (Unthreaded)TerminationIDC, Ribbon CableFeaturesGrounding Indents, Strain ReliefShell Material, FinishSteel, Tin PlatedContact Finish Thickness8μin (0.20μm)Ingress Protection-Material Flammability RatingUL94 V-0	Package	-
Connector TypePlug, Male PinsNumber of Positions9Number of Rows2Shell Size, Connector Layout1 (DE, E)Contact TypeSignalMounting TypePanel MountFlange FeatureHousing/Shell (Unthreaded)TerminationIDC, Ribbon CableFeaturesGrounding Indents, Strain ReliefShell Material, FinishSteel, Tin PlatedContact Finish Thickness8μin (0.20μm)Ingress Protection-Material Flammability RatingUL94 V-0	Series	-
Number of Positions9Number of Rows2Shell Size, Connector Layout1 (DE, E)Contact TypeSignalMounting TypePanel MountFlange FeatureHousing/Shell (Unthreaded)TerminationIDC, Ribbon CableFeaturesGrounding Indents, Strain ReliefShell Material, FinishSteel, Tin PlatedContact Finish Thickness8μin (0.20μm)Ingress Protection-Material Flammability RatingUL94 V-0	Connector Style	D-Sub
Number of Rows2Shell Size, Connector Layout1 (DE, E)Contact TypeSignalMounting TypePanel MountFlange FeatureHousing/Shell (Unthreaded)TerminationIDC, Ribbon CableFeaturesGrounding Indents, Strain ReliefShell Material, FinishSteel, Tin PlatedContact Finish Thickness8μin (0.20μm)Ingress Protection-Material Flammability RatingUL94 V-0	Connector Type	Plug, Male Pins
Shell Size, Connector Layout1 (DE, E)Contact TypeSignalMounting TypePanel MountFlange FeatureHousing/Shell (Unthreaded)TerminationIDC, Ribbon CableFeaturesGrounding Indents, Strain ReliefShell Material, FinishSteel, Tin PlatedContact FinishGoldContact Finish Thickness8μin (0.20μm)Ingress Protection-Material Flammability RatingUL94 V-0	Number of Positions	9
Contact TypeSignalMounting TypePanel MountFlange FeatureHousing/Shell (Unthreaded)TerminationIDC, Ribbon CableFeaturesGrounding Indents, Strain ReliefShell Material, FinishSteel, Tin PlatedContact FinishGoldContact Finish Thickness8μin (0.20μm)Ingress Protection-Material Flammability RatingUL94 V-0	Number of Rows	2
Mounting TypePanel MountFlange FeatureHousing/Shell (Unthreaded)TerminationIDC, Ribbon CableFeaturesGrounding Indents, Strain ReliefShell Material, FinishSteel, Tin PlatedContact FinishGoldContact Finish Thickness8μin (0.20μm)Ingress Protection-Material Flammability RatingUL94 V-0	Shell Size, Connector Layout	1 (DE, E)
Flange Feature Housing/Shell (Unthreaded) Termination IDC, Ribbon Cable Features Grounding Indents, Strain Relief Shell Material, Finish Steel, Tin Plated Contact Finish Gold Contact Finish Thickness 8µin (0.20µm) Ingress Protection - Material Flammability Rating UL94 V-0	Contact Type	Signal
Termination IDC, Ribbon Cable Features Grounding Indents, Strain Relief Shell Material, Finish Steel, Tin Plated Contact Finish Gold Contact Finish Thickness 8μin (0.20μm) Ingress Protection - Material Flammability Rating UL94 V-0	Mounting Type	Panel Mount
Features Grounding Indents, Strain Relief Shell Material, Finish Steel, Tin Plated Contact Finish Gold Contact Finish Thickness 8µin (0.20µm) Ingress Protection - Material Flammability Rating UL94 V-0	Flange Feature	Housing/Shell (Unthreaded)
Shell Material, FinishSteel, Tin PlatedContact FinishGoldContact Finish Thickness8μin (0.20μm)Ingress Protection-Material Flammability RatingUL94 V-0	Termination	IDC, Ribbon Cable
Contact FinishGoldContact Finish Thickness8μin (0.20μm)Ingress Protection-Material Flammability RatingUL94 V-0	Features	Grounding Indents, Strain Relief
Contact Finish Thickness 8μin (0.20μm) Ingress Protection - Material Flammability Rating UL94 V-0	Shell Material, Finish	Steel, Tin Plated
Ingress Protection Material Flammability Rating UL94 V-0	Contact Finish	Gold
Material Flammability Rating UL94 V-0	Contact Finish Thickness	8μin (0.20μm)
	Ingress Protection	-
Report errors?	Material Flammability Rating	UL94 V-0
		Report errors?

301A10089X-1S Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

301A10089X-1S Payment Methods


































If you have any question about 301A10089X-1S, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com