

3031555 Information



For Reference Only

Part Number 3031555

Manufacturer Phoenix Contact

Category Connectors, Interconnects

Terminal Blocks - Din Rail, Channel

Description CONN TERM BLK FEED THRU 12-28AWG

Package

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









3031555 Specifications

Manufacturer Part Number 3031555 Manufacturer Phoenix Contact Category Connectors, Interconnects Terminal Blocks - Din Rail, Channel Package - Series CLIPLINE STTB Type Feed Through Disconnect Type - Number of Positions 4 Number of Levels 2; Connected Terminal - Width 5.2mm Termination Style Push In, Spring Current - IEC 22A Voltage - IEC 500V Current - UL 20A Voltage - UL 600V Wire Gauge or Range - AWG 12-28 AWG Wire Gauge or Range - mm² 0.08-4mm² Features Diode Color Gray		
Category Connectors, Interconnects Terminal Blocks - Din Rail, Channel Package - Series CLIPLINE STTB Type Feed Through Disconnect Type - Number of Positions 4 Number of Levels 2; Connected Terminal - Width 5.2mm Termination Style Push In, Spring Current - IEC 22A Voltage - IEC 500V Current - UL 20A Voltage - UL Wire Gauge or Range - AWG Wire Gauge or Range - AWG Wire Gauge or Range - mm² Features Diode Color	Manufacturer Part Number	3031555
Package - CLIPLINE STTB Type Feed Through Disconnect Type - Number of Positions 4 Number of Levels 2; Connected Terminal - Width 5.2mm Termination Style Push In, Spring Current - IEC 22A Voltage - IEC 500V Current - UL 20A Voltage - UL Wire Gauge or Range - AWG Wire Gauge or Range - AWG Color Gray	Manufacturer	Phoenix Contact
Package - Series CLIPLINE STTB Type Feed Through Disconnect Type - Number of Positions 4 Number of Levels 2; Connected Terminal - Width 5.2mm Termination Style Push In, Spring Current - IEC 22A Voltage - IEC 500V Current - UL 20A Voltage - UL 600V Wire Gauge or Range - AWG 12-28 AWG Wire Gauge or Range - mm² 0.08-4mm² Features Diode Color Gray	Category	Connectors, Interconnects
Series CLIPLINE STTB Type Feed Through Disconnect Type - Number of Positions 4 Number of Levels 2; Connected Terminal - Width 5.2mm Termination Style Push In, Spring Current - IEC 22A Voltage - IEC 500V Current - UL 20A Voltage - UL 600V Wire Gauge or Range - AWG 12-28 AWG Wire Gauge or Range - mm² 0.08-4mm² Features Diode Color Gray		Terminal Blocks - Din Rail, Channel
Type Feed Through Disconnect Type - Number of Positions 4 Number of Levels 2; Connected Terminal - Width 5.2mm Termination Style Push In, Spring Current - IEC 22A Voltage - IEC 500V Current - UL 20A Voltage - UL 600V Wire Gauge or Range - AWG 12-28 AWG Wire Gauge or Range - mm² 0.08-4mm² Features Diode Color Gray	Package	-
Disconnect Type Number of Positions 4 Number of Levels 1: Connected Terminal - Width 5: 2mm Termination Style Push In, Spring Current - IEC 22A Voltage - IEC 500V Current - UL 20A Voltage - UL 600V Wire Gauge or Range - AWG Wire Gauge or Range - mm² Features Diode Color Gray	Series	CLIPLINE STTB
Number of Positions Number of Levels 2; Connected Terminal - Width 5.2mm Termination Style Push In, Spring Current - IEC 22A Voltage - IEC 500V Current - UL 20A Voltage - UL Wire Gauge or Range - AWG Wire Gauge or Range - mm² Features Diode Color Gray	Туре	Feed Through
Number of Levels Terminal - Width 5.2mm Termination Style Push In, Spring Current - IEC 22A Voltage - IEC 500V Current - UL 20A Voltage - UL Wire Gauge or Range - AWG Wire Gauge or Range - mm² Features Diode Color Gray	Disconnect Type	-
Terminal - Width Termination Style Push In, Spring Current - IEC 22A Voltage - IEC 500V Current - UL 20A Voltage - UL 600V Wire Gauge or Range - AWG Wire Gauge or Range - mm² Features Diode Color Gray	Number of Positions	4
Termination Style Current - IEC 22A Voltage - IEC 500V Current - UL 20A Voltage - UL 600V Wire Gauge or Range - AWG Wire Gauge or Range - mm² Features Diode Color Push In, Spring Push In, Spring Push In, Spring 12-2A 20A 500V 000V 600V 600V	Number of Levels	2; Connected
Current - IEC 22A Voltage - IEC 500V Current - UL 20A Voltage - UL 600V Wire Gauge or Range - AWG 12-28 AWG Wire Gauge or Range - mm² 0.08-4mm² Features Diode Color Gray	Terminal - Width	5.2mm
Voltage - IEC Current - UL 20A Voltage - UL 600V Wire Gauge or Range - AWG Wire Gauge or Range - mm² 0.08-4mm² Features Diode Color Gray	Termination Style	Push In, Spring
Current - UL 20A Voltage - UL 600V Wire Gauge or Range - AWG 12-28 AWG Wire Gauge or Range - mm² 0.08-4mm² Features Diode Color Gray	Current - IEC	22A
Voltage - UL600VWire Gauge or Range - AWG12-28 AWGWire Gauge or Range - mm²0.08-4mm²FeaturesDiodeColorGray	Voltage - IEC	500V
Wire Gauge or Range - AWG Wire Gauge or Range - mm² O.08-4mm² Features Diode Color Gray	Current - UL	20A
Wire Gauge or Range - mm ² Features Color 0.08-4mm ² Diode Gray	Voltage - UL	600V
Features Diode Color Gray	Wire Gauge or Range - AWG	12-28 AWG
Color Gray	Wire Gauge or Range - mm ²	0.08-4mm ²
·	Features	Diode
Report errors?	Color	Gray
		Report errors?

3031555 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

3031555 Payment Methods



















3031555 Shipping Methods













If you have any question about 3031555, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com