

3031652

3031652 Information

Heisener.com	Part Number Manufacturer Category Description Package	3031652 Phoenix Contact Connectors, Interconnects Terminal Blocks - Din Rail, Channel CONN TERM BLK FEED THRU 12-28AWG - For the pricing/inventory/lead time, please contact	
For Reference Only		us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



3031652 Specifications

Manufacturer Part Number 3031652 Manufacturer Phoenix Contact Category Connectors, Interconnects Terminal Blocks - Din Rail, Channel Package - Series CLIPLINE STTB Type Feed Through Disconnect Type - Number of Positions 4 Number of Levels 2 Terminal - Width 5.2mm Current - IEC 2AA Voltage - IEC 2SOV Current - UL 20A Voltage - UL 300V Wire Gauge or Range - AWG 12-28 AWG Wire Gauge or Range - mm² Diode Color Gray		
CategoryConnectors, InterconnectsTerminal Blocks - Din Rail, ChannelPackage-SeriesCLIPLINE STTBTypeFeed ThroughDisconnect Type-Number of Positions4Number of Levels2Terminal - Width5.2mmTermination StylePush In, SpringCurrent - IEC22AVoltage - IEC20NVoltage - UL300VWire Gauge or Range - AWG0.8-4mm²Wire Gauge or Range - AWG0.8-4mm²FeaturesDiodeColorGray	Manufacturer Part Number	3031652
Terminal Blocks - Din Rail, ChannelPackage-SeriesCLIPLINE STTBTypeFeed ThroughDisconnect Type-Number of Positions4Number of Levels2Terminal - Width5.2mmTermination StylePush In, SpringCurrent - IEC22AVoltage - IEC20NVoltage - UL300VWire Gauge or Range - AWG0.8-Amm²Wire Gauge or Range - mm²0.08-Amm²FeaturesDiodeColorGray	Manufacturer	Phoenix Contact
Package-SeriesCLIPLINE STTBTypeFeed ThroughDisconnect Type-Number of Positions4Number of Levels2Terminal - WidthS.2mmTermination StylePush In, SpringCurrent - IEC22AVoltage - IECSoVVoltage or Range - AWG30VWire Gauge or Range - AWG12-28 AWGWire Gauge or Range - AWGDiodeFeaturesDiodeFolorSingeColorGange - Marcel Section	Category	Connectors, Interconnects
SeriesCLIPLINE STTBTypeFeed ThroughDisconnect Type-Number of Positions4Number of Levels2Terminal - Width5.2mmTermination StylePush In, SpringCurrent - IEC22AVoltage - IEC50VCurrent - UL300VWire Gauge or Range - AWG12-28 AWGWire Gauge or Range - AWG0.84-4mm²FeaturesDiodeColorGray		Terminal Blocks - Din Rail, Channel
TypeFeed ThroughTypeFeed ThroughDisconnect Type-Number of Positions4Number of Levels2Terminal - Width5.2mmTermination StylePush In, SpringCurrent - IEC22AVoltage - IEC20NCurrent - UL00AVoltage - UL300VWire Gauge or Range - AWG12-28 AWGWire Gauge or Range - amma0.08-4mm²FeaturesDiodeColorGray	Package	-
Disconnect Type-Number of Positions4Number of Levels2Terminal - Width5.2mmTermination StylePush In, SpringCurrent - IEC22AVoltage - IEC20NCurrent - UL00AVoltage - UL300VWire Gauge or Range - AWG12-28 AWGWire Gauge or Range - mm²0.08-4mm²FeaturesDiodeColorGray	Series	CLIPLINE STTB
Number of Positions4Number of Levels2Terminal - Width5.2mmTermination StylePush In, SpringCurrent - IEC22AVoltage - IEC20NCurrent - UL00AVoltage - UL300VWire Gauge or Range - AWG0.84-Ama²FeaturesDiodeColorGray	Туре	Feed Through
Number of Levels2Terminal - Width5.2mmTermination StylePush In, SpringCurrent - IEC22AVoltage - IEC250VCurrent - UL20AVoltage - UL300VWire Gauge or Range - AWG12-28 AWGWire Gauge or Range - mm²0.08-4mm²FeaturesDiodeColorGray	Disconnect Type	-
Terminal - Width5.2mmTermination StylePush In, SpringCurrent - IEC22AVoltage - IEC250VCurrent - UL20AVoltage - UL300VWire Gauge or Range - AWG12-28 AWGWire Gauge or Range - mm²0.08-4mm²FeaturesDiodeColorGray	Number of Positions	4
Termination StylePush In, SpringCurrent - IEC22AVoltage - IEC250VCurrent - UL20AVoltage - UL300VWire Gauge or Range - AWG12-28 AWGWire Gauge or Range - mm²0.08-4mm²FeaturesDiodeColorGray	Number of Levels	2
Current - IEC22AVoltage - IEC250VCurrent - UL20AVoltage - UL300VWire Gauge or Range - AWG12-28 AWGWire Gauge or Range - mm²0.08-4mm²FeaturesDiodeColorGray	Terminal - Width	5.2mm
Voltage - IEC250VCurrent - UL20AVoltage - UL300VWire Gauge or Range - AWG12-28 AWGWire Gauge or Range - mm²0.08-4mm²FeaturesDiodeColorGray	Termination Style	Push In, Spring
Current - UL20AVoltage - UL300VWire Gauge or Range - AWG12-28 AWGWire Gauge or Range - mm²0.08-4mm²FeaturesDiodeColorGray	Current - IEC	22A
Voltage - UL300VWire Gauge or Range - AWG12-28 AWGWire Gauge or Range - mm²0.08-4mm²FeaturesDiodeColorGray	Voltage - IEC	250V
Wire Gauge or Range - AWG12-28 AWGWire Gauge or Range - mm²0.08-4mm²FeaturesDiodeColorGray	Current - UL	20A
Wire Gauge or Range - mm²0.08-4mm²FeaturesDiodeColorGray	Voltage - UL	300V
Features Diode Color Gray	Wire Gauge or Range - AWG	12-28 AWG
Color Gray	Wire Gauge or Range - mm ²	0.08-4mm ²
	Features	Diode
Report errors?	Color	Gray
		Report errors?

3031652 Guarantees



If you have any question about 3031652, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com