

3031856 Information

Heisener.com

Part Number 3031856

Manufacturer Phoenix Contact

Category Connectors, Interconnects

Terminal Blocks - Din Rail, Channel

Description CONN TERM BLK FEED THRU 12-28AWG

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









3031856 Specifications

Manufacturer Part Number 3031856 Manufacturer Phoenix Contact Category Connectors, Interconnects Terminal Blocks - Din Rail, Channel Package Series CLIPLINE STI Type Feed Through Disconnect Type - Number of Positions 4 Number of Levels 2 Terminal - Width 5.2mm Termination Style Push In, Spring Current - IEC 24A Voltage - IEC 400V Current - UL 20A Voltage - UL 300V Wire Gauge or Range - AWG 12-28 AWG Wire Gauge or Range - mm² 0.08-4mm² Features - Color Gray		
Category Connectors, Interconnects Terminal Blocks - Din Rail, Channel Package - Series CLIPLINE STI Type Feed Through Disconnect Type - Number of Positions 4 Number of Levels 2 Terminal - Width 5.2mm Termination Style Push In, Spring Current - IEC 24A Voltage - IEC 400V Current - UL 20A Voltage - UL 300V Wire Gauge or Range - AWG Wire Gauge or Range - mm² Features - Color Gray	Manufacturer Part Number	3031856
Package - CLIPLINE STI Type Feed Through Disconnect Type - Number of Positions 4 Number of Levels 2 Terminal - Width 5.2mm Termination Style Push In, Spring Current - IEC 24A Voltage - IEC 400V Current - UL 20A Voltage - UL Wire Gauge or Range - AWG Wire Gauge or Range - mm² 0.08-4mm² Features Color Gray	Manufacturer	Phoenix Contact
Package - Series CLIPLINE STI Type Feed Through Disconnect Type - Number of Positions 4 Number of Levels 2 Terminal - Width 5.2mm Termination Style Push In, Spring Current - IEC 24A Voltage - IEC 400V Current - UL 20A Voltage - UL 300V Wire Gauge or Range - AWG 12-28 AWG Wire Gauge or Range - mm² 0.08-4mm² Features - Color Gray	Category	Connectors, Interconnects
Series CLIPLINE STI Type Feed Through Disconnect Type - Number of Positions 4 Number of Levels 2 Terminal - Width 5.2mm Termination Style Push In, Spring Current - IEC 24A Voltage - IEC 400V Current - UL 20A Voltage - UL 300V Wire Gauge or Range - AWG 12-28 AWG Wire Gauge or Range - mm² 0.08-4mm² Features - Color Gray		Terminal Blocks - Din Rail, Channel
Type Feed Through Disconnect Type - Number of Positions 4 Number of Levels 2 Terminal - Width 5.2mm Termination Style Push In, Spring Current - IEC 24A Voltage - IEC 400V Current - UL 20A Voltage - UL 300V Wire Gauge or Range - AWG 12-28 AWG Wire Gauge or Range - mm² 0.08-4mm² Features - Color Gray	Package	-
Disconnect Type Number of Positions 4 Number of Levels 2 Terminal - Width 5.2mm Termination Style Push In, Spring Current - IEC 24A Voltage - IEC 400V Current - UL 20A Voltage - UL 300V Wire Gauge or Range - AWG Wire Gauge or Range - mm² Features Color Gray	Series	CLIPLINE STI
Number of Positions Number of Levels 2 Terminal - Width 5.2mm Termination Style Push In, Spring Current - IEC 24A Voltage - IEC 400V Current - UL 20A Voltage - UL Wire Gauge or Range - AWG Wire Gauge or Range - mm² 0.08-4mm² Features Color Gray	Туре	Feed Through
Number of Levels 2 Terminal - Width 5.2mm Termination Style Push In, Spring Current - IEC 24A Voltage - IEC 400V Current - UL 20A Voltage - UL 300V Wire Gauge or Range - AWG 12-28 AWG Wire Gauge or Range - mm² 0.08-4mm² Features - Color Gray	Disconnect Type	-
Terminal - Width Termination Style Push In, Spring Current - IEC 24A Voltage - IEC 400V Current - UL 20A Voltage - UL 300V Wire Gauge or Range - AWG Wire Gauge or Range - mm² Features Color Gray	Number of Positions	4
Termination Style Current - IEC 24A Voltage - IEC 400V Current - UL 20A Voltage - UL 300V Wire Gauge or Range - AWG Wire Gauge or Range - mm² Features Color Gray	Number of Levels	2
Current - IEC 24A Voltage - IEC 400V Current - UL 20A Voltage - UL 300V Wire Gauge or Range - AWG 12-28 AWG Wire Gauge or Range - mm² 0.08-4mm² Features - Color Gray	Terminal - Width	5.2mm
Voltage - IEC400VCurrent - UL20AVoltage - UL300VWire Gauge or Range - AWG12-28 AWGWire Gauge or Range - mm²0.08-4mm²Features-ColorGray	Termination Style	Push In, Spring
Current - UL 20A Voltage - UL 300V Wire Gauge or Range - AWG 12-28 AWG Wire Gauge or Range - mm² 0.08-4mm² Features - Color Gray	Current - IEC	24A
Voltage - UL300VWire Gauge or Range - AWG12-28 AWGWire Gauge or Range - mm²0.08-4mm²Features-ColorGray	Voltage - IEC	400V
Wire Gauge or Range - AWG Wire Gauge or Range - mm² O.08-4mm² Features Color Gray	Current - UL	20A
Wire Gauge or Range - mm² Features Color Gray	Voltage - UL	300V
Features - Color Gray	Wire Gauge or Range - AWG	12-28 AWG
Color Gray	Wire Gauge or Range - mm ²	0.08-4mm ²
-	Features	-
D0	Color	Gray
Report errors?		Report errors?

3031856 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

3031856 Payment Methods

































If you have any question about 3031856, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com