

# **3034141 Information**

Heisener.com

Part Number 3034141

Manufacturer Phoenix Contact

Category Connectors, Interconnects

Terminal Blocks - Din Rail, Channel

**Description** CONN TERM BLK FEED THRU 12-24AWG

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com

Request a Quote



Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









2024141	Charifications
<b>3U34141</b>	<b>Specifications</b>

Manufacturer Part Number  Manufacturer  Category  Connectors, Interconnects  Terminal Blocks - Din Rail, Channel  Package  Series  CLIPLINE DT  Type  Feed Through  Disconnect Type  Number of Positions  2  Number of Levels  I  Terminal - Width  5.2mm  Termination Style  Current - IEC  24A  Voltage - IEC  Surder  Wire Gauge or Range - AWG  Wire Gauge or Range - AWG  Wire Gauge or Range - mm²  Features  Color  Report errors?		
Category         Connectors, Interconnects           Terminal Blocks - Din Rail, Channel           Package         -           Series         CLIPLINE DT           Type         Feed Through           Disconnect Type         -           Number of Positions         2           Number of Levels         1           Terminal - Width         5.2mm           Termination Style         Push In, Spring           Current - IEC         24A           Voltage - IEC         800V           Current - UL         1A           Voltage - UL         600V           Wire Gauge or Range - AWG         12-24 AWG           Wire Gauge or Range - mm²         0.2-4mm²           Features         Diode           Color         Gray	Manufacturer Part Number	3034141
Terminal Blocks - Din Rail, Channel  Package  Series  CLIPLINE DT  Type  Feed Through  Disconnect Type  - Number of Positions  2  Number of Levels  1  Terminal - Width  5.2mm  Termination Style  Current - IEC  24A  Voltage - IEC  800V  Current - UL  Voltage - UL  Wire Gauge or Range - AWG  Wire Gauge or Range - mm²  Features  Diode  Color  Gray	Manufacturer	Phoenix Contact
Package         -           Series         CLIPLINE DT           Type         Feed Through           Disconnect Type         -           Number of Positions         2           Number of Levels         1           Terminal - Width         5.2mm           Termination Style         Push In, Spring           Current - IEC         24A           Voltage - IEC         800V           Current - UL         1A           Voltage - UL         600V           Wire Gauge or Range - AWG         12-24 AWG           Wire Gauge or Range - mm²         0.2-4mm²           Features         Diode           Color         Gray	Category	Connectors, Interconnects
Series         CLIPLINE DT           Type         Feed Through           Disconnect Type         -           Number of Positions         2           Number of Levels         1           Terminal - Width         5.2mm           Termination Style         Push In, Spring           Current - IEC         24A           Voltage - IEC         800V           Current - UL         1A           Voltage - UL         600V           Wire Gauge or Range - AWG         12-24 AWG           Wire Gauge or Range - mm²         0.2-4mm²           Features         Diode           Color         Gray		Terminal Blocks - Din Rail, Channel
Type Feed Through Disconnect Type - Number of Positions 2 Number of Levels 1 Terminal - Width 5.2mm Termination Style Push In, Spring Current - IEC 24A Voltage - IEC 800V Current - UL 1A Voltage - UL 600V Wire Gauge or Range - AWG 12-24 AWG Wire Gauge or Range - mm² 0.2-4mm² Features Diode Color Gray	Package	-
Disconnect Type         -           Number of Positions         2           Number of Levels         1           Terminal - Width         5.2mm           Termination Style         Push In, Spring           Current - IEC         24A           Voltage - IEC         800V           Current - UL         1A           Voltage - UL         600V           Wire Gauge or Range - AWG         12-24 AWG           Wire Gauge or Range - mm²         0.2-4mm²           Features         Diode           Color         Gray	Series	CLIPLINE DT
Number of Positions         2           Number of Levels         1           Terminal - Width         5.2mm           Termination Style         Push In, Spring           Current - IEC         24A           Voltage - IEC         800V           Current - UL         1A           Voltage - UL         600V           Wire Gauge or Range - AWG         12-24 AWG           Wire Gauge or Range - mm²         0.2-4mm²           Features         Diode           Color         Gray	Туре	Feed Through
Number of Levels       1         Terminal - Width       5.2mm         Termination Style       Push In, Spring         Current - IEC       24A         Voltage - IEC       800V         Current - UL       1A         Voltage - UL       600V         Wire Gauge or Range - AWG       12-24 AWG         Wire Gauge or Range - mm²       0.2-4mm²         Features       Diode         Color       Gray	Disconnect Type	-
Terminal - Width  Termination Style Push In, Spring  Current - IEC 24A  Voltage - IEC 800V  Current - UL 1A  Voltage - UL 600V  Wire Gauge or Range - AWG Wire Gauge or Range - mm² Features Diode Color Gray	Number of Positions	2
Termination Style  Current - IEC  24A  Voltage - IEC  800V  Current - UL  1A  Voltage - UL  600V  Wire Gauge or Range - AWG  Wire Gauge or Range - mm²  Features  Diode  Color  Gray	Number of Levels	1
Current - IEC       24A         Voltage - IEC       800V         Current - UL       1A         Voltage - UL       600V         Wire Gauge or Range - AWG       12-24 AWG         Wire Gauge or Range - mm²       0.2-4mm²         Features       Diode         Color       Gray	Terminal - Width	5.2mm
Voltage - IEC 800V  Current - UL 1A  Voltage - UL 600V  Wire Gauge or Range - AWG 12-24 AWG  Wire Gauge or Range - mm² 0.2-4mm²  Features Diode  Color Gray	Termination Style	Push In, Spring
Current - UL 1A  Voltage - UL 600V  Wire Gauge or Range - AWG 12-24 AWG  Wire Gauge or Range - mm² 0.2-4mm²  Features Diode  Color Gray	Current - IEC	24A
Voltage - UL  Wire Gauge or Range - AWG  12-24 AWG  Wire Gauge or Range - mm²  0.2-4mm²  Features  Diode  Color  Gray	Voltage - IEC	800V
Wire Gauge or Range - AWG  Wire Gauge or Range - mm²  O.2-4mm²  Features  Diode  Color  Gray	Current - UL	1A
Wire Gauge or Range - mm²  Features  Color  O.2-4mm²  Diode  Gray	Voltage - UL	600V
Features Diode Color Gray	Wire Gauge or Range - AWG	12-24 AWG
Color Gray	Wire Gauge or Range - mm <sup>2</sup>	0.2-4mm <sup>2</sup>
	Features	Diode
Report errors?	Color	Gray
		Report errors?

## 3034141 Guarantees



### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

# 3034141 Payment Methods





















# 3034141 Shipping Methods













If you have any question about 3034141, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com