

3035043 Information

Heisener.com

Part Number 3035043

Manufacturer Phoenix Contact

Category Connectors, Interconnects

Terminal Blocks - Din Rail, Channel

Description CONN TERM BLK DISCONN 12-28AWG

Package -


For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com

Request a Quote



Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









2025042	Specifications
3033043	Specifications

Manufacturer Phoenix Contact Category Connectors, Interconnects Terminal Blocks - Din Rail, Channel Package - Series CLIPLINE ST Type Disconnect Disconnect Type Switch, Knife Number of Positions 4 Number of Levels 1 Terminal - Width 5.2mm Termination Style Push In, Spring Current - IEC 20A Voltage - IEC 400V Current - UL 16A Voltage - UL 600V Wire Gauge or Range - AWG 12-28 AWG Wire Gauge or Range - mm² 0.08-4mm² Features - Color Red		
Category Connectors, Interconnects Terminal Blocks - Din Rail, Channel Package - Series CLIPLINE ST Type Disconnect Disconnect Type Switch, Knife Number of Positions 4 Number of Levels 1 Terminal - Width 5.2mm Termination Style Push In, Spring Current - IEC 20A Voltage - IEC 400V Current - UL 16A Voltage - UL 600V Wire Gauge or Range - AWG 12-28 AWG Wire Gauge or Range - mm² 0.08-4mm² Features - Color Red	Manufacturer Part Number	3035043
Terminal Blocks - Din Rail, Channel Package Series CLIPLINE ST Type Disconnect Disconnect Type Switch, Knife Number of Positions 4 Number of Levels 1 Terminal - Width 5.2mm Termination Style Push In, Spring Current - IEC 20A Voltage - IEC 400V Current - UL 16A Voltage - UL Wire Gauge or Range - AWG Wire Gauge or Range - mm² Peatures - Color Red	Manufacturer	Phoenix Contact
Package - Series CLIPLINE ST Type Disconnect Disconnect Type Switch, Knife Number of Positions 4 Number of Levels 1 Terminal - Width 5.2mm Termination Style Push In, Spring Current - IEC 20A Voltage - IEC 400V Current - UL 16A Voltage - UL 600V Wire Gauge or Range - AWG 12-28 AWG Wire Gauge or Range - mm² 0.08-4mm² Features - Color Red	Category	Connectors, Interconnects
Series CLIPLINE ST Type Disconnect Disconnect Type Switch, Knife Number of Positions 4 Number of Levels 1 Terminal - Width 5.2mm Termination Style Push In, Spring Current - IEC 20A Voltage - IEC 400V Current - UL 16A Voltage - UL 600V Wire Gauge or Range - AWG 12-28 AWG Wire Gauge or Range - mm² 0.08-4mm² Features - Color Red		Terminal Blocks - Din Rail, Channel
Type Disconnect Disconnect Type Switch, Knife Number of Positions 4 Number of Levels 1 Terminal - Width 5.2mm Termination Style Push In, Spring Current - IEC 20A Voltage - IEC 400V Current - UL 16A Voltage - UL 600V Wire Gauge or Range - AWG 12-28 AWG Wire Gauge or Range - mm² 0.08-4mm² Features - Color Red	Package	-
Disconnect Type Switch, Knife Number of Positions 4 Number of Levels 1 Terminal - Width 5.2mm Termination Style Push In, Spring Current - IEC 20A Voltage - IEC 400V Current - UL 16A Voltage - UL 600V Wire Gauge or Range - AWG 12-28 AWG Wire Gauge or Range - mm² 0.08-4mm² Features - Color Red	Series	CLIPLINE ST
Number of Positions Number of Levels 1 Terminal - Width 5.2mm Termination Style Push In, Spring Current - IEC 20A Voltage - IEC 400V Current - UL 16A Voltage - UL Wire Gauge or Range - AWG Wire Gauge or Range - mm² Features Color Red	Туре	Disconnect
Number of Levels 1 Terminal - Width 5.2mm Termination Style Push In, Spring Current - IEC 20A Voltage - IEC 400V Current - UL 16A Voltage - UL 600V Wire Gauge or Range - AWG 12-28 AWG Wire Gauge or Range - mm² 0.08-4mm² Features - Color Red	Disconnect Type	Switch, Knife
Terminal - Width 5.2mm Termination Style Push In, Spring Current - IEC 20A Voltage - IEC 400V Current - UL 16A Voltage - UL 600V Wire Gauge or Range - AWG 12-28 AWG Wire Gauge or Range - mm² 0.08-4mm² Features - Color Red	Number of Positions	4
Termination Style Current - IEC 20A Voltage - IEC 400V Current - UL 16A Voltage - UL 600V Wire Gauge or Range - AWG Wire Gauge or Range - mm² Features Color Push In, Spring 20A 400V 400V 400V 600V 600V 600V Red	Number of Levels	1
Current - IEC 20A Voltage - IEC 400V Current - UL 16A Voltage - UL 600V Wire Gauge or Range - AWG 12-28 AWG Wire Gauge or Range - mm² 0.08-4mm² Features - Color Red	Terminal - Width	5.2mm
Voltage - IEC 400V Current - UL 16A Voltage - UL 600V Wire Gauge or Range - AWG 12-28 AWG Wire Gauge or Range - mm² 0.08-4mm² Features - Color Red	Termination Style	Push In, Spring
Current - UL 16A Voltage - UL 600V Wire Gauge or Range - AWG 12-28 AWG Wire Gauge or Range - mm² 0.08-4mm² Features - Color Red	Current - IEC	20A
Voltage - UL Wire Gauge or Range - AWG Wire Gauge or Range - mm² O.08-4mm² Features Color Red	Voltage - IEC	400V
Wire Gauge or Range - AWG Wire Gauge or Range - mm² Features Color 12-28 AWG 0.08-4mm² - Red	Current - UL	16A
Wire Gauge or Range - mm² Features Color Red	Voltage - UL	600V
Features - Color Red	Wire Gauge or Range - AWG	12-28 AWG
Color Red	Wire Gauge or Range - mm ²	0.08-4mm ²
	Features	-
D	Color	Red
Report errors?		Report errors?

3035043 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

3035043 Payment Methods





















3035043 Shipping Methods













If you have any question about 3035043, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com