

3035697 Information



For Reference Only

Part Number 3035697

Manufacturer Phoenix Contact

Category Connectors, Interconnects

Terminal Blocks - Din Rail, Channel

Description CONN TERM BLK FEED THRU 8-20 AWG

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









3035697 Specifications

Manufacturer Part Number Manufacturer Phoenix Contact Category Connectors, Interconnects Terminal Blocks - Din Rail, Channel Package Series CLIPLINE PTME Type Feed Through Disconnect Type Number of Positions 2 Number of Levels I Terminal - Width 8.2mm Termination Style Push In, Spring Current - IEC 5A Voltage - IEC 1000V Current - UL Voltage - UL Wire Gauge or Range - AWG Wire Gauge or Range - mm² Features Diode Color Report errors?		
Category Connectors, Interconnects Terminal Blocks - Din Rail, Channel Package - Series CLIPLINE PTME Type Feed Through Disconnect Type - Number of Positions 2 Number of Levels 1 Terminal - Width 8.2mm Termination Style Push In, Spring Current - IEC 5A Voltage - IEC 1000V Current - UL 10A Voltage - UL 600V Wire Gauge or Range - AWG 8-20 AWG Wire Gauge or Range - mm² 0.5-10mm² Features Diode Color Gray	Manufacturer Part Number	3035697
Terminal Blocks - Din Rail, Channel Package Series CLIPLINE PTME Type Feed Through Disconnect Type - Number of Positions 2 Number of Levels 1 Terminal - Width 8.2mm Termination Style Push In, Spring Current - IEC 5A Voltage - IEC 1000V Current - UL Voltage - UL Wire Gauge or Range - AWG Wire Gauge or Range - mm² Features Diode Color Gray	Manufacturer	Phoenix Contact
Package - Series CLIPLINE PTME Type Feed Through Disconnect Type - Number of Positions 2 Number of Levels 1 Terminal - Width 8.2mm Termination Style Push In, Spring Current - IEC 5A Voltage - IEC 1000V Current - UL 10A Voltage - UL 600V Wire Gauge or Range - AWG 8-20 AWG Wire Gauge or Range - mm² 0.5-10mm² Features Diode Color Gray	Category	Connectors, Interconnects
Series CLIPLINE PTME Type Feed Through Disconnect Type - Number of Positions 2 Number of Levels 1 Terminal - Width 8.2mm Termination Style Push In, Spring Current - IEC 5A Voltage - IEC 1000V Current - UL 10A Voltage - UL 600V Wire Gauge or Range - AWG 8-20 AWG Wire Gauge or Range - mm² 0.5-10mm² Features Diode Color Gray		Terminal Blocks - Din Rail, Channel
Type Feed Through Disconnect Type - Number of Positions 2 Number of Levels 1 Terminal - Width 8.2mm Termination Style Push In, Spring Current - IEC 5A Voltage - IEC 1000V Current - UL 10A Voltage - UL 600V Wire Gauge or Range - AWG 8-20 AWG Wire Gauge or Range - mm² 0.5-10mm² Features Diode Color Gray	Package	-
Disconnect Type - Number of Positions 2 Number of Levels 1 Terminal - Width 8.2mm Termination Style Push In, Spring Current - IEC 5A Voltage - IEC 1000V Current - UL 10A Voltage - UL 600V Wire Gauge or Range - AWG 8-20 AWG Wire Gauge or Range - mm² 0.5-10mm² Features Diode Color Gray	Series	CLIPLINE PTME
Number of Positions 2 Number of Levels 1 Terminal - Width 8.2mm Termination Style Push In, Spring Current - IEC 5A Voltage - IEC 1000V Current - UL 10A Voltage - UL 600V Wire Gauge or Range - AWG 8-20 AWG Wire Gauge or Range - mm² 0.5-10mm² Features Diode Color Gray	Туре	Feed Through
Number of Levels 1 Terminal - Width 8.2mm Termination Style Push In, Spring Current - IEC 5A Voltage - IEC 1000V Current - UL 10A Voltage - UL 600V Wire Gauge or Range - AWG 8-20 AWG Wire Gauge or Range - mm² 0.5-10mm² Features Diode Color Gray	Disconnect Type	-
Terminal - Width Termination Style Push In, Spring Current - IEC 5A Voltage - IEC 1000V Current - UL 10A Voltage - UL 600V Wire Gauge or Range - AWG Wire Gauge or Range - mm² Features Diode Color 6ray	Number of Positions	2
Termination Style Current - IEC 5A Voltage - IEC 1000V Current - UL 10A Voltage - UL 600V Wire Gauge or Range - AWG Wire Gauge or Range - mm² Features Diode Color Push In, Spring 600V 1000V 1000V 1000 600V 60	Number of Levels	1
Current - IEC 5A Voltage - IEC 1000V Current - UL 10A Voltage - UL 600V Wire Gauge or Range - AWG 8-20 AWG Wire Gauge or Range - mm² 0.5-10mm² Features Diode Color Gray	Terminal - Width	8.2mm
Voltage - IEC Current - UL 10A Voltage - UL 600V Wire Gauge or Range - AWG Wire Gauge or Range - mm² Features Diode Color 1000V 600V	Termination Style	Push In, Spring
Current - UL 10A Voltage - UL 600V Wire Gauge or Range - AWG 8-20 AWG Wire Gauge or Range - mm² 0.5-10mm² Features Diode Color Gray	Current - IEC	5A
Voltage - UL Wire Gauge or Range - AWG Wire Gauge or Range - mm² 0.5-10mm² Features Diode Color Gray	Voltage - IEC	1000V
Wire Gauge or Range - AWG Wire Gauge or Range - mm² 0.5-10mm² Features Diode Color Gray	Current - UL	10A
Wire Gauge or Range - mm² Features Color O.5-10mm² Diode Gray	Voltage - UL	600V
Features Diode Color Gray	Wire Gauge or Range - AWG	8-20 AWG
Color Gray	Wire Gauge or Range - mm ²	0.5-10mm ²
	Features	Diode
Report errors?	Color	Gray
		Report errors?

3035697 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

3035697 Payment Methods





















3035697 Shipping Methods













If you have any question about 3035697, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com