

3036178 Information



For Reference Only

Part Number 3036178

Manufacturer Phoenix Contact

Category Connectors, Interconnects

Terminal Blocks - Din Rail, Channel

Description CONN TERM BLK FEED THRU 2-14 AWG

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









3036178 Specifications

Manufacturer Part Number 3036178 Manufacturer Phoenix Contact Category Connectors, Interconnects Terminal Blocks - Din Rail, Channel Package - Series CLIPLINE ST Type Feed Through Disconnect Type - Number of Positions 2 Number of Levels 1 Terminal - Width 16.0mm Termination Style Push In, Spring Current - IEC 125A Voltage - IEC 1000V Current - UL 115A Voltage - UL 600V Wire Gauge or Range - AWG 2-14 AWG Wire Gauge or Range - mm² 2.5-35mm² Features - Color Gray		
Category Connectors, Interconnects Terminal Blocks - Din Rail, Channel Package - Series CLIPLINE ST Type Feed Through Disconnect Type - Number of Positions 2 Number of Levels 1 Terminal - Width 16.0mm Termination Style Push In, Spring Current - IEC 125A Voltage - IEC 1000V Current - UL 115A Voltage - UL 600V Wire Gauge or Range - AWG 2-14 AWG Wire Gauge or Range - mm² 2.5-35mm² Features - Color Gray	Manufacturer Part Number	3036178
Package - Series CLIPLINE ST Type Feed Through Disconnect Type - Number of Positions 2 Number of Levels 1 Terminal - Width 16.0mm Termination Style Push In, Spring Current - IEC 125A Voltage - IEC 1000V Current - UL 115A Voltage - UL 600V Wire Gauge or Range - AWG 2-14 AWG Wire Gauge or Range - mm² 2.5-35mm² Features - Color Gray	Manufacturer	Phoenix Contact
Package - Series CLIPLINE ST Type Feed Through Disconnect Type - Number of Positions 2 Number of Levels 1 Terminal - Width 16.0mm Termination Style Push In, Spring Current - IEC 125A Voltage - IEC 1000V Current - UL 115A Voltage - UL 600V Wire Gauge or Range - AWG 2-14 AWG Wire Gauge or Range - mm² 2.5-35mm² Features - Color Gray	Category	Connectors, Interconnects
Series CLIPLINE ST Type Feed Through Disconnect Type - Number of Positions 2 Number of Levels 1 Terminal - Width 16.0mm Termination Style Push In, Spring Current - IEC 125A Voltage - IEC 1000V Current - UL 115A Voltage - UL 600V Wire Gauge or Range - AWG 2-14 AWG Wire Gauge or Range - mm² 2.5-35mm² Features - Color Gray		Terminal Blocks - Din Rail, Channel
Type Feed Through Disconnect Type - Number of Positions 2 Number of Levels 1 Terminal - Width 16.0mm Termination Style Push In, Spring Current - IEC 125A Voltage - IEC 1000V Current - UL 115A Voltage - UL 600V Wire Gauge or Range - AWG 2-14 AWG Wire Gauge or Range - mm² 2.5-35mm² Features - Color Gray	Package	-
Disconnect Type - Number of Positions 2 Number of Levels 1 Terminal - Width 16.0mm Termination Style Push In, Spring Current - IEC 125A Voltage - IEC 1000V Current - UL 115A Voltage - UL 600V Wire Gauge or Range - AWG 2-14 AWG Wire Gauge or Range - mm² 2.5-35mm² Features - Color Gray	Series	CLIPLINE ST
Number of Positions2Number of Levels1Terminal - Width16.0mmTermination StylePush In, SpringCurrent - IEC125AVoltage - IEC1000VCurrent - UL115AVoltage - UL600VWire Gauge or Range - AWG2-14 AWGWire Gauge or Range - mm²2.5-35mm²Features-ColorGray	Туре	Feed Through
Number of Levels 1 Terminal - Width 16.0mm Termination Style Push In, Spring Current - IEC 125A Voltage - IEC 1000V Current - UL 115A Voltage - UL 600V Wire Gauge or Range - AWG 2-14 AWG Wire Gauge or Range - mm² 2.5-35mm² Features - Color Gray	Disconnect Type	-
Terminal - Width Termination Style Push In, Spring Current - IEC 125A Voltage - IEC 1000V Current - UL 115A Voltage - UL 600V Wire Gauge or Range - AWG Wire Gauge or Range - mm² Features Color Gray	Number of Positions	2
Termination Style Current - IEC 125A Voltage - IEC 1000V Current - UL 115A Voltage - UL 600V Wire Gauge or Range - AWG Wire Gauge or Range - mm² Features - Color Push In, Spring 125A 1000V 215A 1000V 215A 115A 600V 600	Number of Levels	1
Current - IEC 125A Voltage - IEC 1000V Current - UL 115A Voltage - UL 600V Wire Gauge or Range - AWG 2-14 AWG Wire Gauge or Range - mm² 2.5-35mm² Features - Color Gray	Terminal - Width	16.0mm
Voltage - IEC Current - UL 115A Voltage - UL 600V Wire Gauge or Range - AWG Wire Gauge or Range - mm² 2.5-35mm² Features - Color Gray	Termination Style	Push In, Spring
Current - UL 115A Voltage - UL 600V Wire Gauge or Range - AWG 2-14 AWG Wire Gauge or Range - mm² 2.5-35mm² Features - Gray	Current - IEC	125A
Voltage - UL Wire Gauge or Range - AWG Wire Gauge or Range - mm² 2.5-35mm² Features Color Gray	Voltage - IEC	1000V
Wire Gauge or Range - AWG Wire Gauge or Range - mm² 2-14 AWG 2.5-35mm² Features - Color Gray	Current - UL	115A
Wire Gauge or Range - mm ² Features Color Gray	Voltage - UL	600V
Features - Color Gray	Wire Gauge or Range - AWG	2-14 AWG
Color Gray	Wire Gauge or Range - mm ²	2.5-35mm ²
	Features	-
Report errors?	Color	Gray
		Report errors?

3036178 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

3036178 Payment Methods



















3036178 Shipping Methods













If you have any question about 3036178, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com