

3036521 Information

Heisener.com

Part Number 3036521

Manufacturer Phoenix Contact

Category Connectors, Interconnects

Terminal Blocks - Din Rail, Channel

Description CONN TERM BLK FEED THRU 12-28AWG

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









3036521 Specifications

| Manufacturer Part Number 3036521 Manufacturer Phoenix Contact Category Connectors, Interconnects Terminal Blocks - Din Rail, Channel Package - Series CLIPLINE ST Type Feed Through Disconnect Type - Number of Positions 3 Number of Levels 1 Terminal - Width 5.2mm Termination Style Push In, Spring Current - IEC 0.5A Voltage - IEC 800V Current - UL 20A Voltage - UL 600V Wire Gauge or Range - AWG 12-28 AWG Wire Gauge or Range - mm² 0.08-4mm² Features Diode Color Gray | | |
|--|---------------------------------------|-------------------------------------|
| Category Connectors, Interconnects Terminal Blocks - Din Rail, Channel Package - Series CLIPLINE ST Type Feed Through Disconnect Type - Number of Positions 3 Number of Levels 1 Terminal - Width 5.2mm Termination Style Push In, Spring Current - IEC 0.5A Voltage - IEC 800V Current - UL 20A Voltage - UL 600V Wire Gauge or Range - AWG 12-28 AWG Wire Gauge or Range - mm² 0.08-4mm² Features Diode Color Gray | Manufacturer Part Number | 3036521 |
| Package - CLIPLINE ST Type Feed Through Disconnect Type - Number of Positions 3 Number of Levels 1 Terminal - Width 5.2mm Termination Style Push In, Spring Current - IEC 0.5A Voltage - IEC 800V Current - UL 20A Voltage - UL Wire Gauge or Range - AWG Wire Gauge or Range - AWG Color Color Color Voltage - Gauge or Gauge - March August Augu | Manufacturer | Phoenix Contact |
| Package - Series CLIPLINE ST Type Feed Through Disconnect Type - Number of Positions 3 Number of Levels 1 Terminal - Width 5.2mm Termination Style Push In, Spring Current - IEC 0.5A Voltage - IEC 800V Current - UL 20A Voltage - UL 600V Wire Gauge or Range - AWG 12-28 AWG Wire Gauge or Range - mm² 0.08-4mm² Features Diode Color Gray | Category | Connectors, Interconnects |
| Series CLIPLINE ST Type Feed Through Disconnect Type - Number of Positions 3 Number of Levels 1 Terminal - Width 5.2mm Termination Style Push In, Spring Current - IEC 0.5A Voltage - IEC 800V Current - UL 20A Voltage - UL 600V Wire Gauge or Range - AWG 12-28 AWG Wire Gauge or Range - mm² 0.08-4mm² Features Diode Color Gray | | Terminal Blocks - Din Rail, Channel |
| Type Feed Through Disconnect Type - Number of Positions 3 Number of Levels 1 Terminal - Width 5.2mm Termination Style Push In, Spring Current - IEC 0.5A Voltage - IEC 800V Current - UL 20A Voltage - UL 600V Wire Gauge or Range - AWG 12-28 AWG Wire Gauge or Range - mm² 0.08-4mm² Features Diode Color Gray | Package | - |
| Disconnect Type - Number of Positions 3 Number of Levels 1 Terminal - Width 5.2mm Termination Style Push In, Spring Current - IEC 0.5A Voltage - IEC 800V Current - UL 20A Voltage - UL 600V Wire Gauge or Range - AWG 12-28 AWG Wire Gauge or Range - mm² 0.08-4mm² Features Diode Color Gray | Series | CLIPLINE ST |
| Number of Positions3Number of Levels1Terminal - Width5.2mmTermination StylePush In, SpringCurrent - IEC0.5AVoltage - IEC800VCurrent - UL20AVoltage - UL600VWire Gauge or Range - AWG12-28 AWGWire Gauge or Range - mm²0.08-4mm²FeaturesDiodeColorGray | Туре | Feed Through |
| Number of Levels Terminal - Width 5.2mm Termination Style Push In, Spring Current - IEC 0.5A Voltage - IEC 800V Current - UL 20A Voltage - UL Wire Gauge or Range - AWG Wire Gauge or Range - awG Wire Gauge or Range - mm² Features Diode Color Gray | Disconnect Type | - |
| Terminal - Width Termination Style Push In, Spring Current - IEC 0.5A Voltage - IEC 800V Current - UL 20A Voltage - UL 600V Wire Gauge or Range - AWG Wire Gauge or Range - mm² Features Diode Color Gray | Number of Positions | 3 |
| Termination Style Current - IEC 0.5A Voltage - IEC 800V Current - UL 20A Voltage - UL 600V Wire Gauge or Range - AWG Wire Gauge or Range - mm² Features Diode Color Push In, Spring 0.5A 800V 800V 800V 000V 600V 600 | Number of Levels | 1 |
| Current - IEC 0.5A Voltage - IEC 800V Current - UL 20A Voltage - UL 600V Wire Gauge or Range - AWG 12-28 AWG Wire Gauge or Range - mm² 0.08-4mm² Features Diode Color Gray | Terminal - Width | 5.2mm |
| Voltage - IEC800VCurrent - UL20AVoltage - UL600VWire Gauge or Range - AWG12-28 AWGWire Gauge or Range - mm²0.08-4mm²FeaturesDiodeColorGray | Termination Style | Push In, Spring |
| Current - UL 20A Voltage - UL 600V Wire Gauge or Range - AWG 12-28 AWG Wire Gauge or Range - mm² 0.08-4mm² Features Diode Color Gray | Current - IEC | 0.5A |
| Voltage - UL600VWire Gauge or Range - AWG12-28 AWGWire Gauge or Range - mm²0.08-4mm²FeaturesDiodeColorGray | Voltage - IEC | 800V |
| Wire Gauge or Range - AWG Wire Gauge or Range - mm² O.08-4mm² Features Diode Color Gray | Current - UL | 20A |
| Wire Gauge or Range - mm² Features Color O.08-4mm² Diode Gray | Voltage - UL | 600V |
| Features Diode Color Gray | Wire Gauge or Range - AWG | 12-28 AWG |
| Color Gray | Wire Gauge or Range - mm ² | 0.08-4mm ² |
| | Features | Diode |
| Report errors? | Color | Gray |
| | | Report errors? |

3036521 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

3036521 Payment Methods



















3036521 Shipping Methods













If you have any question about 3036521, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com