

3037180 Information



For Reference Only

Part Number 3037180

Manufacturer Phoenix Contact

Category Connectors, Interconnects

Terminal Blocks - Din Rail, Channel

Description CONN TERM BLK FEED THRU 10-28AWG

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









3037180 Specifications

Manufacturer Part Number 3037180 Manufacturer Phoenix Contact Category Connectors, Interconnects Terminal Blocks - Din Rail, Channel Package - Series CLIPLINE ST Type Feed Through Disconnect Type - Number of Positions 2 Number of Levels 1 Terminal - Width 6.2mm Termination Style Push In, Spring Current - IEC 32A Voltage - IEC 800V Current - UL 30A Voltage - UL 600V Wire Gauge or Range - AWG 10-28 AWG Wire Gauge or Range - mm² 0.08-6mm² Features - Color Black		
Category Connectors, Interconnects Terminal Blocks - Din Rail, Channel Package - Series CLIPLINE ST Type Feed Through Disconnect Type - Number of Positions 2 Number of Levels 1 Terminal - Width 6.2mm Termination Style Push In, Spring Current - IEC 32A Voltage - IEC 800V Current - UL 30A Voltage - UL 600V Wire Gauge or Range - AWG 10-28 AWG Wire Gauge or Range - mm² 0.08-6mm² Features -	Manufacturer Part Number	3037180
Terminal Blocks - Din Rail, Channel	Manufacturer	Phoenix Contact
Package - Series CLIPLINE ST Type Feed Through Disconnect Type - Number of Positions 2 Number of Levels 1 Terminal - Width 6.2mm Termination Style Push In, Spring Current - IEC 32A Voltage - IEC 800V Current - UL 30A Voltage - UL 600V Wire Gauge or Range - AWG 10-28 AWG Wire Gauge or Range - mm² 0.08-6mm² Features -	Category	Connectors, Interconnects
Series CLIPLINE ST Type Feed Through Disconnect Type - Number of Positions 2 Number of Levels 1 Terminal - Width 6.2mm Termination Style Push In, Spring Current - IEC 32A Voltage - IEC 800V Current - UL 30A Voltage - UL 600V Wire Gauge or Range - AWG 10-28 AWG Wire Gauge or Range - mm² 0.08-6mm² Features -		Terminal Blocks - Din Rail, Channel
Type Feed Through Disconnect Type - Number of Positions 2 Number of Levels 1 Terminal - Width 6.2mm Termination Style Push In, Spring Current - IEC 32A Voltage - IEC 800V Current - UL 30A Voltage - UL 600V Wire Gauge or Range - AWG 10-28 AWG Wire Gauge or Range - mm² 0.08-6mm² Features -	Package	-
Disconnect Type - Number of Positions 2 Number of Levels 1 Terminal - Width 6.2mm Termination Style Push In, Spring Current - IEC 32A Voltage - IEC 800V Current - UL 30A Voltage - UL 600V Wire Gauge or Range - AWG 10-28 AWG Wire Gauge or Range - mm² 0.08-6mm² Features -	Series	CLIPLINE ST
Number of Positions 2 Number of Levels 1 Terminal - Width 6.2mm Termination Style Push In, Spring Current - IEC 32A Voltage - IEC 800V Current - UL 30A Voltage - UL 600V Wire Gauge or Range - AWG 10-28 AWG Wire Gauge or Range - mm² 0.08-6mm² Features -	Туре	Feed Through
Number of Levels 1 Terminal - Width 6.2mm Termination Style Push In, Spring Current - IEC 32A Voltage - IEC 800V Current - UL 30A Voltage - UL 600V Wire Gauge or Range - AWG 10-28 AWG Wire Gauge or Range - mm² 0.08-6mm² Features -	Disconnect Type	-
Terminal - Width Termination Style Push In, Spring Current - IEC 32A Voltage - IEC 800V Current - UL 30A Voltage - UL 600V Wire Gauge or Range - AWG Wire Gauge or Range - mm² Features - 6.2mm 6.2mm 6.2mm 10-28 AWG 000V	Number of Positions	2
Termination Style Current - IEC 32A Voltage - IEC 800V Current - UL 30A Voltage - UL 600V Wire Gauge or Range - AWG Wire Gauge or Range - mm² Features Push In, Spring 32A 800V 800V 10-28 AWG 10-28 AWG - 0.08-6mm²	Number of Levels	1
Current - IEC 32A Voltage - IEC 800V Current - UL 30A Voltage - UL 600V Wire Gauge or Range - AWG 10-28 AWG Wire Gauge or Range - mm² 0.08-6mm² Features -	Terminal - Width	6.2mm
Voltage - IEC 800V Current - UL 30A Voltage - UL 600V Wire Gauge or Range - AWG 10-28 AWG Wire Gauge or Range - mm² 0.08-6mm² Features -	Termination Style	Push In, Spring
Current - UL 30A Voltage - UL 600V Wire Gauge or Range - AWG 10-28 AWG Wire Gauge or Range - mm² 0.08-6mm² Features -	Current - IEC	32A
Voltage - UL 600V Wire Gauge or Range - AWG 10-28 AWG Wire Gauge or Range - mm² 0.08-6mm² Features -	Voltage - IEC	800V
Wire Gauge or Range - AWG Wire Gauge or Range - mm ² Features 10-28 AWG 0.08-6mm ² -	Current - UL	30A
Wire Gauge or Range - mm ² Features 0.08-6mm ² -	Voltage - UL	600V
Features -	Wire Gauge or Range - AWG	10-28 AWG
	Wire Gauge or Range - mm ²	0.08-6mm ²
Color Black	Features	-
	Color	Black
Report errors?		Report errors?

3037180 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

3037180 Payment Methods





















3037180 Shipping Methods













If you have any question about 3037180, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com