

### 3037313 Information

Part Number 3037313

Manufacturer Phoenix Contact

Category Connectors, Interconnects

Terminal Blocks - Din Rail, Channel

**Description** CONN TERM BLK FEED THRU 12-28AWG

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

### **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









## **3037313 Specifications**

Manufacturer Part Number         3037313           Manufacturer         Phoenix Contact           Category         Connectors, Interconnects           Terminal Blocks - Din Rail, Channel           Package         -           Series         CLIPLINE ST           Type         Feed Through           Disconnect Type         -           Number of Positions         3           Number of Levels         1           Terminal - Width         5.2mm           Termination Style         Push In, Spring           Current - IEC         24A           Voltage - IEC         800V           Current - UL         20A           Voltage - UL         600V           Wire Gauge or Range - AWG         12-28 AWG           Wire Gauge or Range - mm²         0.08-4mm²		
Category         Connectors, Interconnects           Terminal Blocks - Din Rail, Channel           Package         -           Series         CLIPLINE ST           Type         Feed Through           Disconnect Type         -           Number of Positions         3           Number of Levels         1           Terminal - Width         5.2mm           Termination Style         Push In, Spring           Current - IEC         24A           Voltage - IEC         800V           Current - UL         20A           Voltage - UL         600V           Wire Gauge or Range - AWG         12-28 AWG           Wire Gauge or Range - mm²         0.08-4mm²	Manufacturer Part Number	3037313
Terminal Blocks - Din Rail, Channel	Manufacturer	Phoenix Contact
Package         -           Series         CLIPLINE ST           Type         Feed Through           Disconnect Type         -           Number of Positions         3           Number of Levels         1           Terminal - Width         5.2mm           Termination Style         Push In, Spring           Current - IEC         24A           Voltage - IEC         800V           Current - UL         20A           Voltage - UL         600V           Wire Gauge or Range - AWG         12-28 AWG           Wire Gauge or Range - mm²         0.08-4mm²	Category	Connectors, Interconnects
Series         CLIPLINE ST           Type         Feed Through           Disconnect Type         -           Number of Positions         3           Number of Levels         1           Terminal - Width         5.2mm           Termination Style         Push In, Spring           Current - IEC         24A           Voltage - IEC         800V           Current - UL         20A           Voltage - UL         600V           Wire Gauge or Range - AWG         12-28 AWG           Wire Gauge or Range - mm²         0.08-4mm²		Terminal Blocks - Din Rail, Channel
Type Feed Through  Disconnect Type - Number of Positions 3 Number of Levels 1 Terminal - Width 5.2mm  Termination Style Push In, Spring  Current - IEC 24A  Voltage - IEC 800V  Current - UL 20A  Voltage - UL 600V  Wire Gauge or Range - AWG 12-28 AWG  Wire Gauge or Range - mm² 0.08-4mm²	Package	-
Disconnect Type         -           Number of Positions         3           Number of Levels         1           Terminal - Width         5.2mm           Termination Style         Push In, Spring           Current - IEC         24A           Voltage - IEC         800V           Current - UL         20A           Voltage - UL         600V           Wire Gauge or Range - AWG         12-28 AWG           Wire Gauge or Range - mm²         0.08-4mm²	Series	CLIPLINE ST
Number of Positions       3         Number of Levels       1         Terminal - Width       5.2mm         Termination Style       Push In, Spring         Current - IEC       24A         Voltage - IEC       800V         Current - UL       20A         Voltage - UL       600V         Wire Gauge or Range - AWG       12-28 AWG         Wire Gauge or Range - mm²       0.08-4mm²	Туре	Feed Through
Number of Levels  Terminal - Width  5.2mm  Termination Style  Push In, Spring  Current - IEC  24A  Voltage - IEC  800V  Current - UL  20A  Voltage - UL  600V  Wire Gauge or Range - AWG  Wire Gauge or Range - mm²  1  1  5.2mm  600V  800V  600V  600V	Disconnect Type	-
Terminal - Width  Termination Style  Push In, Spring  Current - IEC  24A  Voltage - IEC  800V  Current - UL  20A  Voltage - UL  600V  Wire Gauge or Range - AWG  Wire Gauge or Range - mm²  0.08-4mm²	Number of Positions	3
Termination Style         Push In, Spring           Current - IEC         24A           Voltage - IEC         800V           Current - UL         20A           Voltage - UL         600V           Wire Gauge or Range - AWG         12-28 AWG           Wire Gauge or Range - mm²         0.08-4mm²	Number of Levels	1
Current - IEC       24A         Voltage - IEC       800V         Current - UL       20A         Voltage - UL       600V         Wire Gauge or Range - AWG       12-28 AWG         Wire Gauge or Range - mm²       0.08-4mm²	Terminal - Width	5.2mm
Voltage - IEC       800V         Current - UL       20A         Voltage - UL       600V         Wire Gauge or Range - AWG       12-28 AWG         Wire Gauge or Range - mm²       0.08-4mm²	Termination Style	Push In, Spring
Current - UL       20A         Voltage - UL       600V         Wire Gauge or Range - AWG       12-28 AWG         Wire Gauge or Range - mm²       0.08-4mm²	Current - IEC	24A
Voltage - UL 600V Wire Gauge or Range - AWG 12-28 AWG Wire Gauge or Range - mm² 0.08-4mm²	Voltage - IEC	800V
Wire Gauge or Range - AWG  Wire Gauge or Range - mm <sup>2</sup> 12-28 AWG  0.08-4mm <sup>2</sup>	Current - UL	20A
Wire Gauge or Range - mm <sup>2</sup> 0.08-4mm <sup>2</sup>	Voltage - UL	600V
	Wire Gauge or Range - AWG	12-28 AWG
	Wire Gauge or Range - mm <sup>2</sup>	0.08-4mm <sup>2</sup>
Features -	Features	-
Color Yellow	Color	Yellow
Report errors?		Report errors?

#### 3037313 Guarantees



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

# 3037313 Payment Methods





















## 3037313 Shipping Methods













If you have any question about 3037313, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com