

3037410 Information



For Reference Only

Part Number 3037410

Manufacturer Phoenix Contact

Category Connectors, Interconnects

Terminal Blocks - Din Rail, Channel

Description CONN TERM BLK FEED THRU 12-28AWG

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









3037410 Specifications

Manufacturer Part Number 3037410 Manufacturer Phoenix Contact Category Connectors, Interconnects Terminal Blocks - Din Rail, Channel Package Series CLIPLINE ST Type Feed Through Disconnect Type - Number of Positions 4 Number of Levels 1 Terminal - Width 5.2mm Termination Style Push In, Spring Current - IEC 24A Voltage - IEC 800V Current - UL 20A Voltage - UL 600V Wire Gauge or Range - AWG 12-28 AWG Wire Gauge or Range - mm² 0.08-4mm² Features - Color Red		
Category Connectors, Interconnects Terminal Blocks - Din Rail, Channel Package - Series CLIPLINE ST Type Feed Through Disconnect Type - Number of Positions 4 Number of Levels 1 Terminal - Width 5.2mm Termination Style Push In, Spring Current - IEC 24A Voltage - IEC 800V Current - UL 20A Voltage - UL 600V Wire Gauge or Range - AWG 12-28 AWG Wire Gauge or Range - mm² 0.08-4mm² Features - Color Red	Manufacturer Part Number	3037410
Package - CLIPLINE ST Type Feed Through Disconnect Type - Number of Positions 4 Number of Levels 1 Terminal - Width 5.2mm Termination Style Push In, Spring Current - IEC 24A Voltage - IEC 800V Current - UL 20A Voltage - UL Wire Gauge or Range - AWG Wire Gauge or Range - mm² 0.08-4mm² Features - Color Red	Manufacturer	Phoenix Contact
Package - Series CLIPLINE ST Type Feed Through Disconnect Type - Number of Positions 4 Number of Levels 1 Terminal - Width 5.2mm Termination Style Push In, Spring Current - IEC 24A Voltage - IEC 800V Current - UL 20A Voltage - UL 600V Wire Gauge or Range - AWG 12-28 AWG Wire Gauge or Range - mm² 0.08-4mm² Features - Color Red	Category	Connectors, Interconnects
Series CLIPLINE ST Type Feed Through Disconnect Type - Number of Positions 4 Number of Levels 1 Terminal - Width 5.2mm Termination Style Push In, Spring Current - IEC 24A Voltage - IEC 800V Current - UL 20A Voltage - UL 600V Wire Gauge or Range - AWG 12-28 AWG Wire Gauge or Range - mm² 0.08-4mm² Features - Color Red		Terminal Blocks - Din Rail, Channel
Type Feed Through Disconnect Type - Number of Positions 4 Number of Levels 1 Terminal - Width 5.2mm Termination Style Push In, Spring Current - IEC 24A Voltage - IEC 800V Current - UL 20A Voltage - UL 600V Wire Gauge or Range - AWG 12-28 AWG Wire Gauge or Range - mm² 0.08-4mm² Features - Color Red	Package	-
Disconnect Type - Number of Positions 4 Number of Levels 1 Terminal - Width 5.2mm Termination Style Push In, Spring Current - IEC 24A Voltage - IEC 800V Current - UL 20A Voltage - UL 600V Wire Gauge or Range - AWG 12-28 AWG Wire Gauge or Range - mm² 0.08-4mm² Features - Color Red	Series	CLIPLINE ST
Number of Positions Number of Levels 1 Terminal - Width 5.2mm Termination Style Push In, Spring Current - IEC 24A Voltage - IEC 800V Current - UL 20A Voltage - UL 600V Wire Gauge or Range - AWG Wire Gauge or Range - mm² 0.08-4mm² Features Color Red	Туре	Feed Through
Number of Levels 1 Terminal - Width 5.2mm Termination Style Push In, Spring Current - IEC 24A Voltage - IEC 800V Current - UL 20A Voltage - UL 600V Wire Gauge or Range - AWG 12-28 AWG Wire Gauge or Range - mm² 0.08-4mm² Features - Color Red	Disconnect Type	-
Terminal - Width Termination Style Push In, Spring Current - IEC 24A Voltage - IEC 800V Current - UL 20A Voltage - UL 600V Wire Gauge or Range - AWG Wire Gauge or Range - mm² Features Color Red	Number of Positions	4
Termination Style Current - IEC 24A Voltage - IEC 800V Current - UL 20A Voltage - UL 600V Wire Gauge or Range - AWG Wire Gauge or Range - mm² Features Color Push In, Spring 24A 800V 800V 800V 000V 600V 600V Red	Number of Levels	1
Current - IEC 24A Voltage - IEC 800V Current - UL 20A Voltage - UL 600V Wire Gauge or Range - AWG 12-28 AWG Wire Gauge or Range - mm² 0.08-4mm² Features - Color Red	Terminal - Width	5.2mm
Voltage - IEC800VCurrent - UL20AVoltage - UL600VWire Gauge or Range - AWG12-28 AWGWire Gauge or Range - mm²0.08-4mm²Features-ColorRed	Termination Style	Push In, Spring
Current - UL 20A Voltage - UL 600V Wire Gauge or Range - AWG 12-28 AWG Wire Gauge or Range - mm² 0.08-4mm² Features - Color Red	Current - IEC	24A
Voltage - UL Wire Gauge or Range - AWG Wire Gauge or Range - mm² 0.08-4mm² Features Color Red	Voltage - IEC	800V
Wire Gauge or Range - AWG Wire Gauge or Range - mm² 0.08-4mm² Features - Color Red	Current - UL	20A
Wire Gauge or Range - mm² Features Color Red 0.08-4mm² - Red	Voltage - UL	600V
Features - Color Red	Wire Gauge or Range - AWG	12-28 AWG
Color Red	Wire Gauge or Range - mm ²	0.08-4mm ²
	Features	-
Panort arrors?	Color	Red
Report errors:		Report errors?

3037410 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

3037410 Payment Methods





















3037410 Shipping Methods













If you have any question about 3037410, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com