

3040054 Information

For Reference Only

Part Number 3040054

Manufacturer Phoenix Contact

Category Connectors, Interconnects Terminal Blocks - Specialized

Description TERM BLK PLUG 4POS 5.2MM GRAY

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









3040054 Specifications

Manufacturer Part Number 3040054 Manufacturer Phoenix Contact Category Connectors, Interconnects Terminal Blocks - Specialized Package - Series CLIPLINE STTB Type Plug Connection Mounting Type DIN Rail Number of Positions 4 Number of Levels 2 Terminal - Width 5.2mm Termination Style Plug Receptacles, Push In, Spring Current - IEC 22A Voltage - IEC 500V Current - UL 20A Voltage - UL 600V Wire Gauge or Range - AWG 12-28 AWG Wire Gauge or Range - mm² 0.08-4mm² Features - Housing Color Gray		
CategoryConnectors, InterconnectsPackage-SeriesCLIPLINE STTBTypePlug ConnectionMounting TypeDIN RailNumber of Positions4Number of Levels2Terminal - Width5.2mmTermination StylePlug Receptacles, Push In, SpringCurrent - IEC22AVoltage - IEC500VCurrent - UL20AVoltage - UL600VWire Gauge or Range - AWG12-28 AWGWire Gauge or Range - mm²0.08-4mm²Features-Housing ColorGray	Manufacturer Part Number	3040054
Package - CLIPLINE STTB Type Plug Connection Mounting Type DIN Rail Number of Positions 4 Number of Levels 2 Terminal - Width 5.2mm Termination Style Plug Receptacles, Push In, Spring Current - IEC 22A Voltage - IEC 500V Current - UL 20A Voltage - UL Wire Gauge or Range - AWG 12-28 AWG Wire Gauge or Range - mm² 0.08-4mm² Features - Housing Color Gray	Manufacturer	Phoenix Contact
Package - Series CLIPLINE STTB Type Plug Connection Mounting Type DIN Rail Number of Positions 4 Number of Levels 2 Terminal - Width 5.2mm Termination Style Plug Receptacles, Push In, Spring Current - IEC 22A Voltage - IEC 500V Current - UL 20A Voltage - UL 600V Wire Gauge or Range - AWG 12-28 AWG Wire Gauge or Range - mm² 0.08-4mm² Features - Housing Color Gray	Category	Connectors, Interconnects
SeriesCLIPLINE STTBTypePlug ConnectionMounting TypeDIN RailNumber of Positions4Number of Levels2Terminal - Width5.2mmTermination StylePlug Receptacles, Push In, SpringCurrent - IEC22AVoltage - IEC500VCurrent - UL20AVoltage - UL600VWire Gauge or Range - AWG12-28 AWGWire Gauge or Range - mm²0.08-4mm²Features-Housing ColorGray		Terminal Blocks - Specialized
Type Plug Connection Mounting Type DIN Rail Number of Positions 4 Number of Levels 2 Terminal - Width 5.2mm Termination Style Plug Receptacles, Push In, Spring Current - IEC 22A Voltage - IEC 500V Current - UL 20A Voltage - UL 600V Wire Gauge or Range - AWG 12-28 AWG Wire Gauge or Range - ame 0.08-4mm² Features - Housing Color Gray	Package	-
Mounting TypeDIN RailNumber of Positions4Number of Levels2Terminal - Width5.2mmTermination StylePlug Receptacles, Push In, SpringCurrent - IEC22AVoltage - IEC500VCurrent - UL20AVoltage - UL600VWire Gauge or Range - AWG12-28 AWGWire Gauge or Range - mm²0.08-4mm²Features-Housing ColorGray	Series	CLIPLINE STTB
Number of Positions4Number of Levels2Terminal - Width5.2mmTermination StylePlug Receptacles, Push In, SpringCurrent - IEC22AVoltage - IEC500VCurrent - UL20AVoltage - UL600VWire Gauge or Range - AWG12-28 AWGWire Gauge or Range - mm²0.08-4mm²Features-Housing ColorGray	Туре	Plug Connection
Number of Levels Terminal - Width 5.2mm Termination Style Plug Receptacles, Push In, Spring Current - IEC 22A Voltage - IEC 500V Current - UL 20A Voltage - UL 600V Wire Gauge or Range - AWG Wire Gauge or Range - mm² Features - Housing Color Gray	Mounting Type	DIN Rail
Terminal - Width Termination Style Plug Receptacles, Push In, Spring Current - IEC 22A Voltage - IEC 500V Current - UL 20A Voltage - UL 600V Wire Gauge or Range - AWG Wire Gauge or Range - mm² Features - Housing Color 5.2mm 5.2mm 5.2mm 6.24A Plug Receptacles, Push In, Spring 22A 20A 20A 20A 00V 600V 60	Number of Positions	4
Termination Style Plug Receptacles, Push In, Spring Current - IEC 22A Voltage - IEC 500V Current - UL 20A Voltage - UL 600V Wire Gauge or Range - AWG 12-28 AWG Wire Gauge or Range - mm² 0.08-4mm² Features - Housing Color Gray	Number of Levels	2
Current - IEC 22A Voltage - IEC 500V Current - UL 20A Voltage - UL 600V Wire Gauge or Range - AWG 12-28 AWG Wire Gauge or Range - mm² 0.08-4mm² Features - Housing Color Gray	Terminal - Width	5.2mm
Voltage - IEC500VCurrent - UL20AVoltage - UL600VWire Gauge or Range - AWG12-28 AWGWire Gauge or Range - mm²0.08-4mm²Features-Housing ColorGray	Termination Style	Plug Receptacles, Push In, Spring
Current - UL 20A Voltage - UL 600V Wire Gauge or Range - AWG 12-28 AWG Wire Gauge or Range - mm² 0.08-4mm² Features - Gray	Current - IEC	22A
Voltage - UL600VWire Gauge or Range - AWG12-28 AWGWire Gauge or Range - mm²0.08-4mm²Features-Housing ColorGray	Voltage - IEC	500V
Wire Gauge or Range - AWG Wire Gauge or Range - mm² 0.08-4mm² Features - Housing Color Gray	Current - UL	20A
Wire Gauge or Range - mm² Features - Housing Color Gray	Voltage - UL	600V
Features - Gray	Wire Gauge or Range - AWG	12-28 AWG
Housing Color Gray	Wire Gauge or Range - mm ²	0.08-4mm ²
	Features	-
Report errors?	Housing Color	Gray
		Report errors?

3040054 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

3040054 Payment Methods





















3040054 Shipping Methods













If you have any question about 3040054, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com