

3046235 Information

Heisener.com

Part Number 3046235

Manufacturer Phoenix Contact

Category Connectors, Interconnects

Terminal Blocks - Din Rail, Channel

Description CONN TERM BLK FEED THRU 10-26AWG

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









3046235 Specifications

ManufacturerPhoenix ContactCategoryConnectors, InterconnectsTerminal Blocks - Din Rail, ChannelPackage-SeriesCLIPLINE UTTypeFeed Through, IsolatedDisconnect Type-Number of Positions3Number of Levels2; 1 GroundedTerminal - Width6.2mmTermination StyleScrewCurrent - IEC0.5AVoltage - IEC500VCurrent - UL0.5AVoltage - UL300VWire Gauge or Range - AWG10-26 AWGWire Gauge or Range - mm²0.14-6mm²FeaturesDiodeColorGray		
Category Connectors, Interconnects Terminal Blocks - Din Rail, Channel Package - Series CLIPLINE UT Type Feed Through, Isolated Disconnect Type - Number of Positions 3 Number of Levels 2; 1 Grounded Terminal - Width 6.2mm Termination Style Screw Current - IEC 0.5A Voltage - IEC 500V Current - UL 0.5A Voltage - UL 300V Wire Gauge or Range - AWG Wire Gauge or Range - AWG Wire Gauge or Range - mm² Features Color Gray	Manufacturer Part Number	3046235
Package - Series CLIPLINE UT Type Feed Through, Isolated Disconnect Type - Number of Positions 3 Number of Levels 2; 1 Grounded Terminal - Width 6.2mm Termination Style Screw Current - IEC 0.5A Voltage - IEC 500V Current - UL 0.5A Voltage - UL Wire Gauge or Range - AWG Wire Gauge or Range - mm² Peatures Color Gray	Manufacturer	Phoenix Contact
Package - Series CLIPLINE UT Type Feed Through, Isolated Disconnect Type - Number of Positions 3 Number of Levels 2; 1 Grounded Terminal - Width 6.2mm Termination Style Screw Current - IEC 0.5A Voltage - IEC 500V Current - UL 0.5A Voltage - UL 300V Wire Gauge or Range - AWG 10-26 AWG Wire Gauge or Range - mm² 0.14-6mm² Features Diode Color Gray	Category	Connectors, Interconnects
Series CLIPLINE UT Type Feed Through, Isolated Disconnect Type - Number of Positions 3 Number of Levels 2; 1 Grounded Terminal - Width 6.2mm Termination Style Screw Current - IEC 0.5A Voltage - IEC 500V Current - UL 0.5A Voltage - UL 300V Wire Gauge or Range - AWG 10-26 AWG Wire Gauge or Range - mm² 0.14-6mm² Features Diode Color Gray		Terminal Blocks - Din Rail, Channel
Type Feed Through, Isolated Disconnect Type - Number of Positions 3 Number of Levels 2; 1 Grounded Terminal - Width 6.2mm Termination Style Screw Current - IEC 0.5A Voltage - IEC 500V Current - UL 0.5A Voltage - UL 300V Wire Gauge or Range - AWG 10-26 AWG Wire Gauge or Range - mm² 0.14-6mm² Features Diode Color Gray	Package	-
Disconnect Type Number of Positions 3 Number of Levels 2; 1 Grounded Terminal - Width 6.2mm Termination Style Screw Current - IEC 0.5A Voltage - IEC 500V Current - UL 0.5A Voltage - UL 300V Wire Gauge or Range - AWG Wire Gauge or Range - mm² Features Diode Color Gray	Series	CLIPLINE UT
Number of Positions3Number of Levels2; 1 GroundedTerminal - Width6.2mmTermination StyleScrewCurrent - IEC0.5AVoltage - IEC500VCurrent - UL0.5AVoltage - UL300VWire Gauge or Range - AWG10-26 AWGWire Gauge or Range - mm²0.14-6mm²FeaturesDiodeColorGray	Туре	Feed Through, Isolated
Number of Levels Terminal - Width 6.2mm Termination Style Screw Current - IEC 0.5A Voltage - IEC 500V Current - UL 0.5A Voltage - UL 300V Wire Gauge or Range - AWG Wire Gauge or Range - mm² Features Diode Color Gray	Disconnect Type	-
Terminal - Width Termination Style Screw Current - IEC 0.5A Voltage - IEC 500V Current - UL 0.5A Voltage - UL 300V Wire Gauge or Range - AWG Wire Gauge or Range - mm² Features Diode Color Gray	Number of Positions	3
Termination Style Current - IEC 0.5A Voltage - IEC 500V Current - UL 0.5A Voltage - UL 300V Wire Gauge or Range - AWG Wire Gauge or Range - mm² Features Diode Color Gray	Number of Levels	2; 1 Grounded
Current - IEC 0.5A Voltage - IEC 500V Current - UL 0.5A Voltage - UL 300V Wire Gauge or Range - AWG 10-26 AWG Wire Gauge or Range - mm² 0.14-6mm² Features Diode Color Gray	Terminal - Width	6.2mm
Voltage - IEC500VCurrent - UL0.5AVoltage - UL300VWire Gauge or Range - AWG10-26 AWGWire Gauge or Range - mm²0.14-6mm²FeaturesDiodeColorGray	Termination Style	Screw
Current - UL 0.5A Voltage - UL 300V Wire Gauge or Range - AWG 10-26 AWG Wire Gauge or Range - mm² 0.14-6mm² Features Diode Color Gray	Current - IEC	0.5A
Voltage - UL300VWire Gauge or Range - AWG10-26 AWGWire Gauge or Range - mm²0.14-6mm²FeaturesDiodeColorGray	Voltage - IEC	500V
Wire Gauge or Range - AWG Wire Gauge or Range - mm² O.14-6mm² Features Diode Color Gray	Current - UL	0.5A
Wire Gauge or Range - mm² Features Color Diode Gray	Voltage - UL	300V
Features Diode Color Gray	Wire Gauge or Range - AWG	10-26 AWG
Color Gray	Wire Gauge or Range - mm ²	0.14-6mm ²
	Features	Diode
Report errors?	Color	Gray
report errors.		Report errors?

3046235 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

3046235 Payment Methods





















3046235 Shipping Methods













If you have any question about 3046235, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com