



305PSB850K4R Information



For Reference Only

Part Number 305PSB850K4R
Manufacturer Illinois Capacitor
Category Capacitors
Film Capacitors

Description CAP FILM 3UF 10% 850VDC RAD 4LD

Package Radial - 4 Leads

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









305PSB850K4R Specifications

Manufacturer Part Number 305PSB850K4R Manufacturer Illinois Capacitors Category Capacitors Package Radial - 4 Leads Series PSB Capacitance 3µF Tolerance ±10% Voltage Rating - AC 500V Voltage Rating - DC 850V Dielectric Material Polypropylene (PP), Metallized ESR (Equivalent Series Resistance) 2.3 mOhm Operating Temperature -40°C ~ 100°C Mounting Type Through Hole Package / Case Radial - 4 Leads Size / Dimension 2.264" L x 1.181" W (57.50mm x 30.00mm) Height - Seated (Max) 1.772" (45.00mm) Termination PC Pins Lead Spacing 2.067" (52.50mm) Applications High Frequency, Switching; High Pulse, DV/DT; Snubber Features -	•		
CategoryCapacitorsPackageRadial - 4 LeadsSeriesPSBCapacitance3μFTolerance±10%Voltage Rating - AC500VVoltage Rating - DC850VDielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)2.3 mOhmOperating Temperature-40°C ~ 100°CMounting TypeThrough HolePackage / CaseRadial - 4 LeadsSize / Dimension2.264" L x 1.181" W (57.50mm x 30.00mm)Height - Seated (Max)1.772" (45.00mm)TerminationPC PinsLead Spacing2.067" (52.50mm)ApplicationsHigh Frequency, Switching; High Pulse, DV/DT; SnubberFeatures-	Manufacturer Part Number	305PSB850K4R	
$\begin{array}{c} \begin{tabular}{lll} Film Capacitors \\ \begin{tabular}{lll} Package & Radial - 4 Leads \\ \begin{tabular}{lll} Series & PSB \\ \begin{tabular}{lll} Capacitance & 98B \\ \begin{tabular}{lll} Capacitance & μ	Manufacturer	Illinois Capacitor	
PackageRadial - 4 LeadsSeriesPSBCapacitance3μFTolerance±10%Voltage Rating - AC500VVoltage Rating - DC850VDielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)2.3 mOhmOperating Temperature-40°C ~ 100°CMounting TypeThrough HolePackage / CaseRadial - 4 LeadsSize / Dimension2.264" L x 1.181" W (57.50mm x 30.00mm)Height - Seated (Max)1.772" (45.00mm)TerminationPC PinsLead Spacing2.067" (52.50mm)ApplicationsHigh Frequency, Switching; High Pulse, DV/DT; SnubberFeatures-	Category	Capacitors	
Series PSB Capacitance 3µF Tolerance ±10% Voltage Rating - AC 500V Voltage Rating - DC 850V Dielectric Material Polypropylene (PP), Metallized ESR (Equivalent Series Resistance) 2.3 mOhm Operating Temperature -40°C ~ 100°C Mounting Type Through Hole Package / Case Radial - 4 Leads Size / Dimension 2.264" L x 1.181" W (57.50mm x 30.00mm) Height - Seated (Max) 1.772" (45.00mm) Termination PC Pins Lead Spacing 2.067" (52.50mm) Applications High Frequency, Switching; High Pulse, DV/DT; Snubber Features		Film Capacitors	
Capacitance $3\mu F$ Tolerance $\pm 10\%$ Voltage Rating - AC $500V$ Voltage Rating - DC $850V$ Dielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance) 2.3 mOhm Operating Temperature $-40^{\circ}\text{C} \sim 100^{\circ}\text{C}$ Mounting TypeThrough HolePackage / CaseRadial - 4 LeadsSize / Dimension $2.264^{\circ}\text{L x 1.181}^{\circ}\text{W (57.50mm x 30.00mm)}$ Height - Seated (Max) 1.772° (45.00mm)TerminationPC PinsLead Spacing 2.067° (52.50mm)ApplicationsHigh Frequency, Switching; High Pulse, DV/DT; SnubberFeatures-	Package	Radial - 4 Leads	
Tolerance ±10% Voltage Rating - AC 500V Voltage Rating - DC 850V Dielectric Material Polypropylene (PP), Metallized ESR (Equivalent Series Resistance) 2.3 mOhm Operating Temperature -40°C ~ 100°C Mounting Type Through Hole Package / Case Radial - 4 Leads Size / Dimension 2.264" L x 1.181" W (57.50mm x 30.00mm) Height - Seated (Max) 1.772" (45.00mm) Termination PC Pins Lead Spacing 2.067" (52.50mm) Applications High Frequency, Switching; High Pulse, DV/DT; Snubber Features -	Series	PSB	
Voltage Rating - AC Voltage Rating - DC 850V Dielectric Material Polypropylene (PP), Metallized ESR (Equivalent Series Resistance) Operating Temperature -40°C ~ 100°C Mounting Type Through Hole Package / Case Radial - 4 Leads Size / Dimension Height - Seated (Max) 1.772" (45.00mm) Termination PC Pins Lead Spacing 2.067" (52.50mm) High Frequency, Switching; High Pulse, DV/DT; Snubber Features -	Capacitance	3μF	
Voltage Rating - DC Dielectric Material Polypropylene (PP), Metallized ESR (Equivalent Series Resistance) 2.3 mOhm Operating Temperature -40°C ~ 100°C Mounting Type Through Hole Package / Case Radial - 4 Leads Size / Dimension 2.264" L x 1.181" W (57.50mm x 30.00mm) Height - Seated (Max) 1.772" (45.00mm) Termination PC Pins Lead Spacing 2.067" (52.50mm) Applications High Frequency, Switching; High Pulse, DV/DT; Snubber Features -	Tolerance	±10%	
Dielectric Material Polypropylene (PP), Metallized ESR (Equivalent Series Resistance) 2.3 mOhm Operating Temperature -40°C ~ 100°C Mounting Type Through Hole Package / Case Radial - 4 Leads Size / Dimension 2.264" L x 1.181" W (57.50mm x 30.00mm) Height - Seated (Max) 1.772" (45.00mm) Termination PC Pins Lead Spacing 2.067" (52.50mm) Applications High Frequency, Switching; High Pulse, DV/DT; Snubber Features -	Voltage Rating - AC	500V	
ESR (Equivalent Series Resistance) Operating Temperature -40°C ~ 100°C Mounting Type Through Hole Package / Case Radial - 4 Leads Size / Dimension 2.264" L x 1.181" W (57.50mm x 30.00mm) Height - Seated (Max) 1.772" (45.00mm) Termination PC Pins Lead Spacing 2.067" (52.50mm) Applications High Frequency, Switching; High Pulse, DV/DT; Snubber Features -	Voltage Rating - DC	850V	
Operating Temperature -40°C ~ 100°C Mounting Type Through Hole Package / Case Radial - 4 Leads Size / Dimension 2.264" L x 1.181" W (57.50mm x 30.00mm) Height - Seated (Max) 1.772" (45.00mm) Termination PC Pins Lead Spacing 2.067" (52.50mm) Applications High Frequency, Switching; High Pulse, DV/DT; Snubber Features -	Dielectric Material	Polypropylene (PP), Metallized	
Mounting Type Package / Case Radial - 4 Leads Size / Dimension 2.264" L x 1.181" W (57.50mm x 30.00mm) Height - Seated (Max) 1.772" (45.00mm) Termination PC Pins Lead Spacing 2.067" (52.50mm) Applications High Frequency, Switching; High Pulse, DV/DT; Snubber Features -	ESR (Equivalent Series Resistance)	2.3 mOhm	
Package / Case Radial - 4 Leads Size / Dimension 2.264" L x 1.181" W (57.50mm x 30.00mm) Height - Seated (Max) 1.772" (45.00mm) Termination PC Pins Lead Spacing 2.067" (52.50mm) Applications High Frequency, Switching; High Pulse, DV/DT; Snubber Features -	Operating Temperature	-40°C ~ 100°C	
Size / Dimension 2.264" L x 1.181" W (57.50mm x 30.00mm) Height - Seated (Max) 1.772" (45.00mm) Termination PC Pins Lead Spacing 2.067" (52.50mm) Applications High Frequency, Switching; High Pulse, DV/DT; Snubber Features -	Mounting Type	Through Hole	
Height - Seated (Max) 1.772" (45.00mm) PC Pins Lead Spacing 2.067" (52.50mm) Applications High Frequency, Switching; High Pulse, DV/DT; Snubber Features -	Package / Case	Radial - 4 Leads	
Termination PC Pins Lead Spacing 2.067" (52.50mm) Applications High Frequency, Switching; High Pulse, DV/DT; Snubber Features -	Size / Dimension	2.264" L x 1.181" W (57.50mm x 30.00mm)	
Lead Spacing 2.067" (52.50mm) Applications High Frequency, Switching; High Pulse, DV/DT; Snubber Features -	Height - Seated (Max)	1.772" (45.00mm)	
Applications High Frequency, Switching; High Pulse, DV/DT; Snubber Features -	Termination	PC Pins	
Features -	Lead Spacing	2.067" (52.50mm)	
	Applications	High Frequency, Switching; High Pulse, DV/DT; Snubber	
Report errors?	Features	-	
			Report errors?

305PSB850K4R Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

305PSB850K4R Payment Methods



















305PSB850K4R Shipping Methods













If you have any question about 305PSB850K4R, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com