

307-050-542-202

307-050-542-202 Information

Heisener.com	Part Number Manufacturer Category Description Package		
For Reference Only		us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



307-050-542-202 Specifications

ManufacturerEDAC Inc.CategoryConnectors, InterconnectsCard Edge Connectors - Edgeboard ConnectorsPackage-Series307Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row25Number of Positions/Bay/Row062" (1.57mm)Number of Rows2Pitch0.156" (3.96mm)Features-Mounting TypeThrough HoleContact FinishGoldContact FinishGoldContact Type-Contact Type-Contact Type-Contact Type-Contact Type-Contact Finish Thickness-Contact Type-Contact Type-Contact Type-Fauge FeatureFush Mount, Top Opening, Unthreaded, 0.128" (3.25mm) DiaOperating Temperature-40°C ~ 105°C	•		
CategoryConnectors, InterconnectsCard Edge Connectors - Edgeboard ConnectorsPackage-Package307Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row25Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.156" (3.96mm)Features-Mounting TypeThrough HoleContact FinishGoldContact Finish Thickness-Contact Finish Thickness-Contact TypeGoldContact Type-Contact Type-Contact Type-Contact Finish Thickness-Contact TypeFeseFaque FeatureFush Mount, Top Opening, Unthreaded, 0.128" (3.25mm) DiaOperating Temperature40°C ~ 105°C	Manufacturer Part Number	307-050-542-202	
Card Edge Connectors - Edgeboard ConnectorsPackage-Series307Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row25Number of Positions0.062" (1.57mm)Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.156" (3.96mm)Features-Mounting TypeThrough HoleContact MaterialCopper, Nickel, Tin AlloyContact Finish Thickness-Contact Finish Thickness-Contact Type-Contact Type-Contact Type-Contact Type-Contact Type-Contact Type-Contact Type-Contact Type-Contact Type-Flange FeatureFlush Mount, Top Opening, Unthreaded, 0.128" (3.25mm) DiaOperating Temperature-Au°C ~ 105°C-	Manufacturer	EDAC Inc.	
Package-Series307Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row25Card Thickness0.062" (1.57mm)Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.156" (3.96mm)Features-Mounting TypeThrough HoleContact MaterialCopper, Nickel, Tin AlloyContact Finish Thickness-Contact Finish Thickness-Contact Type-Contact Type-Contact Type-Contact Type-Contact Type-Flange FeatureFlush Mount, Top Opening, Unthreaded, 0.128" (3.25mm) DiaOperating Temperature-40°C ~ 105°C	Category	Connectors, Interconnects	
Series307Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row25Number of Positions50Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.156" (3.96mm)Features-Mounting TypeThrough HoleContact Finish ThicknessCopper, Nickel, Tin AlloyContact Finish Thickness-Contact Type-Contact Type-Fange FeatureFeaturesFush Mount, Top Opening, Unthreaded, 0.128" (3.25mm) DiaOperating Temperature-40°C ~ 105°C		Card Edge Connectors - Edgeboard Connectors	
Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row25Number of Positions50Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.156" (3.96mm)Features-Mounting TypeThrough HoleContact MaterialCopper, Nickel, Tin AlloyContact Finish Thickness-Contact Finish Thickness-Contact TypeGeldContact TypeGreenFlange FeatureFush Mount, Top Opening, Unthreaded, 0.128" (3.25mm) DiaOperating Temperature-40°C ~ 105°C	Package	-	
GenderFemaleNumber of Positions/Bay/Row25Number of Positions50Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.156" (3.96mm)Features-Mounting Type1100 HoleContact MaterialCoper, Nickel, Tin AlloyContact Finish-Contact Finish Thickness-Contact Type-Contact Type-Fatures-Pitch-Contact Type-Contact Type-<	Series	307	
Number of Positions/Bay/Row25Number of Positions50Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.156" (3.96mm)Features-Mounting Type0.156" (3.96mm)Contact MaterialCopper, Nickel, Tin AlloyContact FinishGoldContact Finish Thickness-Contact Type-ColorGreenFlange FeatureFush Mount, Top Opening, Unthreaded, 0.128" (3.25mm) DiaOperating Temperature-40°C ~ 105°C	Card Type	Non Specified - Dual Edge	
Number of Positions 50 Card Thickness 0.062" (1.57mm) Number of Rows 2 Pitch 0.156" (3.96mm) Features - Mounting Type Through Hole Contact Material Copper, Nickel, Tin Alloy Contact Finish Gold Contact Type - Color Green Flange Feature Flush Mount, Top Opening, Unthreaded, 0.128" (3.25mm) Dia Operating Temperature -40°C ~ 105°C	Gender	Female	
Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.156" (3.96mm)Features-Mounting Type-TerminationWire WrapContact MaterialCopper, Nickel, Tin AlloyContact Finish Thickness-Contact Type-ColorGreenFlange FeatureFush Mount, Top Opening, Unthreaded, 0.128" (3.25mm) DiaOperating Temperature-40°C ~ 105°C	Number of Positions/Bay/Row	25	
Number of Rows2Pitch0.156" (3.96mm)Features-Mounting TypeThrough HoleTerminationWire WrapContact MaterialCopper, Nickel, Tin AlloyContact FinishGoldContact Finish Thickness-Contact Type-ColorGreenFlange FeatureFlush Mount, Top Opening, Unthreaded, 0.128" (3.25mm) DiaOperating Temperature-40°C ~ 105°C	Number of Positions	50	
Pitch0.156" (3.96mm)Features-Mounting TypeThrough HoleTerminationWire WrapContact MaterialCopper, Nickel, Tin AlloyContact Finish Thickness-Contact Finish Thickness-Contact Type-ColorGreenFlange FeatureFlush Mount, Top Opening, Unthreaded, 0.128" (3.25mm) DiaOperating Temperature-40°C ~ 105°C	Card Thickness	0.062" (1.57mm)	
Features-Mounting TypeThrough HoleTerminationWire WrapContact MaterialCopper, Nickel, Tin AlloyContact FinishGoldContact Finish Thickness-Contact Type-ColorGreenFlange FeatureFlush Mount, Top Opening, Unthreaded, 0.128" (3.25mm) DiaOperating Temperature-40°C ~ 105°C	Number of Rows	2	
Mounting TypeThrough HoleTerminationWire WrapContact MaterialCopper, Nickel, Tin AlloyContact FinishGoldContact Finish Thickness-Contact Type-ColorGreenFlange FeatureFlush Mount, Top Opening, Unthreaded, 0.128" (3.25mm) DiaOperating Temperature-40°C ~ 105°C	Pitch	0.156" (3.96mm)	
TerminationWire WrapContact MaterialCopper, Nickel, Tin AlloyContact FinishGoldContact Finish Thickness-Contact Type-ColorGreenFlange FeatureFlush Mount, Top Opening, Unthreaded, 0.128" (3.25mm) DiaOperating Temperature-40°C ~ 105°C	Features	-	
Contact MaterialCopper, Nickel, Tin AlloyContact FinishGoldContact Finish Thickness-Contact Type-ColorGreenFlange FeatureFlush Mount, Top Opening, Unthreaded, 0.128" (3.25mm) DiaOperating Temperature-40°C ~ 105°C	Mounting Type	Through Hole	
Contact FinishGoldContact Finish Thickness-Contact Type-ColorGreenFlange FeatureFlush Mount, Top Opening, Unthreaded, 0.128" (3.25mm) DiaOperating Temperature-40°C ~ 105°C	Termination	Wire Wrap	
Contact Finish Thickness-Contact Type-ColorGreenFlange FeatureFlush Mount, Top Opening, Unthreaded, 0.128" (3.25mm) DiaOperating Temperature-40°C ~ 105°C	Contact Material	Copper, Nickel, Tin Alloy	
Contact Type-ColorGreenFlange FeatureFlush Mount, Top Opening, Unthreaded, 0.128" (3.25mm) DiaOperating Temperature-40°C ~ 105°C	Contact Finish	Gold	
ColorGreenFlange FeatureFlush Mount, Top Opening, Unthreaded, 0.128" (3.25mm) DiaOperating Temperature-40°C ~ 105°C	Contact Finish Thickness	-	
Flange FeatureFlush Mount, Top Opening, Unthreaded, 0.128" (3.25mm) DiaOperating Temperature-40°C ~ 105°C	Contact Type	-	
Operating Temperature $-40^{\circ}\text{C} \sim 105^{\circ}\text{C}$	Color	Green	
	Flange Feature	Flush Mount, Top Opening, Unthreaded, 0.128" (3.25mm) Dia	
Report errors?	Operating Temperature	-40° C ~ 105° C	
			Report errors?

307-050-542-202 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

DISCOVER

307-050-542-202 Payment Methods

307-050-542-202 Shipping Methods



If you have any question about 307-050-542-202, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com