

3073199 Information



For Reference Only

Part Number 3073199

Manufacturer Phoenix Contact

Category Connectors, Interconnects

Terminal Blocks - Din Rail, Channel

Description CONN TERM BLK FEED THRU 12-28AWG

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









3073199 Specific	ations
-------------------------	--------

Manufacturer Part Number 3073199 Manufacturer Phoenix Contact Category Connectors, Interconnects Package - Series CLIPLINE MSBV Type Feed Through Disconnect Type - Number of Positions 2 Number of Levels 1 Terminal - Width 5.2mm Termination Style Push In, Spring Current - IEC 24A Voltage - IEC 800V Current - UL 20A Voltage - UL 600V Wire Gauge or Range - AWG 12-28 AWG Wire Gauge or Range - mm² 0.08-4mm² Features - Color Orange		
Category Connectors, Interconnects Terminal Blocks - Din Rail, Channel Package - Series CLIPLINE MSBV Type Feed Through Disconnect Type - Number of Positions 2 Number of Levels 1 Terminal - Width 5.2mm Termination Style Push In, Spring Current - IEC 24A Voltage - IEC 800V Current - UL Voltage - UL Wire Gauge or Range - AWG Wire Gauge or Range - awG Cornent Color Cornege	Manufacturer Part Number	3073199
Package-SeriesCLIPLINE MSBVTypeFeed ThroughDisconnect Type-Number of Positions2Number of Levels1Terminal - Width5.2mmTermination StylePush In, SpringCurrent - IEC24AVoltage - IEC800VCurrent - UL20AVoltage - UL600VWire Gauge or Range - AWG12-28 AWGWire Gauge or Range - mm²0.08-4mm²Features-ColorOrange	Manufacturer	Phoenix Contact
Package - Series CLIPLINE MSBV Type Feed Through Disconnect Type - Number of Positions 2 Number of Levels 1 Terminal - Width 5.2mm Termination Style Push In, Spring Current - IEC 24A Voltage - IEC 800V Current - UL 20A Voltage - UL 600V Wire Gauge or Range - AWG 12-28 AWG Wire Gauge or Range - mm² 0.08-4mm² Features - Color Orange	Category	Connectors, Interconnects
SeriesCLIPLINE MSBVTypeFeed ThroughDisconnect Type-Number of Positions2Number of Levels1Terminal - Width5.2mmTermination StylePush In, SpringCurrent - IEC24AVoltage - IEC800VCurrent - UL20AVoltage - UL600VWire Gauge or Range - AWG12-28 AWGWire Gauge or Range - mm²0.08-4mm²Features-ColorOrange		Terminal Blocks - Din Rail, Channel
Type Feed Through Disconnect Type - Number of Positions 2 Number of Levels 1 Terminal - Width 5.2mm Termination Style Push In, Spring Current - IEC 24A Voltage - IEC 800V Current - UL 20A Voltage - UL 600V Wire Gauge or Range - AWG 12-28 AWG Wire Gauge or Range - mm² 0.08-4mm² Features - Color Orange	Package	-
Disconnect Type Number of Positions 2 Number of Levels 1 Terminal - Width 5.2mm Termination Style Push In, Spring Current - IEC 24A Voltage - IEC 800V Current - UL 20A Voltage - UL 600V Wire Gauge or Range - AWG Wire Gauge or Range - mm² Features Color Orange	Series	CLIPLINE MSBV
Number of Positions 2 Number of Levels 1 Terminal - Width 5.2mm Termination Style Push In, Spring Current - IEC 24A Voltage - IEC 800V Current - UL 20A Voltage - UL 600V Wire Gauge or Range - AWG 12-28 AWG Wire Gauge or Range - mm² 0.08-4mm² Features - Color Orange	Type	Feed Through
Number of Levels 1 Terminal - Width 5.2mm Termination Style Push In, Spring Current - IEC 24A Voltage - IEC 800V Current - UL 20A Voltage - UL 600V Wire Gauge or Range - AWG 12-28 AWG Wire Gauge or Range - mm² 0.08-4mm² Features - Color Orange	Disconnect Type	-
Terminal - Width Termination Style Push In, Spring Current - IEC 24A Voltage - IEC 800V Current - UL 20A Voltage - UL 600V Wire Gauge or Range - AWG Wire Gauge or Range - mm² Features - Color Orange	Number of Positions	2
Termination Style Current - IEC 24A Voltage - IEC 800V Current - UL 20A Voltage - UL 600V Wire Gauge or Range - AWG Wire Gauge or Range - mm² Features - Color Orange	Number of Levels	1
Current - IEC 24A Voltage - IEC 800V Current - UL 20A Voltage - UL 600V Wire Gauge or Range - AWG 12-28 AWG Wire Gauge or Range - mm² 0.08-4mm² Features - Color Orange	Terminal - Width	5.2mm
Voltage - IEC800VCurrent - UL20AVoltage - UL600VWire Gauge or Range - AWG12-28 AWGWire Gauge or Range - mm²0.08-4mm²Features-ColorOrange	Termination Style	Push In, Spring
Current - UL 20A Voltage - UL 600V Wire Gauge or Range - AWG 12-28 AWG Wire Gauge or Range - mm² 0.08-4mm² Features - Color Orange	Current - IEC	24A
Voltage - UL Wire Gauge or Range - AWG Wire Gauge or Range - mm² O.08-4mm² Features Color Orange	Voltage - IEC	800V
Wire Gauge or Range - AWG Wire Gauge or Range - mm² O.08-4mm² Features Color Orange	Current - UL	20A
Wire Gauge or Range - mm² Features Color Orange	Voltage - UL	600V
Features - Color Orange	Wire Gauge or Range - AWG	12-28 AWG
Color Orange	Wire Gauge or Range - mm ²	0.08-4mm ²
	Features	-
Report errors?	Color	Orange
		Report errors?

3073199 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

3073199 Payment Methods



















3073199 Shipping Methods













If you have any question about 3073199, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com