

## 309NPC50K

### **309NPC50K Information**

Owned and the second	Part Number Manufacturer Category Description Package	309NPC50K Honeywell Sensing and Productivity Solutions Potentiometers, Variable Resistors Rotary Potentiometers, Rheostats POT 50K OHM 1W CERMET LINEAR - For the pricing/inventory/lead time, please contact	
For Reference Only		us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



## **309NPC50K Specifications**

ManufacturerHoneywell Sensing and Productivity SolutionsCategoryPotentiometers, Variable ResistorsRotary Potentiometers, RheostatsPackage-Series309NPCTaperLinearResistance (Ohms)50kTolerance±10%Number of Gangs1Built in SwitchNonePower (Watts)1WTomperature Coefficient-Number of Turns1Rotation295°Adjustment TypeSide AdjustmentResistive MaterialCermetTermination StyleSlottedActuator Length0.750" (19.05mm)Actuator Diameter0.125" (3.18mm)Bushing Thread1/4-32		
Category     Potentiometers, Variable Resistors       Rotary Potentiometers, Rheostats       Package     -       Series     309NPC       Taper     Linear       Resistance (Ohms)     50k       Tolerance     ±10%       Number of Gangs     1       Built in Switch     None       Power (Watts)     1W       Tomperature Coefficient     -       Number of Turns     1       Rotation     295°       Adjustment Type     Side Adjustment       Resistive Material     Cermet       Actuator Type     Slotted       Actuator Type     Slotted       Actuator Diameter     0.125" (3.18mm)       Bushing Thread     1/4-32       Mounting Type     Banel Mount	Manufacturer Part Number	309NPC50K
Rotary Potentiometers, RheostatsPackage-Series309NPCTaperLinearResistance (Ohms)50kTolerance±10%Number of Gangs1Built in SwitchNonePower (Watts)1%Rongerature Coefficient-Number of Turns10Rotation295°Adjustment TypeSole AdjustmentResistive MaterialCermetResistive MaterialSoltedActuator TypeSoltedActuator Length0.750° (19.5mm)Actuator Diameter1.25° (3.18mm)Bushing Thread1.4.32Mounting TypePael MountBushing Type	Manufacturer	Honeywell Sensing and Productivity Solutions
Package-Series309NPCTaperLinearResistance (Ohms)50kTolerance±10%Number of Gangs1Built in SwitchNonePower (Watts)1WTemperature Coefficient-Number of Turns1Rotation295°Adjustment TypeSide AdjustmentResistive MaterialCermetTermination StyleSlottedActuator Length0.750" (19.05mm)Actuator Diameter0.125" (3.18mm)Bushing Thread14-32Mounting TypePanel MountMounting TypePanel Mount	Category	Potentiometers, Variable Resistors
Series309NPCTaperLinearResistance (Ohms)50kTolerance±10%Number of Gangs1Built in SwitchNonePower (Watts)1WTemperature Coefficient-Number of Turns1Rotation295°Adjustment TypeSide AdjustmentResistive MaterialCermetTermination StyleSlottedActuator TypeSlottedActuator Length0.750° (19.05mm)Actuator Diameter0.125° (3.18mm)Bushing Thread14-32Mounting TypePanel MountBushing ThreadPanel Mount		Rotary Potentiometers, Rheostats
TaperLinearResistance (Ohms)50kTolerance±10%Number of Gangs1Built in SwitchNonePower (Watts)1WTemperature Coefficient-Number of Turns1Rotation295°Adjustment TypeSide AdjustmentResistive MaterialCermetActuator TypeSlottedActuator Length.50tredActuator Length.750° (19.05mm)Actuator Diameter.14-32Bushing ThreadMounting TypeMounting TypeShel MountMounting Type.14-32	Package	-
AResistance (Ohms)50kTolerance±10%Number of Gangs1Built in SwitchNonePower (Watts)1WTemperature Coefficient-Number of Turns1Rotation295°Adjustment TypeSide AdjustmentResistive MaterialCermetTermination StyleSlottedActuator TypeSlottedActuator Diameter0.125" (3.18mm)Bushing ThreadHael MountMounting TypePanel Mount	Series	309NPC
Tolerance±10%Number of Gangs1Built in SwitchNonePower (Watts)1WTemperature Coefficient-Number of Turns1Rotation295°Adjustment TypeSide AdjustmentResistive MaterialCermetTermination StyleSlottedActuator TypeSlottedActuator Diameter0.125" (3.18mm)Bushing ThreadHallMounting TypePanel Mount	Taper	Linear
Number of Gangs1Built in SwitchNonePower (Watts)IWTemperature Coefficient-Number of Turns1Rotation295°Adjustment TypeSide AdjustmentResistive MaterialCermetTermination StylePC PinsActuator TypeSlottedActuator Length0.750° (19.05mm)Actuator Diameter0.125° (3.18mm)Bushing ThreadPanel Mount	Resistance (Ohms)	50k
Built in SwitchNoneBuilt in SwitchIWPower (Watts)ITemperature Coefficient-Number of Turns1Rotation295°Adjustment TypeSide AdjustmentResistive MaterialCermetTermination StyleSlottedActuator TypeSlottedActuator Diameter0.125" (3.18mm)Bushing ThreadI/4-32Mounting TypePanel Mount	Tolerance	$\pm 10\%$
Power (Watts)IWPower (Watts)-Temperature Coefficient-Number of Turns1Rotation295°Adjustment TypeSide AdjustmentResistive MaterialCermetTermination StylePC PinsActuator TypeSlottedActuator Length0.750" (19.05mm)Actuator Diameter0.125" (3.18mm)Bushing ThreadPanel MountiMounting TypePanel Mount	Number of Gangs	1
Temperature Coefficient-Number of Turns1Rotation295°Adjustment TypeSide AdjustmentResistive MaterialCermetTermination StyleSlottedActuator TypeSlottedActuator Length0.750" (19.05mm)Actuator Diameter0.125" (3.18mm)Bushing Thread1/4-32Mounting TypePanel Mount	Built in Switch	None
Number of Turns1Rotation295°Adjustment TypeSide AdjustmentResistive MaterialCermetTermination StylePC PinsActuator TypeSlottedActuator Length0.750" (19.05mm)Actuator Diameter0.125" (3.18mm)Bushing Thread1/4-32Mounting TypePanel Mount	Power (Watts)	1W
Rotation295°Adjustment TypeSide AdjustmentResistive MaterialCermetTermination StylePC PinsActuator TypeSlottedActuator Length0.750" (19.05mm)Actuator Diameter0.125" (3.18mm)Bushing Thread1/4-32Mounting TypePanel Mount	Temperature Coefficient	-
Adjustment TypeSide AdjustmentResistive MaterialCermetTermination StylePC PinsActuator TypeSlottedActuator Length0.750" (19.05mm)Actuator Diameter0.125" (3.18mm)Bushing Thread1/4-32Mounting TypePanel Mount	Number of Turns	1
Resistive MaterialCermetTermination StylePC PinsActuator TypeSlottedActuator Length0.750" (19.05mm)Actuator Diameter0.125" (3.18mm)Bushing Thread1/4-32Mounting TypePanel Mount	Rotation	295°
Termination StylePC PinsActuator TypeSlottedActuator Length0.750" (19.05mm)Actuator Diameter0.125" (3.18mm)Bushing Thread1/4-32Mounting TypePanel Mount	Adjustment Type	Side Adjustment
Actuator TypeSlottedActuator Length0.750" (19.05mm)Actuator Diameter0.125" (3.18mm)Bushing Thread1/4-32Mounting TypePanel Mount	Resistive Material	Cermet
Actuator Length0.750" (19.05mm)Actuator Diameter0.125" (3.18mm)Bushing Thread1/4-32Mounting TypePanel Mount	Termination Style	PC Pins
Actuator Diameter0.125" (3.18mm)Bushing Thread1/4-32Mounting TypePanel Mount	Actuator Type	Slotted
Bushing Thread 1/4-32   Mounting Type Panel Mount	Actuator Length	0.750" (19.05mm)
Mounting Type Panel Mount	Actuator Diameter	0.125" (3.18mm)
	Bushing Thread	1/4-32
Report errors?	Mounting Type	Panel Mount
		Report errors?

#### **309NPC50K Guarantees**



Quality Guarantees

We provide 90 days warranty. \* If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

# SERVICE GUARANTEE

#### **Service Guarantees**

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.



If you have any question about 309NPC50K, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com