

#### 310-83-127-01-666101 Information



For Reference Only

**Part Number** 310-83-127-01-666101

Manufacturer Preci-Dip

**Category** Connectors, Interconnects

Rectangular Connectors - Headers, Receptacles,

Female Sockets

**Description** PCB CONN SOLDER TAIL

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# 310-83-127-01-666101 Specifications

Manufacturer Part Number         310-83-127-01-666101           Manufacturer         Preci-Dip           Category         Connectors, Interconnects           Rectangular Connectors - Headers, Receptacles, Female Sockets           Package         -           Series         310           Connector Type         Socket           Contact Type         Female Socket           Style         Board to Board           Number of Positions         27           Number of Positions Loaded         All           Pitch - Mating         0.100" (2.54mm)           Number of Rows         1           Row Spacing - Mating         -           Mounting Type         Through Hole           Termination         Press-Fit, Solder           Fastening Type         Push-Pull           Contact Finish - Mating         Gold           Contact Finish Thickness - Mating         29.5µin (0.75µm)           Insulation Color         Black           Insulation Height         0.165" (4.20mm)           Contact Length - Post         0.122" (3.10mm)           Operating Temperature         -55°C ~ 125°C           Material Elemmobility Pating         Ul 94 V.O					
Category         Connectors, Interconnects           Package         -           Series         310           Connector Type         Socket           Contact Type         Female Socket           Style         Board to Board           Number of Positions         27           Number of Positions Loaded         All           Pitch - Mating         0.100" (2.54mm)           Number of Rows         1           Row Spacing - Mating         -           Mounting Type         Through Hole           Termination         Press-Fit, Solder           Fastening Type         Push-Pull           Contact Finish - Mating         Gold           Contact Finish Thickness - Mating         29.5µin (0.75µm)           Insulation Color         Black           Insulation Height         0.165" (4.20mm)           Contact Length - Post         0.122" (3.10mm)           Operating Temperature         -55°C ~ 125°C	Manufacturer Part Number	310-83-127-01-666101			
Rectangular Connectors - Headers, Receptacles, Female Sockets  Package - 310  Connector Type Socket  Contact Type Female Socket  Style Board to Board  Number of Positions 27  Number of Positions Loaded All  Pitch - Mating 0.100" (2.54mm)  Number of Rows 1  Row Spacing - Mating - Through Hole  Termination Press-Fit, Solder  Fastening Type Push-Pull  Contact Finish - Mating Gold  Contact Finish Thickness - Mating 29.5µin (0.75µm)  Insulation Color Black  Insulation Height 0.165" (4.20mm)  Contact Length - Post 0.122" (3.10mm)  Operating Temperature - 55°C ~ 125°C	Manufacturer	Preci-Dip			
Package         -           Series         310           Connector Type         Socket           Contact Type         Female Socket           Style         Board to Board           Number of Positions         27           Number of Positions Loaded         All           Pitch - Mating         0.100" (2.54mm)           Number of Rows         1           Row Spacing - Mating         -           Mounting Type         Through Hole           Termination         Press-Fit, Solder           Fastening Type         Push-Pull           Contact Finish - Mating         Gold           Contact Finish Thickness - Mating         29.5µin (0.75µm)           Insulation Color         Black           Insulation Height         0.165" (4.20mm)           Contact Length - Post         0.122" (3.10mm)           Operating Temperature         -55°C ~ 125°C	Category	Connectors, Interconnects			
Series         310           Connector Type         Socket           Contact Type         Female Socket           Style         Board to Board           Number of Positions         27           Number of Positions Loaded         All           Pitch - Mating         0.100" (2.54mm)           Number of Rows         1           Row Spacing - Mating         -           Mounting Type         Through Hole           Termination         Press-Fit, Solder           Fastening Type         Push-Pull           Contact Finish - Mating         Gold           Contact Finish Thickness - Mating         29.5μin (0.75μm)           Insulation Color         Black           Insulation Height         0.165" (4.20mm)           Contact Length - Post         0.122" (3.10mm)           Operating Temperature         -55°C ~ 125°C		Rectangular Connectors - Headers, Receptacles, Female Sockets			
Connector TypeSocketContact TypeFemale SocketStyleBoard to BoardNumber of Positions27Number of Positions LoadedAllPitch - Mating0.100" (2.54mm)Number of Rows1Row Spacing - Mating-Mounting TypeThrough HoleTerminationPress-Fit, SolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating29.5µin (0.75µm)Insulation ColorBlackInsulation Height0.165" (4.20mm)Contact Length - Post0.122" (3.10mm)Operating Temperature-55°C ~ 125°C	Package	-			
Contact TypeFemale SocketStyleBoard to BoardNumber of Positions27Number of Positions LoadedAllPitch - Mating0.100" (2.54mm)Number of Rows1Row Spacing - Mating-Mounting TypeThrough HoleTerminationPress-Fit, SolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating29.5μin (0.75μm)Insulation ColorBlackInsulation Height0.165" (4.20mm)Contact Length - Post0.122" (3.10mm)Operating Temperature-55°C ~ 125°C	Series	310			
StyleBoard to BoardNumber of Positions27Number of Positions LoadedAllPitch - Mating0.100" (2.54mm)Number of Rows1Row Spacing - Mating-Mounting TypeThrough HoleTerminationPress-Fit, SolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating29.5μin (0.75μm)Insulation ColorBlackInsulation Height0.165" (4.20mm)Contact Length - Post0.122" (3.10mm)Operating Temperature-55°C ~ 125°C	Connector Type	Socket			
Number of Positions27Number of Positions LoadedAllPitch - Mating0.100" (2.54mm)Number of Rows1Row Spacing - Mating-Mounting TypeThrough HoleTerminationPress-Fit, SolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating29.5μin (0.75μm)Insulation ColorBlackInsulation Height0.165" (4.20mm)Contact Length - Post0.122" (3.10mm)Operating Temperature-55°C ~ 125°C	Contact Type	Female Socket			
Number of Positions LoadedAllPitch - Mating0.100" (2.54mm)Number of Rows1Row Spacing - Mating-Mounting TypeThrough HoleTerminationPress-Fit, SolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating29.5μin (0.75μm)Insulation ColorBlackInsulation Height0.165" (4.20mm)Contact Length - Post0.122" (3.10mm)Operating Temperature-55°C ~ 125°C	Style	Board to Board			
Pitch - Mating0.100" (2.54mm)Number of Rows1Row Spacing - Mating-Mounting TypeThrough HoleTerminationPress-Fit, SolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating29.5μin (0.75μm)Insulation ColorBlackInsulation Height0.165" (4.20mm)Contact Length - Post0.122" (3.10mm)Operating Temperature-55°C ~ 125°C	Number of Positions	27			
Number of Rows1Row Spacing - Mating-Mounting TypeThrough HoleTerminationPress-Fit, SolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating29.5μin (0.75μm)Insulation ColorBlackInsulation Height0.165" (4.20mm)Contact Length - Post0.122" (3.10mm)Operating Temperature-55°C ~ 125°C	Number of Positions Loaded	All			
Row Spacing - Mating-Mounting TypeThrough HoleTerminationPress-Fit, SolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating29.5μin (0.75μm)Insulation ColorBlackInsulation Height0.165" (4.20mm)Contact Length - Post0.122" (3.10mm)Operating Temperature-55°C ~ 125°C	Pitch - Mating	0.100" (2.54mm)			
Mounting TypeThrough HoleTerminationPress-Fit, SolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating29.5μin (0.75μm)Insulation ColorBlackInsulation Height0.165" (4.20mm)Contact Length - Post0.122" (3.10mm)Operating Temperature-55°C ~ 125°C	Number of Rows	1			
Termination Press-Fit, Solder  Fastening Type Push-Pull  Contact Finish - Mating Gold  Contact Finish Thickness - Mating 29.5 $\mu$ in (0.75 $\mu$ m)  Insulation Color Black  Insulation Height 0.165" (4.20mm)  Contact Length - Post 0.122" (3.10mm)  Operating Temperature -55°C ~ 125°C	Row Spacing - Mating	-			
Fastening Type Push-Pull  Contact Finish - Mating Gold  Contact Finish Thickness - Mating 29.5 $\mu$ in (0.75 $\mu$ m)  Insulation Color Black  Insulation Height 0.165" (4.20mm)  Contact Length - Post 0.122" (3.10mm)  Operating Temperature -55°C ~ 125°C	Mounting Type	Through Hole			
Contact Finish - Mating Gold  Contact Finish Thickness - Mating 29.5 $\mu$ in (0.75 $\mu$ m)  Insulation Color Black  Insulation Height 0.165" (4.20mm)  Contact Length - Post 0.122" (3.10mm)  Operating Temperature -55°C ~ 125°C	Termination	Press-Fit, Solder			
Contact Finish Thickness - Mating $29.5\mu in (0.75\mu m)$ Insulation Color Black  Insulation Height $0.165'' (4.20mm)$ Contact Length - Post $0.122'' (3.10mm)$ Operating Temperature $-55^{\circ}\text{C} \sim 125^{\circ}\text{C}$	Fastening Type	Push-Pull			
Insulation ColorBlackInsulation Height $0.165"$ (4.20mm)Contact Length - Post $0.122"$ (3.10mm)Operating Temperature $-55^{\circ}$ C ~ $125^{\circ}$ C	Contact Finish - Mating	Gold			
Insulation Height $0.165"$ (4.20mm)Contact Length - Post $0.122"$ (3.10mm)Operating Temperature $-55^{\circ}\text{C} \sim 125^{\circ}\text{C}$	Contact Finish Thickness - Mating	29.5μin (0.75μm)			
Contact Length - Post $0.122" (3.10 \text{mm})$ Operating Temperature $-55^{\circ}\text{C} \sim 125^{\circ}\text{C}$	Insulation Color	Black			
Operating Temperature $-55^{\circ}\text{C} \sim 125^{\circ}\text{C}$	Insulation Height	0.165" (4.20mm)			
	Contact Length - Post	0.122" (3.10mm)			
Material Flammability Rating LII 94 V-0	Operating Temperature	-55°C ~ 125°C			
Waterial Flammatority Nating OL94 V-0	Material Flammability Rating	UL94 V-0			

Contact Finish - Post	Tin		
Mated Stacking Heights	-		
Ingress Protection	-		
Features	-		
			Report errors?

### 310-83-127-01-666101 Guarantees



### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

# 310-83-127-01-666101 Payment Methods



















### 310-83-127-01-666101 Shipping Methods













If you have any question about 310-83-127-01-666101, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com