



## **3100-15Q19999CL Information**

Heisener.com

Part Number 3100-15Q19999CL

Manufacturer TE Connectivity Potter & Brumfield Relays

Category

Power Relays, Over 2 Amps

**Description** RELAY CONTACTOR SPST 25A 24V

**Package** 

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# 3100-15Q19999CL Specifications

Manufacturer Part Number         3100-15Q19999CL           Manufacturer         TE Connectivity Potter & Brumfield Relays           Category         Relays           Power Relays, Over 2 Amps           Package         -           Series         3100, Products Unlimited           Relay Type         Contactor           Coil Type         Non Latching           Coil Current         -           Coil Voltage         24VAC           Contact Form         SPST-NO (1 Form X)           Contact Rating (Current)         25A           Switching Voltage         600VAC - Max           Turn On Voltage (Max)         18 VAC           Turn Off Voltage (Min)         6 VAC           Operate Time         -
Category         Relays           Power Relays, Over 2 Amps           Package         -           Series         3100, Products Unlimited           Relay Type         Contactor           Coil Type         Non Latching           Coil Current         -           Coil Voltage         24VAC           Contact Form         SPST-NO (1 Form X)           Contact Rating (Current)         25A           Switching Voltage         600VAC - Max           Turn On Voltage (Max)         18 VAC           Turn Off Voltage (Min)         6 VAC           Operate Time         -
Package - Series 3100, Products Unlimited Relay Type Contactor Coil Type Non Latching Coil Current - Coil Voltage 24VAC Contact Form SPST-NO (1 Form X) Contact Rating (Current) 25A Switching Voltage 600VAC - Max Turn On Voltage (Max) 18 VAC Operate Time -
Package - 3100, Products Unlimited  Relay Type Contactor  Coil Type Non Latching  Coil Current - Coil Voltage 24VAC  Contact Form SPST-NO (1 Form X)  Contact Rating (Current) 25A  Switching Voltage 600VAC - Max  Turn On Voltage (Max) 18 VAC  Operate Time - Contact Form Facility of VAC  Operate Time - Contact Summer
Series 3100, Products Unlimited Relay Type Contactor Coil Type Non Latching Coil Current - Coil Voltage 24VAC Contact Form SPST-NO (1 Form X) Contact Rating (Current) 25A Switching Voltage 600VAC - Max Turn On Voltage (Max) 18 VAC Turn Off Voltage (Min) 6 VAC Operate Time -
Relay Type Contactor  Coil Type Non Latching  Coil Current - Coil Voltage 24VAC  Contact Form SPST-NO (1 Form X)  Contact Rating (Current) 25A  Switching Voltage 600VAC - Max  Turn On Voltage (Max) 18 VAC  Turn Off Voltage (Min) 6 VAC  Operate Time -
Coil Type Non Latching  Coil Current - Coil Voltage 24VAC  Contact Form SPST-NO (1 Form X)  Contact Rating (Current) 25A  Switching Voltage 600VAC - Max  Turn On Voltage (Max) 18 VAC  Turn Off Voltage (Min) 6 VAC  Operate Time -
Coil Current - Coil Voltage 24VAC  Contact Form SPST-NO (1 Form X)  Contact Rating (Current) 25A Switching Voltage 600VAC - Max  Turn On Voltage (Max) 18 VAC  Turn Off Voltage (Min) 6 VAC  Operate Time -
Coil Voltage 24VAC  Contact Form SPST-NO (1 Form X)  Contact Rating (Current) 25A  Switching Voltage 600VAC - Max  Turn On Voltage (Max) 18 VAC  Turn Off Voltage (Min) 6 VAC  Operate Time -
Contact Form SPST-NO (1 Form X)  Contact Rating (Current) 25A  Switching Voltage 600VAC - Max  Turn On Voltage (Max) 18 VAC  Turn Off Voltage (Min) 6 VAC  Operate Time -
Contact Rating (Current)  Switching Voltage  600VAC - Max  Turn On Voltage (Max)  18 VAC  Turn Off Voltage (Min)  6 VAC  Operate Time  -
Switching Voltage 600VAC - Max  Turn On Voltage (Max) 18 VAC  Turn Off Voltage (Min) 6 VAC  Operate Time -
Turn On Voltage (Max)  18 VAC  Turn Off Voltage (Min)  6 VAC  Operate Time  -
Turn Off Voltage (Min) 6 VAC Operate Time -
Operate Time -
Release Time -
Features Insulation - Class B
Mounting Type Chassis Mount
Termination Style Screw Terminal, Quick Connect - 0.250" (6.3mm)
Report errors?

### **3100-15Q19999CL Guarantees**



### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### 3100-15Q19999CL Payment Methods



















## 3100-15Q19999CL Shipping Methods













If you have any question about 3100-15Q19999CL, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com