

3100-15T2999C Information

Heisener.com

Part Number 3100-15T2999C

Manufacturer TE Connectivity Potter & Brumfield Relays

Category

Power Relays, Over 2 Amps

Description RELAY CONTACTOR SPST 30A 120V

Package

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









3100-15T2999C Specifications

Manufacturer Part Number 3100-15T2999C Manufacturer TE Connectivity Potter & Brumfield Relays Category Relays Power Relays, Over 2 Amps Package - Series 3100, Products Unlimited Relay Type Contactor Coil Type Non Latching Coil Current - Coil Voltage 120VAC Contact Form SPST-NO (1 Form X) Contact Rating (Current) 30A Switching Voltage 600VAC - Max Turn On Voltage (Max) 88 VAC Turn Off Voltage (Min) 20 VAC Operate Time - Release Time - Features Insulation - Class B Mounting Type Chassis Mount Termination Style Screw Terminal, Quick Connect - 0.250" (6.3mm)		
CategoryRelaysPackage-Series3100, Products UnlimitedRelay TypeContactorCoil TypeNon LatchingCoil Current-Coil Voltage120VACContact FormSPST-NO (1 Form X)Contact Rating (Current)30ASwitching Voltage600VAC - MaxTurn On Voltage (Max)88 VACTurn Off Voltage (Min)20 VACOperate Time-Release Time-FeaturesInsulation - Class BMounting TypeChassis MountTermination StyleScrew Terminal, Quick Connect - 0.250" (6.3mm)	Manufacturer Part Number	3100-15T2999C
Package - Series 3100, Products Unlimited Relay Type Contactor Coil Type Non Latching Coil Current - Coil Voltage 120VAC Contact Form SPST-NO (1 Form X) Contact Rating (Current) 30A Switching Voltage 600VAC - Max Turn On Voltage (Max) 88 VAC Turn Off Voltage (Min) 20 VAC Operate Time - Release Time - Features Insulation - Class B Mounting Type Chassis Mount Termination Style Screw Terminal, Quick Connect - 0.250" (6.3mm)	Manufacturer	TE Connectivity Potter & Brumfield Relays
Package - Series 3100, Products Unlimited Relay Type Contactor Coil Type Non Latching Coil Current - Coil Voltage 120VAC Contact Form SPST-NO (1 Form X) Contact Rating (Current) 30A Switching Voltage 600VAC - Max Turn On Voltage (Max) 88 VAC Turn Off Voltage (Min) 20 VAC Operate Time - Release Time - Features Insulation - Class B Mounting Type Chassis Mount Termination Style Screw Terminal, Quick Connect - 0.250" (6.3mm)	Category	Relays
Series 3100, Products Unlimited Relay Type Contactor Coil Type Non Latching Coil Current - Coil Voltage 120VAC Contact Form SPST-NO (1 Form X) Contact Rating (Current) 30A Switching Voltage 600VAC - Max Turn On Voltage (Max) 88 VAC Turn Off Voltage (Min) 20 VAC Operate Time - Release Time - Features Insulation - Class B Mounting Type Chassis Mount Termination Style Screw Terminal, Quick Connect - 0.250" (6.3mm)		Power Relays, Over 2 Amps
Relay TypeContactorCoil TypeNon LatchingCoil Current-Coil Voltage120VACContact FormSPST-NO (1 Form X)Contact Rating (Current)30ASwitching Voltage600VAC - MaxTurn On Voltage (Max)88 VACTurn Off Voltage (Min)20 VACOperate Time-Release Time-FeaturesInsulation - Class BMounting TypeChassis MountTermination StyleScrew Terminal, Quick Connect - 0.250" (6.3mm)	Package	-
Coil Type Non Latching Coil Current - Coil Voltage 120VAC Contact Form SPST-NO (1 Form X) Contact Rating (Current) 30A Switching Voltage 600VAC - Max Turn On Voltage (Max) 88 VAC Turn Off Voltage (Min) 20 VAC Operate Time - Release Time - Features Insulation - Class B Mounting Type Chassis Mount Termination Style SPST-NO (1 Form X) Contact Rating (Current) 30A SPST-NO (1 Form X) SPST-NO (1	Series	3100, Products Unlimited
Coil Current Coil Voltage 120VAC Contact Form SPST-NO (1 Form X) Contact Rating (Current) 30A Switching Voltage 600VAC - Max Turn On Voltage (Max) 88 VAC Turn Off Voltage (Min) 20 VAC Operate Time - Release Time - Features Insulation - Class B Mounting Type Chassis Mount Termination Style SPST-NO (1 Form X) 20 VAC 600VAC - Max 88 VAC Turn Off Voltage (Min) 20 VAC Coperate Time - Seatures Sea	Relay Type	Contactor
Coil Voltage 120VAC Contact Form SPST-NO (1 Form X) Contact Rating (Current) 30A Switching Voltage 600VAC - Max Turn On Voltage (Max) 88 VAC Turn Off Voltage (Min) 20 VAC Operate Time - Release Time - Release Time - Features Insulation - Class B Mounting Type Chassis Mount Termination Style SPST-NO (1 Form X) SPST-N	Coil Type	Non Latching
Contact Form SPST-NO (1 Form X) Contact Rating (Current) 30A Switching Voltage 600VAC - Max Turn On Voltage (Max) 88 VAC Turn Off Voltage (Min) 20 VAC Operate Time - Release Time - Features Insulation - Class B Mounting Type Chassis Mount Termination Style Screw Terminal, Quick Connect - 0.250" (6.3mm)	Coil Current	-
Contact Rating (Current) Switching Voltage 600VAC - Max Turn On Voltage (Max) 88 VAC Turn Off Voltage (Min) 20 VAC Operate Time - Release Time - Features Insulation - Class B Mounting Type Chassis Mount Termination Style Screw Terminal, Quick Connect - 0.250" (6.3mm)	Coil Voltage	120VAC
Switching Voltage 600VAC - Max Turn On Voltage (Max) 88 VAC Turn Off Voltage (Min) 20 VAC Operate Time - Release Time - Features Insulation - Class B Mounting Type Chassis Mount Termination Style Screw Terminal, Quick Connect - 0.250" (6.3mm)	Contact Form	SPST-NO (1 Form X)
Turn On Voltage (Max) 88 VAC Turn Off Voltage (Min) 20 VAC Operate Time - Release Time - Features Insulation - Class B Mounting Type Chassis Mount Termination Style Screw Terminal, Quick Connect - 0.250" (6.3mm)	Contact Rating (Current)	30A
Turn Off Voltage (Min) Operate Time - Release Time - Features Insulation - Class B Mounting Type Chassis Mount Termination Style Screw Terminal, Quick Connect - 0.250" (6.3mm)	Switching Voltage	600VAC - Max
Operate Time - Release Time - Features Insulation - Class B Mounting Type Chassis Mount Termination Style Screw Terminal, Quick Connect - 0.250" (6.3mm)	Turn On Voltage (Max)	88 VAC
Release Time - Features Insulation - Class B Mounting Type Chassis Mount Termination Style Screw Terminal, Quick Connect - 0.250" (6.3mm)	Turn Off Voltage (Min)	20 VAC
Features Insulation - Class B Mounting Type Chassis Mount Termination Style Screw Terminal, Quick Connect - 0.250" (6.3mm)	Operate Time	-
Mounting Type Chassis Mount Termination Style Screw Terminal, Quick Connect - 0.250" (6.3mm)	Release Time	-
Termination Style Screw Terminal, Quick Connect - 0.250" (6.3mm)	Features	Insulation - Class B
	Mounting Type	Chassis Mount
Report errors?	Termination Style	Screw Terminal, Quick Connect - 0.250" (6.3mm)
Report thous.		Report errors?

3100-15T2999C Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

3100-15T2999C Payment Methods



















3100-15T2999C Shipping Methods













If you have any question about 3100-15T2999C, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com