



3100-20U18999CL Information



For Reference Only

Part Number 3100-20U18999CL

Manufacturer TE Connectivity Potter & Brumfield Relays

Category Relays

Power Relays, Over 2 Amps

Description RELAY CONTACTOR DPST 40A 240V

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









3100-20U18999CL Specifications

Manufacturer Part Number 3100-20U18999CL Manufacturer TE Connectivity Potter & Brumfield Relays Category Relays Power Relays, Over 2 Amps Package - Series 3100, Products Unlimited Relay Type Contactor Coil Type Non Latching Coil Current - Coil Voltage 240VAC Contact Form DPST-NO (2 Form X) Contact Rating (Current) 40A Switching Voltage 600VAC - Max Turn On Voltage (Max) 177 VAC Turn Off Voltage (Min) 40 VAC Operate Time - Release Time - Features Insulation - Class B Mounting Type Chassis Mount Termination Style Box Lug Onick Connect - 0.250" (6.3 mm)		
Category Relays Power Relays, Over 2 Amps Package - Series 3100, Products Unlimited Relay Type Contactor Coil Type Non Latching Coil Current - Coil Voltage 240 VAC Contact Form DPST-NO (2 Form X) Contact Rating (Current) 40A Switching Voltage 600 VAC - Max Turn On Voltage (Max) 177 VAC Turn Off Voltage (Min) 40 VAC Operate Time - Release Time - Features Insulation - Class B Mounting Type Chassis Mount	Manufacturer Part Number	3100-20U18999CL
Package - Series 3100, Products Unlimited Relay Type Contactor Coil Type Non Latching Coil Current - Coil Voltage 240VAC Contact Form DPST-NO (2 Form X) Contact Rating (Current) 40A Switching Voltage 600VAC - Max Turn On Voltage (Max) 177 VAC Turn Off Voltage (Min) 40 VAC Operate Time - Release Time - Features Insulation - Class B Mounting Type Chassis Mount	Manufacturer	TE Connectivity Potter & Brumfield Relays
Package - Series 3100, Products Unlimited Relay Type Contactor Coil Type Non Latching Coil Current - Coil Voltage 240VAC Contact Form DPST-NO (2 Form X) Contact Rating (Current) 40A Switching Voltage 600VAC - Max Turn On Voltage (Max) 177 VAC Turn Off Voltage (Min) 40 VAC Operate Time - Release Time - Insulation - Class B Mounting Type Chassis Mount	Category	Relays
Series3100, Products UnlimitedRelay TypeContactorCoil TypeNon LatchingCoil Current-Coil Voltage240VACContact FormDPST-NO (2 Form X)Contact Rating (Current)40ASwitching Voltage600VAC - MaxTurn On Voltage (Max)177 VACTurn Off Voltage (Min)40 VACOperate Time-Release Time-FeaturesInsulation - Class BMounting TypeChassis Mount		Power Relays, Over 2 Amps
Relay TypeContactorCoil TypeNon LatchingCoil Current-Coil Voltage240VACContact FormDPST-NO (2 Form X)Contact Rating (Current)40ASwitching Voltage600VAC - MaxTurn On Voltage (Max)177 VACTurn Off Voltage (Min)40 VACOperate Time-Release Time-FeaturesInsulation - Class BMounting TypeChassis Mount	Package	-
Coil TypeNon LatchingCoil Current-Coil Voltage240VACContact FormDPST-NO (2 Form X)Contact Rating (Current)40ASwitching Voltage600VAC - MaxTurn On Voltage (Max)177 VACTurn Off Voltage (Min)40 VACOperate Time-Release Time-FeaturesInsulation - Class BMounting TypeChassis Mount	Series	3100, Products Unlimited
Coil Current Coil Voltage 240VAC Contact Form DPST-NO (2 Form X) Contact Rating (Current) 40A Switching Voltage 600VAC - Max Turn On Voltage (Max) 177 VAC Turn Off Voltage (Min) 40 VAC Operate Time - Release Time - Features Insulation - Class B Mounting Type Chassis Mount	Relay Type	Contactor
Coil Voltage240VACContact FormDPST-NO (2 Form X)Contact Rating (Current)40ASwitching Voltage600VAC - MaxTurn On Voltage (Max)177 VACTurn Off Voltage (Min)40 VACOperate Time-Release Time-FeaturesInsulation - Class BMounting TypeChassis Mount	Coil Type	Non Latching
Contact Form DPST-NO (2 Form X) Contact Rating (Current) 40A Switching Voltage 600VAC - Max Turn On Voltage (Max) 177 VAC Turn Off Voltage (Min) 40 VAC Operate Time - Release Time - Features Insulation - Class B Mounting Type Chassis Mount	Coil Current	-
Contact Rating (Current) Switching Voltage 600VAC - Max Turn On Voltage (Max) 177 VAC Turn Off Voltage (Min) 40 VAC Operate Time - Release Time - Features Insulation - Class B Mounting Type 40A	Coil Voltage	240VAC
Switching Voltage 600VAC - Max Turn On Voltage (Max) 177 VAC Turn Off Voltage (Min) 40 VAC Operate Time - Release Time - Features Insulation - Class B Mounting Type Chassis Mount	Contact Form	DPST-NO (2 Form X)
Turn On Voltage (Max) 177 VAC Turn Off Voltage (Min) 40 VAC Operate Time - Release Time - Features Insulation - Class B Mounting Type Chassis Mount	Contact Rating (Current)	40A
Turn Off Voltage (Min) 40 VAC Operate Time - Release Time - Features Insulation - Class B Mounting Type Chassis Mount	Switching Voltage	600VAC - Max
Operate Time	Turn On Voltage (Max)	177 VAC
Release Time - Features Insulation - Class B Mounting Type Chassis Mount	Turn Off Voltage (Min)	40 VAC
Features Insulation - Class B Mounting Type Chassis Mount	Operate Time	-
Mounting Type Chassis Mount	Release Time	-
	Features	Insulation - Class B
Termination Style Box Lug Quick Connect - 0.250" (6.3mm)	Mounting Type	Chassis Mount
Don Dag, Quick Connect 0.230 (0.51111)	Termination Style	Box Lug, Quick Connect - 0.250" (6.3mm)
Report errors?		Report errors?

3100-20U18999CL Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

3100-20U18999CL Payment Methods



















3100-20U18999CL Shipping Methods













If you have any question about 3100-20U18999CL, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com