



3100-30Q10999CG Information

Heisener.com

Part Number 3100-30Q10999CG

Manufacturer TE Connectivity Potter & Brumfield Relays

Category

Power Relays, Over 2 Amps

RELAY CONTACTOR 3PST 40A 24V **Description**

Package

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









3100-30Q10999CG Specifications

Manufacturer Part Number 3100-30Q10999CG Manufacturer TE Connectivity Potter & Brumfield Relays Category Relays Power Relays, Over 2 Amps Package - Series 3100, Products Unlimited Relay Type Contactor Coil Type Non Latching Coil Current - Coil Voltage 24VAC Contact Form 3PST-NO-DM (3 Form X) Contact Rating (Current) 40A Switching Voltage 600VAC - Max Turn On Voltage (Max) 18 VAC Turn Off Voltage (Min) 6 VAC Operate Time - Release Time - Features Insulation - Class B Mounting Type Chassis Mount		
Category Relays Power Relays, Over 2 Amps Package - Series 3100, Products Unlimited Relay Type Contactor Coil Type Non Latching Coil Current - Coil Voltage 24VAC Contact Form 3PST-NO-DM (3 Form X) Contact Rating (Current) 40A Switching Voltage 600VAC - Max Turn On Voltage (Max) 18 VAC Turn Off Voltage (Min) 6 VAC Operate Time - Release Time - Features Insulation - Class B	Manufacturer Part Number	3100-30Q10999CG
Package - Series 3100, Products Unlimited Relay Type Contactor Coil Type Non Latching Coil Current - Coil Voltage 24VAC Contact Form 3PST-NO-DM (3 Form X) Contact Rating (Current) 40A Switching Voltage 600VAC - Max Turn On Voltage (Max) 18 VAC Turn Off Voltage (Min) 6 VAC Operate Time - Release Time - Features Insulation - Class B	Manufacturer	TE Connectivity Potter & Brumfield Relays
Package - Series 3100, Products Unlimited Relay Type Contactor Coil Type Non Latching Coil Current - Coil Voltage 24VAC Contact Form 3PST-NO-DM (3 Form X) Contact Rating (Current) 40A Switching Voltage 600VAC - Max Turn On Voltage (Max) 18 VAC Turn Off Voltage (Min) 6 VAC Operate Time - Release Time - Features Insulation - Class B	Category	Relays
Series 3100, Products Unlimited Relay Type Contactor Coil Type Non Latching Coil Current - Coil Voltage 24VAC Contact Form 3PST-NO-DM (3 Form X) Contact Rating (Current) 40A Switching Voltage 600VAC - Max Turn On Voltage (Max) 18 VAC Turn Off Voltage (Min) 6 VAC Operate Time - Release Time - Features Insulation - Class B		Power Relays, Over 2 Amps
Relay TypeContactorCoil TypeNon LatchingCoil Current-Coil Voltage24VACContact Form3PST-NO-DM (3 Form X)Contact Rating (Current)40ASwitching Voltage600VAC - MaxTurn On Voltage (Max)18 VACTurn Off Voltage (Min)6 VACOperate Time-Release Time-FeaturesInsulation - Class B	Package	-
Coil TypeNon LatchingCoil Current-Coil Voltage24VACContact Form3PST-NO-DM (3 Form X)Contact Rating (Current)40ASwitching Voltage600VAC - MaxTurn On Voltage (Max)18 VACTurn Off Voltage (Min)6 VACOperate Time-Release Time-FeaturesInsulation - Class B	Series	3100, Products Unlimited
Coil Current Coil Voltage 24VAC Contact Form 3PST-NO-DM (3 Form X) Contact Rating (Current) 40A Switching Voltage 600VAC - Max Turn On Voltage (Max) 18 VAC Turn Off Voltage (Min) 6 VAC Operate Time - Release Time - Features Insulation - Class B	Relay Type	Contactor
Coil Voltage 24VAC Contact Form 3PST-NO-DM (3 Form X) Contact Rating (Current) 40A Switching Voltage 600VAC - Max Turn On Voltage (Max) 18 VAC Turn Off Voltage (Min) 6 VAC Operate Time - Release Time - Features Insulation - Class B	Coil Type	Non Latching
Contact Form 3PST-NO-DM (3 Form X) Contact Rating (Current) 40A Switching Voltage 600VAC - Max Turn On Voltage (Max) 18 VAC Turn Off Voltage (Min) 6 VAC Operate Time - Release Time - Features Insulation - Class B	Coil Current	-
Contact Rating (Current) Switching Voltage 600VAC - Max Turn On Voltage (Max) 18 VAC Turn Off Voltage (Min) 6 VAC Operate Time - Release Time - Features Insulation - Class B	Coil Voltage	24VAC
Switching Voltage 600VAC - Max Turn On Voltage (Max) 18 VAC Turn Off Voltage (Min) 6 VAC Operate Time - Release Time - Features Insulation - Class B	Contact Form	3PST-NO-DM (3 Form X)
Turn On Voltage (Max) 18 VAC Turn Off Voltage (Min) 6 VAC Operate Time - Release Time - Features Insulation - Class B	Contact Rating (Current)	40A
Turn Off Voltage (Min) 6 VAC Operate Time - Release Time - Features Insulation - Class B	Switching Voltage	600VAC - Max
Operate Time - Release Time - Insulation - Class B	Turn On Voltage (Max)	18 VAC
Release Time - Features Insulation - Class B	Turn Off Voltage (Min)	6 VAC
Features Insulation - Class B	Operate Time	-
	Release Time	-
Mounting Type Chassis Mount	Features	Insulation - Class B
	Mounting Type	Chassis Mount
Termination Style Box Lug, Quick Connect - 0.250" (6.3mm)	Termination Style	Box Lug, Quick Connect - 0.250" (6.3mm)
Report errors?		Report errors?

3100-30Q10999CG Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

3100-30Q10999CG Payment Methods





















3100-30Q10999CG Shipping Methods













If you have any question about 3100-30Q10999CG, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com