



3100-30Q9999CY Information

Heisener.com

Part Number 3100-30Q9999CY

Manufacturer TE Connectivity Potter & Brumfield Relays

Category

Power Relays, Over 2 Amps

Description RELAY CONTACTOR 3PST 30A 24V

Package

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









3100-30Q9999CY Specifications

| Manufacturer Part Number 3100-30Q9999CY Manufacturer TE Connectivity Potter & Brumfield Relays Category Relays Power Relays, Over 2 Amps Package - Series 3100, Products Unlimited Relay Type Contactor Coil Type Non Latching Coil Current - Coil Voltage 24VAC Contact Form 3PST-NO-DM (3 Form X) Contact Rating (Current) 30A Switching Voltage 600VAC - Max Turn On Voltage (Max) 18 VAC Turn Off Voltage (Min) 6 VAC Operate Time - Release Time - Features Insulation - Class B Mounting Type Chassis Mount Termination Style Screw Terminal, Quick Connect - 0.250" (6.3mm) | | |
|--|--------------------------|--|
| CategoryRelaysPower Relays, Over 2 AmpsPackage-Series3100, Products UnlimitedRelay TypeContactorCoil TypeNon LatchingCoil Current-Coil Voltage24VACContact Form3PST-NO-DM (3 Form X)Contact Rating (Current)30ASwitching Voltage600VAC - MaxTurn On Voltage (Max)18 VACTurn Off Voltage (Min)6 VACOperate Time-Release Time-FeaturesInsulation - Class BMounting TypeChassis MountTermination StyleScrew Terminal, Quick Connect - 0.250" (6.3mm) | Manufacturer Part Number | 3100-30Q9999CY |
| Package - Series 3100, Products Unlimited Relay Type Contactor Coil Type Non Latching Coil Current - Coil Voltage 24VAC Contact Form 3PST-NO-DM (3 Form X) Contact Rating (Current) 30A Switching Voltage 600VAC - Max Turn On Voltage (Max) 18 VAC Turn Off Voltage (Min) 6 VAC Operate Time - Release Time - Features Insulation - Class B Mounting Type Chassis Mount Termination Style Screw Terminal, Quick Connect - 0.250" (6.3mm) | Manufacturer | TE Connectivity Potter & Brumfield Relays |
| Package - Series 3100, Products Unlimited Relay Type Contactor Coil Type Non Latching Coil Current - Coil Voltage 24VAC Contact Form 3PST-NO-DM (3 Form X) Contact Rating (Current) 30A Switching Voltage 600VAC - Max Turn On Voltage (Max) 18 VAC Turn Off Voltage (Min) 6 VAC Operate Time - Release Time - Features Insulation - Class B Mounting Type Chassis Mount Termination Style Screw Terminal, Quick Connect - 0.250" (6.3mm) | Category | Relays |
| Series3100, Products UnlimitedRelay TypeContactorCoil TypeNon LatchingCoil Current-Coil Voltage24VACContact Form3PST-NO-DM (3 Form X)Contact Rating (Current)30ASwitching Voltage600VAC - MaxTurn On Voltage (Max)18 VACTurn Off Voltage (Min)6 VACOperate Time-Release Time-FeaturesInsulation - Class BMounting TypeChassis MountTermination StyleScrew Terminal, Quick Connect - 0.250" (6.3mm) | | Power Relays, Over 2 Amps |
| Relay Type Contactor Coil Type Non Latching Coil Current - Coil Voltage 24VAC Contact Form 3PST-NO-DM (3 Form X) Contact Rating (Current) 30A Switching Voltage 600VAC - Max Turn On Voltage (Max) 18 VAC Turn Off Voltage (Min) 6 VAC Operate Time - Release Time - Release Time - Features Insulation - Class B Mounting Type Chassis Mount Termination Style Serew Terminal, Quick Connect - 0.250" (6.3mm) | Package | - |
| Coil Type Non Latching Coil Current - Coil Voltage 24VAC Contact Form 3PST-NO-DM (3 Form X) Contact Rating (Current) 30A Switching Voltage 600VAC - Max Turn On Voltage (Max) 18 VAC Turn Off Voltage (Min) 6 VAC Operate Time - Release Time - Features Insulation - Class B Mounting Type Chassis Mount Termination Style Screw Terminal, Quick Connect - 0.250" (6.3mm) | Series | 3100, Products Unlimited |
| Coil Current Coil Voltage 24VAC Contact Form 3PST-NO-DM (3 Form X) Contact Rating (Current) 30A Switching Voltage 600VAC - Max Turn On Voltage (Max) 18 VAC Turn Off Voltage (Min) 6 VAC Operate Time - Release Time - Features Insulation - Class B Mounting Type Chassis Mount Termination Style Screw Terminal, Quick Connect - 0.250" (6.3mm) | Relay Type | Contactor |
| Coil Voltage 24VAC Contact Form 3PST-NO-DM (3 Form X) Contact Rating (Current) 30A Switching Voltage 600VAC - Max Turn On Voltage (Max) 18 VAC Turn Off Voltage (Min) 6 VAC Operate Time - Release Time - Release Time - Features Insulation - Class B Mounting Type Chassis Mount Termination Style Screw Terminal, Quick Connect - 0.250" (6.3mm) | Coil Type | Non Latching |
| Contact Form 3PST-NO-DM (3 Form X) Contact Rating (Current) 30A Switching Voltage 600VAC - Max Turn On Voltage (Max) 18 VAC Turn Off Voltage (Min) 6 VAC Operate Time - Release Time - Features Insulation - Class B Mounting Type Chassis Mount Termination Style Screw Terminal, Quick Connect - 0.250" (6.3mm) | Coil Current | - |
| Contact Rating (Current) Switching Voltage 600VAC - Max Turn On Voltage (Max) 18 VAC Turn Off Voltage (Min) 6 VAC Operate Time - Release Time - Features Insulation - Class B Mounting Type Chassis Mount Termination Style Screw Terminal, Quick Connect - 0.250" (6.3mm) | Coil Voltage | 24VAC |
| Switching Voltage 600VAC - Max Turn On Voltage (Max) 18 VAC Turn Off Voltage (Min) 6 VAC Operate Time - Release Time - Features Insulation - Class B Mounting Type Chassis Mount Termination Style Screw Terminal, Quick Connect - 0.250" (6.3mm) | Contact Form | 3PST-NO-DM (3 Form X) |
| Turn On Voltage (Max) 18 VAC Turn Off Voltage (Min) 6 VAC Operate Time - Release Time - Features Insulation - Class B Mounting Type Chassis Mount Termination Style 18 VAC 6 VAC - Connect - 0.250" (6.3mm) | Contact Rating (Current) | 30A |
| Turn Off Voltage (Min) 6 VAC Operate Time - Release Time - Features Insulation - Class B Mounting Type Chassis Mount Termination Style Screw Terminal, Quick Connect - 0.250" (6.3mm) | Switching Voltage | 600VAC - Max |
| Operate Time - Release Time - Features Insulation - Class B Mounting Type Chassis Mount Termination Style Screw Terminal, Quick Connect - 0.250" (6.3mm) | Turn On Voltage (Max) | 18 VAC |
| Release Time - Features Insulation - Class B Mounting Type Chassis Mount Termination Style Screw Terminal, Quick Connect - 0.250" (6.3mm) | Turn Off Voltage (Min) | 6 VAC |
| Features Insulation - Class B Mounting Type Chassis Mount Termination Style Screw Terminal, Quick Connect - 0.250" (6.3mm) | Operate Time | - |
| Mounting Type Chassis Mount Termination Style Screw Terminal, Quick Connect - 0.250" (6.3mm) | Release Time | - |
| Termination Style Screw Terminal, Quick Connect - 0.250" (6.3mm) | Features | Insulation - Class B |
| | Mounting Type | Chassis Mount |
| | Termination Style | Screw Terminal, Quick Connect - 0.250" (6.3mm) |
| Report errors? | | Report errors? |

3100-30Q9999CY Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

3100-30Q9999CY Payment Methods



















3100-30Q9999CY Shipping Methods













If you have any question about 3100-30Q9999CY, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com