

315-83-150-41-003101 Information



For Reference Only

Part Number 315-83-150-41-003101

Manufacturer Preci-Dip

Category Connectors, Interconnects

Rectangular Connectors - Headers, Receptacles,

Female Sockets

Description PCB CONN SOLDER TAIL LOW PRO

Package

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









315-83-150-41-003101 Specifications

Manufacturer Part Number 315-83-150-41-003101 Manufacturer Preci-Dip Category Connectors, Interconnects Package - Series 315 Connector Type Socket Contact Type Female Socket Style Board to Board Number of Positions 50 Number of Positions Loaded All Pitch - Mating 0.100" (2.54mm) Number of Rows 1 Row Spacing - Mating - Mounting Type Through Hole Testening Type Push-Pull Contact Finish - Mating Gold Contact Finish Thickness - Mating 29.5µin (0.75µm) Insulation Color Black Insulation Height 0.095" (2.41mm) Operating Temperature -55°C ~ 125°C Material Flammability Rating UL94 V-0		
Category Connectors, Interconnects Package - Series 315 Connector Type Socket Contact Type Female Socket Style Board to Board Number of Positions 50 Number of Positions Loaded All Pitch - Mating 0.100" (2.54mm) Number of Rows 1 Row Spacing - Mating - Mounting Type Through Hole Termination Solder Pastening Type Push-Pull Contact Finish - Mating Gold Contact Finish Thickness - Mating 29.5µin (0.75µm) Insulation Color Black Insulation Height 0.095" (2.41mm) Contact Length - Post 0.095" (2.41mm) Operating Temperature -55°C ~ 125°C	Manufacturer Part Number	315-83-150-41-003101
Rectangular Connectors - Headers, Receptacles, Female Sockets Package Series 315 Connector Type Socket Contact Type Female Socket Style Board to Board Number of Positions Number of Positions Loaded Pitch - Mating Number of Rows 1 Row Spacing - Mating - Mounting Type Through Hole Termination Solder Fastening Type Push-Pull Contact Finish - Mating Contact Finish Thickness - Mating Dush Thickness - Mating Row Spacing - Mating Contact Finish Thickness - Mating Solder Contact Finish Thickness - Mating Contact Finish Thickness - Mating Dush Color Black Insulation Color Black Insulation Height Contact Length - Post O.095" (2.41mm) Contact Length - Post O.095" (2.41mm) Contact Temperature Socket Female Socket Socket	Manufacturer	Preci-Dip Preci-Dip
Package - Series 315 Connector Type Socket Contact Type Female Socket Style Board to Board Number of Positions 50 Number of Positions Loaded All Pitch - Mating 0.100" (2.54mm) Number of Rows 1 Row Spacing - Mating - Mounting Type Through Hole Termination Solder Fastening Type Push-Pull Contact Finish - Mating Gold Contact Finish Thickness - Mating 29.5µin (0.75µm) Insulation Color Black Insulation Height 0.095" (2.41mm) Contact Length - Post 0.095" (2.41mm) Operating Temperature -55°C ~ 125°C	Category	Connectors, Interconnects
Series 315 Connector Type Socket Contact Type Female Socket Style Board to Board Number of Positions 50 Number of Positions Loaded All Pitch - Mating 0.100" (2.54mm) Number of Rows 1 Row Spacing - Mating - Mounting Type Through Hole Termination Solder Fastening Type Push-Pull Contact Finish - Mating Gold Contact Finish Thickness - Mating 29.5μin (0.75μm) Insulation Color Black Insulation Height 0.095" (2.41mm) Contact Length - Post 0.095" (2.41mm) Operating Temperature -55°C ~ 125°C		Rectangular Connectors - Headers, Receptacles, Female Sockets
Connector TypeSocketContact TypeFemale SocketStyleBoard to BoardNumber of Positions50Number of Positions LoadedAllPitch - Mating0.100" (2.54mm)Number of Rows1Row Spacing - Mating-Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating29.5μin (0.75μm)Insulation ColorBlackInsulation Height0.095" (2.41mm)Contact Length - Post0.095" (2.41mm)Operating Temperature-55°C ~ 125°C	Package	-
Contact TypeFemale SocketStyleBoard to BoardNumber of Positions50Number of Positions LoadedAllPitch - Mating0.100" (2.54mm)Number of Rows1Row Spacing - Mating-Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating29.5μin (0.75μm)Insulation ColorBlackInsulation Height0.095" (2.41mm)Contact Length - Post0.095" (2.41mm)Operating Temperature-55°C ~ 125°C	Series	315
StyleBoard to BoardNumber of Positions50Number of Positions LoadedAllPitch - Mating0.100" (2.54mm)Number of Rows1Row Spacing - Mating-Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating29.5µin (0.75µm)Insulation ColorBlackInsulation Height0.095" (2.41mm)Contact Length - Post0.095" (2.41mm)Operating Temperature-55°C ~ 125°C	Connector Type	Socket
Number of Positions50Number of Positions LoadedAllPitch - Mating0.100" (2.54mm)Number of Rows1Row Spacing - Mating-Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating29.5μin (0.75μm)Insulation ColorBlackInsulation Height0.095" (2.41mm)Contact Length - Post0.095" (2.41mm)Operating Temperature-55°C ~ 125°C	Contact Type	Female Socket
Number of Positions LoadedAllPitch - Mating0.100" (2.54mm)Number of Rows1Row Spacing - Mating-Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating29.5μin (0.75μm)Insulation ColorBlackInsulation Height0.095" (2.41mm)Contact Length - Post0.095" (2.41mm)Operating Temperature-55°C ~ 125°C	Style	Board to Board
Pitch - Mating0.100" (2.54mm)Number of Rows1Row Spacing - Mating-Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating29.5μin (0.75μm)Insulation ColorBlackInsulation Height0.095" (2.41mm)Contact Length - Post0.095" (2.41mm)Operating Temperature-55°C ~ 125°C	Number of Positions	50
Number of Rows1Row Spacing - Mating-Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating29.5μin (0.75μm)Insulation ColorBlackInsulation Height0.095" (2.41mm)Contact Length - Post0.095" (2.41mm)Operating Temperature-55°C ~ 125°C	Number of Positions Loaded	All
Row Spacing - Mating-Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating29.5μin (0.75μm)Insulation ColorBlackInsulation Height0.095" (2.41mm)Contact Length - Post0.095" (2.41mm)Operating Temperature-55°C ~ 125°C	Pitch - Mating	0.100" (2.54mm)
Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating29.5μin (0.75μm)Insulation ColorBlackInsulation Height0.095" (2.41mm)Contact Length - Post0.095" (2.41mm)Operating Temperature-55°C ~ 125°C	Number of Rows	1
Termination Solder Fastening Type Push-Pull Contact Finish - Mating Gold Contact Finish Thickness - Mating 29.5 μ in (0.75 μ m) Insulation Color Black Insulation Height 0.095" (2.41mm) Contact Length - Post 0.095" (2.41mm) Operating Temperature -55°C ~ 125°C	Row Spacing - Mating	-
Fastening Type Push-Pull Contact Finish - Mating Gold Contact Finish Thickness - Mating 29.5 μ in (0.75 μ m) Insulation Color Black Insulation Height 0.095" (2.41mm) Contact Length - Post 0.095" (2.41mm) Operating Temperature -55°C ~ 125°C	Mounting Type	Through Hole
Contact Finish - Mating Gold Contact Finish Thickness - Mating 29.5 μ in (0.75 μ m) Insulation Color Black Insulation Height 0.095" (2.41mm) Contact Length - Post 0.095" (2.41mm) Operating Temperature -55°C ~ 125°C	Termination	Solder
Contact Finish Thickness - Mating $29.5\mu in (0.75\mu m)$ Insulation Color Black Insulation Height $0.095" (2.41mm)$ Contact Length - Post $0.095" (2.41mm)$ Operating Temperature $-55^{\circ}C \sim 125^{\circ}C$	Fastening Type	Push-Pull
Insulation ColorBlackInsulation Height $0.095"$ (2.41mm)Contact Length - Post $0.095"$ (2.41mm)Operating Temperature $-55^{\circ}\text{C} \sim 125^{\circ}\text{C}$	Contact Finish - Mating	Gold
Insulation Height $0.095"$ (2.41mm)Contact Length - Post $0.095"$ (2.41mm)Operating Temperature $-55^{\circ}\text{C} \sim 125^{\circ}\text{C}$	Contact Finish Thickness - Mating	29.5μin (0.75μm)
Contact Length - Post 0.095 " (2.41mm) Operating Temperature -55 °C ~ 125 °C	Insulation Color	Black
Operating Temperature $-55^{\circ}\text{C} \sim 125^{\circ}\text{C}$	Insulation Height	0.095" (2.41mm)
	Contact Length - Post	0.095" (2.41mm)
Material Flammability Rating UL94 V-0	Operating Temperature	-55°C ~ 125°C
	Material Flammability Rating	UL94 V-0

Contact Finish - Post	Tin
Mated Stacking Heights	-
Ingress Protection	-
Features	-
	Report errors?

315-83-150-41-003101 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

315-83-150-41-003101 Payment Methods



















315-83-150-41-003101 Shipping Methods













If you have any question about 315-83-150-41-003101, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com