

# 315-87-135-41-003101

### 315-87-135-41-003101 Information

www.haseneo	Part Number Manufacturer	315-87-135-41-003101 Preci-Dip	
	Category	Connectors, Interconnects Rectangular Connectors - Headers, Receptacles, Female Sockets	
	Description	PCB CONN SOLDER TAIL LOW PRO	
	Package	-	回該支援
For Reference Only		For the pricing/inventory/lead time, please contact us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



## 315-87-135-41-003101 Specifications

Manufacturer Part Number315-87-135-41-003101ManufacturerPreci-DipCategoryConnectors, InterconnectsRectangular Connectors - Headers, Receptacles, Female SocketsPackage-Series315Connector TypeSocketContact TypeBoard to BoardNumber of Positions35Number of Positions LoadedAllPitch - Mating0.100° (2.54mm)Number of Rows1Number of RowsSolderTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish - MatingGoldContact Finish - MatingGoldContact Finish - Mating0.0095° (2.41mm)Contact Finish Thickness - MatingBlackInsulation Height0.095° (2.41mm)Contact Length - Post0.955° Ca '125°CMaterial Flanmability RatingUL94 V-0		
CategoryConnectors, InterconnectsRectangular Connectors - Headers, Receptacles, Female SocketsPackage-Series315Connector TypeSocketContact TypeBoard to BoardNumber of Positions35Number of Positions LoadedAllPrich - Mating0.100" (2.54mm)Number of Rows1Row Spacing - MatingSolderTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - MatingFlashInsulation ColorBlackInsulation Height0.095" (2.41mm)Contact Length - Post0.095" (2.41mm)Contact Length - Post0.095" (2.41mm)Contact Timeperature-55°C ~ 125°C	Manufacturer Part Number	315-87-135-41-003101
Package-Series315Connector TypeSocketContact TypeFemale SocketStyleBoard to BoardNumber of Positions35Number of Positions LoadedAllPitch - Mating0.100" (2.54mm)Number of Rows1Row Spacing - MatingSolderTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - MatingFlashInsulation ColorBlackInsulation Height0.095" (2.41mm)Contact Length - Post0.095" (2.41mm)Contact Funish ThicknesSinger CalarseInsulation Height0.095" (2.41mm)Contact Length - Post55°C ~ 125°C	Manufacturer	Preci-Dip
Package-Series315Connector TypeSocketContact TypeFemale SocketStyleBoard to BoardNumber of Positions35Number of Positions LoadedAllPitch - Mating0.100° (2.54mm)Number of Rows1Row Spacing - Mating-Mounting TypeThrough HoleTerminationSolderFastening TypeGoldContact Finish - MatingGoldContact Finish Thickness - MatingHashInsulation ColorBlackInsulation Height0.095° (2.41mm)Contact Length - Post0.95° (2.41mm)Operating Temperature55°C ~ 125°C	Category	Connectors, Interconnects
Series315Connector TypeSocketContact TypeFemale SocketStyleBoard to BoardNumber of Positions35Number of Positions LoadedAllPitch - Mating0.100" (2.54mm)Number of Rows1Row Spacing - Mating-Mounting TypeThrough HoleTerminationSolderFastening TypeGoldContact Finish - MatingFlashInsulation ColorBlackInsulation Height0.095" (2.41mm)Operating Temperature-55°C ~ 125°C		Rectangular Connectors - Headers, Receptacles, Female Sockets
Connector TypeSocketContact TypeFemale SocketStyleBoard to BoardNumber of Positions35Number of Positions LoadedAllPitch - Mating0.100" (2.54mm)Number of Rows1Row Spacing - Mating-Mounting TypeThrough HoleTerminationSolderFastening TypeOddContact Finish - MatingGoldInsulation ColorBackInsulation Height0.095" (2.41mm)Contact Length - PostSi%C ~ 125°C	Package	-
Contact TypeFemale SocketStyleBoard to BoardNumber of Positions35Number of Positions LoadedAllPitch - Mating0.100° (2.54mm)Number of Rows1Row Spacing - Mating-Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldInsulation ColorBlackInsulation Height0.095° (2.41mm)Contact Length - Post0.95°° (2.41mm)Operating Temperature-55°C ~ 125°C	Series	315
StyleBoard to BoardNumber of Positions35Number of Positions LoadedAllPitch - Mating0.100" (2.54mm)Number of Rows1Row Spacing - Mating-Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldInsulation ColorBlackInsulation Height0.095" (2.41mm)Operating Temperature-55°C ~ 125°C	Connector Type	Socket
Number of Positions 35   Number of Positions Loaded All   Pitch - Mating 0.100" (2.54mm)   Number of Rows 1   Row Spacing - Mating -   Mounting Type Through Hole   Termination Solder   Fastening Type Push-Pull   Contact Finish - Mating Gold   Contact Finish Thickness - Mating Flash   Insulation Color Black   Insulation Height 0.095" (2.41mm)   Operating Temperature -55°C ~ 125°C	Contact Type	Female Socket
Number of Positions LoadedAllPitch - Mating0.100" (2.54mm)Number of Rows1Row Spacing - Mating-Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - MatingBlackInsulation ColorBlackInsulation Height0.095" (2.41mm)Contact Length - Post55°C ~ 125°C	Style	Board to Board
Pitch - Mating0.100" (2.54mm)Number of Rows1Row Spacing - Mating-Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldRoust ColorBlackInsulation Color0.995" (2.41mm)Contact Length - Post0.995" (2.41mm)Operating Temperature55°C ~ 125°C	Number of Positions	35
Number of Rows1Row Spacing - Mating-Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - MatingFlashInsulation ColorBlackInsulation Height0.095" (2.41mm)Contact Length - Post55°C ~ 125°C	Number of Positions Loaded	All
Row Spacing - Mating-Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - MatingHashInsulation ColorBlackInsulation Height0.095" (2.41mm)Contact Length - Post55°C ~ 125°C	Pitch - Mating	0.100" (2.54mm)
Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - MatingFlashInsulation ColorBlackInsulation Height0.095" (2.41mm)Contact Length - Post0.095" (2.41mm)Operating Temperature-55°C ~ 125°C	Number of Rows	1
TerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - MatingFlashInsulation ColorBlackInsulation Height0.095" (2.41mm)Contact Length - Post0.095" (2.41mm)Operating Temperature-55°C ~ 125°C	Row Spacing - Mating	-
Fastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - MatingFlashInsulation ColorBlackInsulation Height0.095" (2.41mm)Contact Length - Post0.095" (2.41mm)Operating Temperature55°C ~ 125°C	Mounting Type	Through Hole
Contact Finish - MatingGoldContact Finish Thickness - MatingFlashInsulation ColorBlackInsulation Height0.095" (2.41mm)Contact Length - Post0.095" (2.41mm)Operating Temperature-55°C ~ 125°C	Termination	Solder
Contact Finish Thickness - MatingFlashInsulation ColorBlackInsulation Height0.095" (2.41mm)Contact Length - Post0.095" (2.41mm)Operating Temperature-55°C ~ 125°C	Fastening Type	Push-Pull
Insulation ColorBlackInsulation Height0.095" (2.41mm)Contact Length - Post0.095" (2.41mm)Operating Temperature-55°C ~ 125°C	Contact Finish - Mating	Gold
Insulation Height 0.095" (2.41mm)   Contact Length - Post 0.095" (2.41mm)   Operating Temperature -55°C ~ 125°C	Contact Finish Thickness - Mating	Flash
Contact Length - Post0.095" (2.41mm)Operating Temperature-55°C ~ 125°C	Insulation Color	Black
Operating Temperature $-55^{\circ}C \sim 125^{\circ}C$	Insulation Height	0.095" (2.41mm)
	Contact Length - Post	0.095" (2.41mm)
Material Flammability Rating UL94 V-0	Operating Temperature	-55°C ~ 125°C
	Material Flammability Rating	UL94 V-0

Contact Finish - Post	Tin
Mated Stacking Heights	-
Ingress Protection	-
Features	-
	Report errors?

### 315-87-135-41-003101 Guarantees



#### **Quality Guarantees**

We provide 90 days warranty. \* If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

# 315-87-135-41-003101 Payment Methods



If you have any question about 315-87-135-41-003101, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com