

315NH3G-690 Information

Heisener.com

Part Number 315NH3G-690

Manufacturer Eaton

Category Circuit Protection

Electrical, Specialty Fuses

Description FUSE SQ 315A 690VAC RECTANGULAR

Package Rectangular, Blade

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









315NH3G-690 Specifications

Manufacturer Part Number 315NH3G-690 Manufacturer Eaton Category Circuit Protection Package Rectangular, Blade Series - Fuse Type Square Current Rating 315A Voltage Rating - AC 690V Voltage Rating - DC - Response Time Fast Applications Electrical, Industrial Features Indicating Class NH Approvals CE, VDE Operating Temperature - Breaking Capacity @ Rated Voltage - Mounting Type Holder Package / Case Rectangular, Blade Size / Dimension 2.677" L x 2.835" W x 3.071" H (68.00mm x 72.00mm x 78.00mm) Report errors?		
Category Circuit Protection Electrical, Specialty Fuses Package Rectangular, Blade Series - Fuse Type Square Current Rating 315A Voltage Rating - AC 690V Voltage Rating - DC - Response Time Fast Applications Electrical, Industrial Features Indicating Class NH Approvals CE, VDE Operating Temperature - Breaking Capacity @ Rated Voltage - Mounting Type Holder Package / Case Rectangular, Blade Size / Dimension 2.677" L x 2.835" W x 3.071" H (68.00mm x 72.00mm x 78.00mm)	Manufacturer Part Number	315NH3G-690
PackageRectangular, BladeSeries-Fuse TypeSquareCurrent Rating315AVoltage Rating - AC690VVoltage Rating - DC-Response TimeFastApplicationsElectrical, IndustrialFeaturesIndicatingClassNHApprovalsCE, VDEOperating Temperature-Breaking Capacity @ Rated Voltage-Mounting TypeHolderPackage / CaseRectangular, BladeSize / Dimension2.677" L x 2.835" W x 3.071" H (68.00mm x 72.00mm x 78.00mm)	Manufacturer	Eaton
Package Rectangular, Blade Series - Fuse Type Square Current Rating 315A Voltage Rating - AC 690V Voltage Rating - DC - Response Time Fast Applications Electrical, Industrial Features Indicating Class NH Approvals CE, VDE Operating Temperature - Breaking Capacity @ Rated Voltage - Mounting Type Holder Package / Case Rectangular, Blade Size / Dimension 2.677" L x 2.835" W x 3.071" H (68.00mm x 72.00mm x 78.00mm)	Category	Circuit Protection
Series - Fuse Type Square Current Rating 315A Voltage Rating - AC 690V Voltage Rating - DC - Response Time Fast Applications Electrical, Industrial Features Indicating Class NH Approvals CE, VDE Operating Temperature - Breaking Capacity @ Rated Voltage - Mounting Type Holder Package / Case Rectangular, Blade Size / Dimension 2.677" L x 2.835" W x 3.071" H (68.00mm x 72.00mm x 78.00mm)		Electrical, Specialty Fuses
Fuse TypeSquareCurrent Rating315AVoltage Rating - AC690VVoltage Rating - DC-Response TimeFastApplicationsElectrical, IndustrialFeaturesIndicatingClassNHApprovalsCE, VDEOperating Temperature-Breaking Capacity @ Rated Voltage-Mounting TypeHolderPackage / CaseRectangular, BladeSize / Dimension2.677" L x 2.835" W x 3.071" H (68.00mm x 72.00mm x 78.00mm)	Package	Rectangular, Blade
Current Rating 315A Voltage Rating - AC 690V Voltage Rating - DC - Response Time Fast Applications Electrical, Industrial Features Indicating Class NH Approvals CE, VDE Operating Temperature - Breaking Capacity @ Rated Voltage - Mounting Type Holder Package / Case Rectangular, Blade Size / Dimension 2.677" L x 2.835" W x 3.071" H (68.00mm x 72.00mm x 78.00mm)	Series	-
Voltage Rating - AC Voltage Rating - DC Response Time Fast Applications Electrical, Industrial Indicating Class NH Approvals CE, VDE Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension 690V	Fuse Type	Square
Voltage Rating - DC Response Time Fast Applications Electrical, Industrial Features Indicating Class NH Approvals CE, VDE Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Rectangular, Blade Size / Dimension Fast F	Current Rating	315A
Response Time Fast Applications Electrical, Industrial Features Indicating Class NH Approvals CE, VDE Operating Temperature - Breaking Capacity @ Rated Voltage - Mounting Type Holder Package / Case Rectangular, Blade Size / Dimension 2.677" L x 2.835" W x 3.071" H (68.00mm x 72.00mm x 78.00mm)	Voltage Rating - AC	690V
Applications Electrical, Industrial Features Indicating Class NH Approvals CE, VDE Operating Temperature - Breaking Capacity @ Rated Voltage - Mounting Type Holder Package / Case Rectangular, Blade Size / Dimension 2.677" L x 2.835" W x 3.071" H (68.00mm x 72.00mm x 78.00mm)	Voltage Rating - DC	-
Features Indicating Class NH Approvals CE, VDE Operating Temperature - Breaking Capacity @ Rated Voltage - Mounting Type Holder Package / Case Rectangular, Blade Size / Dimension 2.677" L x 2.835" W x 3.071" H (68.00mm x 72.00mm x 78.00mm)	Response Time	Fast
Class NH Approvals CE, VDE Operating Temperature - Breaking Capacity @ Rated Voltage - Mounting Type Holder Package / Case Rectangular, Blade Size / Dimension 2.677" L x 2.835" W x 3.071" H (68.00mm x 72.00mm x 78.00mm)	Applications	Electrical, Industrial
Approvals CE, VDE Operating Temperature - Breaking Capacity @ Rated Voltage - Mounting Type Holder Package / Case Rectangular, Blade Size / Dimension CE, VDE - Rectangular, Blade 2.677" L x 2.835" W x 3.071" H (68.00mm x 72.00mm x 78.00mm)	Features	Indicating
Operating Temperature - Breaking Capacity @ Rated Voltage - Mounting Type Holder Package / Case Rectangular, Blade Size / Dimension 2.677" L x 2.835" W x 3.071" H (68.00mm x 72.00mm x 78.00mm)	Class	NH
Breaking Capacity @ Rated Voltage - Mounting Type Holder Package / Case Rectangular, Blade Size / Dimension 2.677" L x 2.835" W x 3.071" H (68.00mm x 72.00mm x 78.00mm)	Approvals	CE, VDE
Mounting Type Holder Package / Case Rectangular, Blade Size / Dimension 2.677" L x 2.835" W x 3.071" H (68.00mm x 72.00mm x 78.00mm)	Operating Temperature	-
Package / Case Rectangular, Blade Size / Dimension 2.677" L x 2.835" W x 3.071" H (68.00mm x 72.00mm x 78.00mm)	Breaking Capacity @ Rated Voltage	-
Size / Dimension 2.677" L x 2.835" W x 3.071" H (68.00mm x 72.00mm x 78.00mm)	Mounting Type	Holder
	Package / Case	Rectangular, Blade
Report errors?	Size / Dimension	2.677" L x 2.835" W x 3.071" H (68.00mm x 72.00mm x 78.00mm)
		Report errors?

315NH3G-690 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

315NH3G-690 Payment Methods



















315NH3G-690 Shipping Methods













If you have any question about 315NH3G-690, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com